

dentsu TRACKING

Dentsu Aegis Network
DATA DICTIONARY v1.4.4

This document details the Data Dictionary for EU Secondary Repository and Router.

Summary of changes

Date	Version	Done by	Comment
17.01.2019	0.1	Dentsu Aegis Network	Internal Draft
05.02.2019	0.2	Dentsu Aegis Network	First Draft shared with stakeholders
21.02.2019	1.0	Dentsu Aegis Network	First release
08.03.2019	1.1	Dentsu Aegis Network	Minor changes
28.03.2019	1.2	Dentsu Aegis Network	Minor changes
16.09.2019	1.3	Dentsu Aegis Network	Addition of the GS1 EPCIS, EDI interface. Improvement of the Validation and address field split.
16.10.2019	1.4	Dentsu Aegis Network	Addition of the validation error codes and the EventTimeLong field.
17.10.2019	1.4.1	Dentsu Aegis Network	Update of the Message Time Long. Update the definition of the Arrival validation in order to remove the FID control. Update the VAL_EVT_24H definition to a warning returning a Http status 299.
20.12.2019	1.4.2	Dentsu Aegis Network	Update EOID, FID and MID , Error codes
31.10.2020	1.4.3	Dentsu Aegis Network	Update of the country codes in preparation for Brexit. Consolidation of optional features into the main documents
15.04.2021	1.4.4 DRAFT	Dentsu Aegis Network	Clerical changes: - Moving the definition of the technical and the business validation from the list of specification to the Data Dictionary - IDA sample. - Augment the M_Producer, M_Model, M_Number to 200 characters.
21.05.2021	1.4.4 DRAFT2	Dentsu Aegis Network	Update of the sequence validation summary table.
15.06.2021	1.4.4	Dentsu Aegis Network	Update of the technical Regular expressions in the datatype table. Update the Error Data in the error description.

Distribution

Date	Version	Submitted to
05.02.2019	0.2	Mail to stakeholder
21.02.2019	1.0	Published
08.03.2019	1.1	Published
28.03.2019	1.2	Published
16.09.2019	1.3	Published
16.10.2019	1.4	Published
17.10.2019	1.4.1	Published

20.12.2019	1.4.2	Published
31.10.2020	1.4.3	Published
15.04.2021	1.4.4 DRAFT	Mail to Primary Providers and ID Issuer
21.05.2021	1.4.4 DRAFT2	Mail to Primary Providers and ID Issuer
15.06.2021	1.4.4	Published

Table of Contents

1	INTRODUCTION	8
2	DATA DESCRIPTION	9
2.1	DATA TYPES	9
2.2	PRIORITY TYPES	14
2.3	CARDINALITY TYPES	14
2.4	MINIMUM DATA MODEL	15
2.4.1	Event	15
2.4.2	Product	16
2.4.3	TobaccoProductItem	17
2.4.4	UniqueIdentifier	20
2.5	REGISTERED ENTITIES	20
2.5.1	EconomicOperator	20
2.5.2	Facility	23
2.5.3	ManufacturingMachine	24
2.6	MASTER DATA TYPES	25
2.6.1	Country Codes	25
2.6.2	DeactivationReasonType	29
2.6.3	EventState	30
2.6.4	EventType	30
2.6.5	FacilityType	31
2.6.6	InvoiceType	31
2.6.7	NotificationType	32
2.6.8	PaymentType	32
2.6.9	RecallReasonType	32
2.6.10	RegisterStatus	32
2.6.11	TobaccoProductType	32
2.6.12	TransportMode	33
2.6.13	UniqueIdentifierState	33
2.6.14	UniqueIdentifierType	33
3	MESSAGES	35
3.1	MESSAGE TYPES TO BE EXCHANGED	35
3.1.1	Optional II2MN II2DW interfaces	36
3.1.2	Message and endpoints	36
3.2	COMMON SCHEMA ELEMENTS	37
3.2.1	Basic information block concerning the request	37
3.2.2	Basic information block concerning the response	38
3.2.3	Basic Error block description	38
3.2.4	Response Information block	39
3.2.5	Empty array and null values	40
3.2.6	Decimal points	40
3.2.7	Common Error codes	40
3.3	MESSAGE VALIDATION	41
3.3.1	Overview	41
3.3.2	Timestamps	44
3.3.3	Type of validation	45
3.3.4	Validation Scope	57
3.3.5	Validation Responsibility	58
3.3.6	Validation and Error Code	59
3.3.7	Transition Period Validation	60
3.3.8	Sequence Validation Grace Period	61
3.3.9	Secondary repository special processing of technical historical data.	63
3.4	IDENTIFIER CODES FOR ECONOMIC OPERATORS, FACILITIES AND MACHINES MESSAGES	65

3.4.1	REO - (1.1) Registration of an Economic operator	66
3.4.2	REOD - Data Registration of an Economic operator.....	68
3.4.3	CEO - (1.2) Correction for an economic operator identifier code.....	72
3.4.4	DEO - (1.3) De-registration of economic operator identifier code.....	75
3.4.5	RFA - (1.4) Request for a facility identifier code	77
3.4.6	RFAD - Data Registration for a facility identifier code	80
3.4.7	CFA - (1.5) Correction of information concerning the facility identifier code.....	83
3.4.8	DFA - (1.6) De-registration of facility identifier code	86
3.4.9	RMA - (1.7) Request for a machine identifier code	87
3.4.10	RMAD- Data Request for a machine identifier code	89
3.4.11	CMA - (1.8) Correction of information concerning the machine identifier code	91
3.4.12	DMA - (1.9) De-registration of machine identifier code	92
3.4.13	ICV - Validate existence of EOID, FID and the MID.	95
3.5	UNIQUE IDENTIFIERS MESSAGES	98
3.5.1	ISU - (2.1) Request for unit level UIs	98
3.5.2	IRU - Message to report the issuance of serial numbers at unit packet level	100
3.5.3	IRUD - Message to report the issuance of serial numbers at unit packet level callback	104
3.5.4	ISA - (2.2) Request for aggregated level UIs	105
3.5.5	IRA - Request for reporting the issuance of serial numbers at aggregated level	106
3.5.6	IDA - (2.3) Request for deactivation of UIs	108
3.5.7	ICM - Validate the delivery of an IRU message.....	112
3.6	REPORTING OPERATIONAL EVENTS (PRODUCT MOVEMENT INFORMATION)	114
3.6.1	EUA - (3.1) Application of unit level UIs on unit packets	114
3.6.2	EPA - (3.2) Application of aggregated level UIs on aggregated packaging	116
3.6.3	EDP - (3.3) Dispatch of tobacco products from a facility	120
3.6.4	ERP - (3.4) Arrival of tobacco products at a facility	129
3.6.5	ETL - (3.5) Trans-loading	134
3.6.6	EUD - (3.6) Disaggregation of aggregated level UIs	138
3.6.7	EVR - (3.7) Report the delivery carried out with a vending van to retail outlet	142
3.7	EPCIS REPORTING OPERATIONAL EVENTS (PRODUCT MOVEMENT INFORMATION)	146
3.7.1	General.....	146
3.7.2	EPCIS - EUA - (3.1) Application of unit level UIs on unit packets	147
3.7.3	EPCIS - EPA - (3.2) Application of aggregated level UIs on aggregated packaging	149
3.7.4	EPCIS - EDP - (3.3) Dispatch of tobacco products from a facility	154
3.7.5	EPCIS - ERP - (3.4) Arrival of tobacco products at a facility	158
3.7.6	EPCIS - ETL - (3.5) Trans-loading.....	160
3.7.7	EPCIS - EUD - (3.6) Disaggregation of aggregated level UIs.....	164
3.7.8	EPCIS - EVR - (3.7) Report the delivery carried out with a vending van to retail outlet	168
3.8	REPORTING TRANSACTIONAL EVENTS (TRADE INFORMATION)	171
3.8.1	EIV - (4.1) Issuing of the invoice.....	171
3.8.2	EPO - (4.2) Issuing of the order number.....	173
3.8.3	EPR - (4.3) Receipt of the payment.....	176
3.9	EDI - REPORTING TRANSACTIONAL EVENTS (TRADE INFORMATION).....	179
3.9.1	EDI - EIV - (4.1) Issuing of the invoice.....	179
3.9.2	EDI - EPO - (4.2) Issuing of the order number.....	186
3.9.3	EDI - EPR - (4.3) Receipt of the payment.....	189
3.10	RECALL	194
3.10.1	RCL - (5.0) Recalls of requests, operational and transactional messages	194
3.11	EPCIS - RECALL	196

3.11.1 EPCIS - RCL – (5) Recalls of requests, operational messages	196
3.12 MANUFACTURER INTERFACE	198
3.12.1 LDI Lookup Dispatch Interface.....	198
4 LIST OF ERROR CODES.....	205
4.1 SECURITY ERRORS.....	205
4.2 PROCESSING ERRORS	205
4.3 VALIDATION WARNING.....	208
4.4 VALIDATION ERRORS	209

Table of Figures

Figure 1 Validation Overview	42
Figure 2 EU secondary validation system diagram	43
Figure 3 Implicit disaggregation triggered by EDP (3.3)	51
Figure 4 Implicit disaggregation triggered by EVR (3.7)	51
Figure 5 Transition warning diagram	61
Figure 6 Implicit disaggregation triggered by a IDA Deact_Reason1 = 1 or 2 ..	109
Figure 7 Implicit disaggregation triggered by a IDA Deact_Reason1 = 3,4,5 or 6	110
Figure 8 Implicit disaggregation triggered by an EPA (3.2) event	119
Figure 9 Arrival sequence error ARRIVAL_NOTALLOWED	132
Figure 10 Arrival sequence error UI_SEQUENCE_ERROR	133
Figure 11 reporting of disaggregation event on aUI that are implicitly disaggregated.	140
Figure 12 Implicit disaggregation trigger	144

1 Introduction

This document defines a data dictionary for Dentsu Tracking System. It will include information about data base entities and flows, authentication, operational and transactional methods, security edge case, router definition, error messages, registration process, message validation and an overall connection diagram.

Note: For the description of the Repositories system components, architecture, processes, data flows, list of interfaces and messages, see the List of Specifications document.

2 Data description

2.1 Data types

There are some types used along the document, which need to be defined.

Data Type	Description	Type	Example or regular expression
ARC	Administrative Reference Code (ARC) or any successive code adopted under the Excise Movement and Control System (EMCS)	Text(30)	'15GB0123456789ABCDEF0' Validation RegEx: <code>^[a-zA-Z0-9]*\$</code>
aUI	Aggregated level unique identifier coded with: either The invariant set of ISO646:1991 and composed of four blocks: (a) ID issuer's prefix in accordance with ISO15459-2:2015, (b) serialization element in the format established by the ID issuer, (c) tobacco facility identifier code following the Data Type: FID and (d) timestamp following the Data Type: Time(s) or The invariant set of ISO646:1991 forming a code structured in accordance with ISO15459-1:2014 or ISO15459-4:2014 (or their latest equivalent))	Text(100)	
Boolean	Boolean value	Boolean	• 0 (false/disabled) • 1 (true/enabled)
Component	A data type defined in the data dictionary		Aggregation
Country	Country name coded with ISO-3166-1:2013 alpha-2 (or its latest equivalent)	Text(2)	'DE'

Currency	Currency name coded with ISO 4217:2015 (or its latest equivalent)	Text(3)	'EUR'
Date	A UTC data in text corresponding to the following format: YYYY-MM-DD	Text(10)	E.g. '2017-03-31'
Decimal	Number values, decimal allowed	Decimal	E.g. '1' or '22.2' or '333.33'
Email	Maximum 80 characters	Text(80)	E.g. 'info@test.com' Validation RegEx: <pre>^((([a-zA-Z] \d [\!#\\$\%&'*\+\-\./=\?\^_`\{\}\ \~]) [\u00A0-\uD7FF\uF900-\uFDCF\uFDF0-\uFFEF])+(\.([a-zA-Z] \d [\!#\\$\%&'\*\+\-\./=\?\^\_`\{\}\ \~]) [\u00A0-\uD7FF\uF900-\uFDCF\uFDF0-\uFFEF])+)*) ((\x22)((((\x20 \x09)*(\x0d\x0a))?(\x20 \x09)+)?(([\x01-\x08\x0b\x0c\x0e-\x1f\x7f] \x21 [\x23-\x5b] [\x5d-\x7e] [\u00A0-\uD7FF\uF900-\uFDCF\uFDF0-\uFFEF]) (\\[\\([\x01-\x09\x0b\x0c\x0d-\x7f] [\u00A0-\uD7FF\uF900-\uFDCF\uFDF0-\uFFEF]))))*(((\x20 \x09)*(\x0d\x0a))?(\x20 \x09)+)?(\x22))@((([a-z] \d [\u00A0-\uD7FF\uF900-\uFDCF\uFDF0-</pre>

			<pre> \uFFEF])([a-z] \d - \. _ ~ [\u00A0- \uD7FF\uF900- \uFDCF\uFDF0- \uFFEF])*([a- z] \d [\u00A0- \uD7FF\uF900- \uFDCF\uFDF0- \uFFEF]))\.)+((([a- z] \u00A0- \uD7FF\uF900- \uFDCF\uFDF0- \uFFEF) ((([a- z] \u00A0- \uD7FF\uF900- \uFDCF\uFDF0- \uFFEF])([a-z] \d - \. _ ~ [\u00A0- \uD7FF\uF900- \uFDCF\uFDF0- \uFFEF])*([a- z] \u00A0- \uD7FF\uF900- \uFDCF\uFDF0- \uFFEF])))\.?\$ </pre>
EOID	Economic operator identifier code corresponding to the format established by ID issuer coded with the invariant set of ISO8859-15:1999 EOID starts with the alphanumeric characters that constitute the ID issuer identification code, followed by alphanumeric sequence which is unique within the code pool of the ID issuer.	Text(50)	
EO_CODE	EO_CODE established by ID issuer coded with the invariant set of ISO8859-15:1999	Text(50)	
FID	Tobacco facility identifier code corresponding to the	Text(50)	

	format established by ID issuer coded with the invariant set of ISO8859-15:1999		
Integer	Rounded number values, no decimal numbers	Integer	E.g. '1' or '22' or '333'
IIID	ID Issuer code in line with the issuing agency codes of ISO/IEC 15459	Text(35)	E.g. 'FTR'
ITU	Individual transport unit code (e.g. SSCC) generated in accordance with ISO15459-1:2014 (or its latest equivalent)		'00791234560000000018'
List	Must be only one of the values present in the 'Values' column		
MID	Machine identifier code corresponding to the format established by ID Issuer coded with the invariant set of ISO8859-15:1999	Text(50)	
MRN	Movement Reference Number (MRN) is a unique customs registration number. It contains 18 digits and is composed of the following elements: (a) last two digits of the year of formal acceptance of export movement (YY), (b) country name coded with ISO3166-1:2013 alpha-2 (or its latest equivalent) of the Member State to which the declaration was sent, (c) unique identifier for entry/import per year and country, and (d) check digit.	Text(18)	'19IT9876AB88901235' Validation RegEx: <code>^[0-9]{2}[A-Z]{2}[a-zA-Z0-9]+[0-9]{1}\$</code>
PN	Product number – numeric identifier used in the EUCEG system to identify product presentations (e.g. GTIN	Text(30)	'00012345600012'

	(Global Trade Identification Number) of the product)		
SEED	Excise number composed of: (a) country name coded with ISO-3166-1:2013 alpha-2 (or its latest equivalent) (e.g. 'LU') and (b) eleven alphanumeric characters, if needed, padded to the left with zeroes (e.g. '00000987ABC').	Text(13)	'LU00000987ABC' Validation RegEx: <code>^[A-Z]{2}[a-zA-Z0-9]{11}\$</code>
Serial	Number corresponding with the invariant set of ISO646:1991 used for serialisation		
SSCC	SSCC-18 container code generated in line with ISO6346:1995 (or its latest equivalent)	Text(20)	00791234560000000018
Text (X)	Alphanumeric values coded with ISO8859-15:1999 limited to X characters		E.g. 'Abcd' or '123455588845'
Time(s)	UTC (Coordinated Universal Time) time in the following format: YYMMDDhh	Text(8)	'19071619'
Time(L)	UTC (Coordinated Universal Time) time in the following format: YYYY-MM-DDThh:mm:ssZ	Text(34)	E.g. '2020-03-31T23:16:45Z'
Time(ms)	Time(ms) format format : yyyy-MM-ddTHH:mm:ss.fffZ		E.g. '2020-08-13T16:01:34.477Z'
TPID	Tobacco Product Identifier (TP-ID) – numeric identifier used in the EU-CEG system in the format: NNNNN-NN-NNNN	Text(14)	'02565-16-00230' Validation RegEx: <code>^[0-9]{5}-[0-9]{2}-[0-9]{5}\$</code>
upUI(L)	Unit packet level unique identifier coded with the invariant set of ISO646:1991 and composed of three blocks: (a) ID Issuer's prefix		

	in line with ISO154592:2015, (b) middle block in the format established by ID Issuer and (c) timestamp following the Data Type: Time(s)		
upUI(s)	Unit packet level unique identifier coded with the invariant set of ISO646:1991 and composed of two blocks: (a) ID Issuer's prefix in line with ISO154592:2015 and (b) serialisation element in the format established by ID issuer (i.e. UI made visible in the human readable format on the unit packets)		

2.2 Priority types

Type	Explanation
Mandatory (M)	The variable must be completed.
Optional (O)	The variable is for optional fields which could be filled depending on the record status or type.


2.3 Cardinality types

Type	Explanation
Simple (S)	Single value
Multiple (M)	Multiple values

2.4 Minimum Data model

The minimal data model describes the contents, format, and structure of a database and the relationship between its different elements.

Note: the Minimum Data Model may be extended.



2.4.1 Event

Field	Description	Data Type	Mandatory	Comments
Id (PK)	Internal identification number of this event	Integer	M	
StateID	The state of the event	EventState ID	M	EventState Type

TypeID	The type of the event	EventType ID	M	EventType Type
EventDateTime	Date and Time when the event occurs	Time(L)	M	
Content	Full content of the event.	Component	M	

2.4.2 Product

Field	Description	Data Type	Mandatory	Comments
Id (PK)	Internal identification number. This number is generated by the ID Issuer	Text(4)	M	
EO_ID (FK)	Economic operator identifier code of the submitting entity (either EU manufacturer or EU importer)	EOID	M	
F_ID	Facility identifier code	FID	M	
Process_Type	Indication if the production process involves machinery	Boolean	M	0 – No (only for fully hand made products) 1 – Yes
M_ID	Machine identifier code	MID	O	
P_Type	Type of tobacco product	Integer	M	See TobaccoProductType
P_OtherType	Description of other type of tobacco product	Text(200)	M, if P_Type = 11 (other tobacco product)	
P_CN	Combined Nomenclature (CN) code	Text(200)	O	
P_weight	Average gross weight of unit packet, including packaging, in grams with 0,1 gram accuracy	Decimal	M	
P_Brand	Brand of tobacco product	Text(200)	M	
TP_ID	The identification number of the product used in the EU-CEG system.	TPID	M, if Intended_Market is an EU country	

TP_PN	Tobacco product number used in the EU-CEG system	PN	M, if Intended_Market is an EU country	
Intended_Market	Intended country of retail sale.	Country	M	
Intended_Route1	Indication if the product is intended to be moved across country borders with terrestrial transport.	Boolean	M	0 – No 1 – Yes
Intended_Route2	The first country of terrestrial transport after the product leaves the Member State of manufacturing or the Member State of importation.	Country	M, if Intended_Route1 = 1	
Import	Indication if the product is imported into the EU	Boolean	M	0 – No 1 – Yes
Req_Quantity	Requested quantity of unit packet level UIs	Integer	M	
P_OtherID	Optional Product ID	Text(20)	O	

2.4.3 TobaccoProductItem

Field	Description	Data Type	Mandator y	Comments
Id (PK)	The identification code (i.e. unique identifier) of the product item as required by Article 15(2)	upUI(L)	M	
ProductId (FK)	The identification code of the product	Product Id	M	
ManufacturerId (FK)	Identifier of the manufacturer of this tobacco product	MID	M	
ImporterId (FK)	The identifier of the importer into the Union, if applicable	EOID		

ManufacturingMachine_ Id (FK)	The identifier of the manufacturing machine	Manufacturing Machine MID	M	
FacilityId (FK)	The identifier of the manufacturing facility. This date is the one used for requesting the issuance of codes.	Facility FID	M	
IntendedMarket	Intended country of retail sale	Country	M	
IsCrossBorder	Indication if the product is intended to be moved across country borders with terrestrial transport	Boolean	M	0 – No 1 – Yes
IntendedRoute	The first country of terrestrial transport after the product leaves the Member State of manufacturing or the Member State of importation	Country		M, if Intended_Route 1 = 1
IsImport	Indication if the product is imported into the EU	Boolean	M	0 – No 1 – Yes
ManufacturingDate	Date of manufacturing. This date is the one used for requesting the issuance of codes	Time(s)	M	
Serial	Serial number provided by the ID Issuer	Serial	M	
ShortIdentifier	Short unique identifier	upUI(s)		

2.4.4 UniqueIdentifier

Field	Description	Data Type	Mandatory	Comments
ID (PK)	Unique identifier of the unit packets or aggregated packaging level	Text(50)	M	
State	The state of the unique identifier	UniqueIdentifier State ID	M	UniqueIdentifier State Type
Type	The type of the unique identifier	UniqueIdentifier Type ID	M	UniqueIdentifier Type Type
GenerationRequestedOn	Date and Time when the generation was requested	Time (L)	M	
AnticipatedUsageOn	Date and Time when the generator intends to use it	Time (L)	M	
IssuerNotificationTime	Date and Time when the generation was notified to the storage	Time(L)	M	
ParentId	The identifier of the parent element that contains this item	UniqueIdentifier ID	O	

2.5 Registered entities

2.5.1 EconomicOperator

Field	Description	Data Type	Mandatory	Comments
Id (PK)	Economic operator's registered ID	EOID	M	
CreatedOn	Timestamp when the registration has been accomplished	Time(L)	M	
LastUpdatedOn	Timestamp of the last change on the register	Time(L)		
RegisterStatus	Status of the registration	Integer	M	RegisterStatus Type
Issuer	Identification number of the ID Issuer solution that has processed the registration	IIID	M	
EO_Name1	Economic operator's registered name	Text(100)	M	
EO_Name2	Economic operator's alternative or abridged name	Text(100)	O	
EO_Address	Economic operator's address – street name, house number, postal code, city	Text(300)	M	
EO_CountryReg	Economic operator's country of registration	Country	M	See Country
EO_Email	Economic operator's email address; used to inform about registration process, incl. subsequent changes and other required correspondence	Text(5000) (Regex protected)	M	
VAT_R	Indication of the VAT registration status	Boolean	M	– No VAT registration – VAT number exists

VAT_N	Economic operator's VAT number	Text(20)	M, if VAT_R = 1	
TAX_N	Economic operator's tax registration number	Text(20)	M, if VAT_R = 0	
EO_ExciseNumber1	Indication if the economic operator has an excise number issued by the competent authority for the purpose of identification of persons/premises	Boolean	M	– No SEED number – SEED number exists
EO_ExciseNumber2	Economic operator's excise number issued by the competent authority for the purpose of identification of persons/premises	SEED	M, if EO_ExciseNumber1 = 1	
OtherEOID_R	Indication if the economic operator has been allocated an identifier by another ID Issuer	Boolean	M	– No – Yes
OtherEOID_N	Economic operator identifier codes allocated by other ID Issuers	Text(5000)	M, if OtherEOID_R = 1	List of EOIDs
Reg_3RD	Indication if the registration is made on behalf of a retail outlet operator not otherwise involved in the tobacco trade	Boolean	M	– No – Yes
Reg_EOID	Identifier of the economic operator that acts on behalf of a retail outlet operator not otherwise	EOID	M, if Reg_3RD = 1	

	involved in the tobacco trade			
EO_OtherID	Optional identifier	Text(50)	O	
EO_CODE	Economic operator's confirmation code provided in response to the registration of economic operator	EO_CODE	M	

2.5.2 Facility

Field	Description	Data Type	Mandatory	Comments
EO_ID(FK)	Economic operator identifier code	EOID	M	
F_ID (PK)	Facility code from the RFA code issuer call	FID	M	
CreatedOn	Timestamp when the registration has been accomplished	Time(L)	M	
LastUpdatedOn	Timestamp of the last change on the register	Time(L)		
RegisterStatus	Status of the registration	Integer	M	RegisterStatus Type
EO_CODE	Economic operator's confirmation code provided in response to the registration of economic operator	EO_CODE	M	
F_Country	Facility's country	Country	M	See Country
F_Type	Type of facility	Integer	M	See FacilityType
F_Type_Other	Description of other facility type	Text(5000)	O	
F_Status	Indication if a part of the facility has a bonded warehouse status	Boolean	M	0 - No 1 - Yes

F_ExciseNumber1	Indication if the facility has an excise number issued by the competent authority for the purpose of identification of persons/premises	Boolean	M	0 - No SEED number 1 - SEED number exists
F_ExciseNumber2	Facility's excise number issued by the competent authority for the purpose of identification of persons/premises	SEED	O	
OtherFID_R	Indication if the facility has been allocated an identifier by another ID Issuer	Boolean	M	0 - No 1 - Yes (possible only for non-EU facilities)
OtherFID_N	Facility identifier codes allocated by other ID Issuers	Text(5000)	M, if OtherFID_R = 1	List of FID
Reg_3RD	Indication if the registration is made on behalf of a retail outlet operator not otherwise involved in the tobacco trade	Boolean	M	0 - No 1 - Yes (possible only if F_Type = 3)
Reg_EOID	Identifier of the economic operator that acts on behalf of a retail outlet operator not otherwise involved in the tobacco trade	EOID	M, if Reg_3RD = 1	

2.5.3 ManufacturingMachine

Field	Description	Data Type	Mandatory	Comments
M_ID (PK)	Machine identifier received from the RMA request made to the code issuer.	MID	M	
F_ID (FK)	Facility identifier code	FID	M	
CreatedOn	Timestamp when the registration has been accomplished	Time(L)	M	
LastUpdatedOn	Timestamp of the last change on the register	Time(L)		

Status	Status of the registration	Integer	M	RegisterStatus Type
M_Producer	Machine producer	Text(20)	M	
M_Model	Machine model	Text(20)	M	
M_Number	Machine serial number	Text(20)	M	
M_Capacity	Maximum capacity over 24hour production cycle expressed in unit packets	Integer	M	

2.6 Master Data Types

2.6.1 Country Codes

Code	Value
AD	Andorra
AE	United Arab Emirates
AF	Afghanistan
AG	Antigua and Barbuda
AI	Anguilla
AL	Albania
AM	Armenia
AO	Angola
AQ	Antarctica
AR	Argentina
AS	American Samoa
AT	Austria
AU	Australia
AW	Aruba
AX	Åland Islands
AZ	Azerbaijan
BA	Bosnia and Herzegovina
BB	Barbados
BD	Bangladesh
BE	Belgium
BF	Burkina Faso
BG	Bulgaria
BH	Bahrain
BI	Burundi
BJ	Benin
BL	Saint Barthélemy
BM	Bermuda
BN	Brunei Darussalam
BO	Bolivia (Plurinational State of)
BQ	Bonaire, Sint Eustatius and Saba
BR	Brazil
BS	Bahamas
BT	Bhutan
BV	Bouvet Island
BW	Botswana
BY	Belarus
BZ	Belize
CA	Canada

CC	Cocos (Keeling) Islands
CD	Congo, Democratic Republic of the
CF	Central African Republic
CG	Congo
CH	Switzerland
CI	Côte d'Ivoire
CK	Cook Islands
CL	Chile
CM	Cameroon
CN	China
CO	Colombia
CR	Costa Rica
CU	Cuba
CV	Cabo Verde
CW	Curaçao
CX	Christmas Island
CY	Cyprus
CZ	Czechia
DE	Germany
DJ	Djibouti
DK	Denmark
DM	Dominica
DO	Dominican Republic
DZ	Algeria
EC	Ecuador
EE	Estonia
EG	Egypt
EH	Western Sahara
ER	Eritrea
ES	Spain
ET	Ethiopia
FI	Finland
FJ	Fiji
FK	Falkland Islands (Malvinas)
FM	Micronesia (Federated States of)
FO	Faroe Islands
FR	France
GA	Gabon
GB	United Kingdom of Great Britain and Northern Ireland
GD	Grenada
GE	Georgia
GF	French Guiana
GG	Guernsey
GH	Ghana
GI	Gibraltar
GL	Greenland
GM	Gambia
GN	Guinea
GP	Guadeloupe
GQ	Equatorial Guinea
GR	Greece
GS	South Georgia and the South Sandwich Islands
GT	Guatemala
GU	Guam

GW	Guinea-Bissau
GY	Guyana
HK	Hong Kong
HM	Heard Island and McDonald Islands
HN	Honduras
HR	Croatia
HT	Haiti
HU	Hungary
ID	Indonesia
IE	Ireland
IL	Israel
IM	Isle of Man
IN	India
IO	British Indian Ocean Territory
IQ	Iraq
IR	Iran (Islamic Republic of)
IS	Iceland
IT	Italy
JE	Jersey
JM	Jamaica
JO	Jordan
JP	Japan
KE	Kenya
KG	Kyrgyzstan
KH	Cambodia
KI	Kiribati
KM	Comoros
KN	Saint Kitts and Nevis
KP	Korea (Democratic People's Republic of)
KR	Korea, Republic of
KW	Kuwait
KY	Cayman Islands
KZ	Kazakhstan
LA	Lao People's Democratic Republic
LB	Lebanon
LC	Saint Lucia
LI	Liechtenstein
LK	Sri Lanka
LR	Liberia
LS	Lesotho
LT	Lithuania
LU	Luxembourg
LV	Latvia
LY	Libya
MA	Morocco
MC	Monaco
MD	Moldova, Republic of
ME	Montenegro
MF	Saint Martin (French part)
MG	Madagascar
MH	Marshall Islands
MK	Macedonia, the former Yugoslav Republic of
ML	Mali
MM	Myanmar
MN	Mongolia

MO	Macao
MP	Northern Mariana Islands
MQ	Martinique
MR	Mauritania
MS	Montserrat
MT	Malta
MU	Mauritius
MV	Maldives
MW	Malawi
MX	Mexico
MY	Malaysia
MZ	Mozambique
NA	Namibia
NC	New Caledonia
NE	Niger
NF	Norfolk Island
NG	Nigeria
NI	Nicaragua
NL	Netherlands
NO	Norway
NP	Nepal
NR	Nauru
NU	Niue
NZ	New Zealand
OM	Oman
PA	Panama
PE	Peru
PF	French Polynesia
PG	Papua New Guinea
PH	Philippines
PK	Pakistan
PL	Poland
PM	Saint Pierre and Miquelon
PN	Pitcairn
PR	Puerto Rico
PS	Palestine, State of
PT	Portugal
PW	Palau
PY	Paraguay
QA	Qatar
RE	Réunion
RO	Romania
RS	Serbia
RU	Russian Federation
RW	Rwanda
SA	Saudi Arabia
SB	Solomon Islands
SC	Seychelles
SD	Sudan
SE	Sweden
SG	Singapore
SH	Saint Helena, Ascension and Tristan da Cunha
SI	Slovenia
SJ	Svalbard and Jan Mayen
SK	Slovakia

SL	Sierra Leone
SM	San Marino
SN	Senegal
SO	Somalia
SR	Suriname
SS	South Sudan
ST	Sao Tome and Principe
SV	El Salvador
SX	Sint Maarten (Dutch part)
SY	Syrian Arab Republic
SZ	Eswatini
TC	Turks and Caicos Islands
TD	Chad
TF	French Southern Territories
TG	Togo
TH	Thailand
TJ	Tajikistan
TK	Tokelau
TL	Timor-Leste
TM	Turkmenistan
TN	Tunisia
TO	Tonga
TR	Turkey
TT	Trinidad and Tobago
TV	Tuvalu
TW	Taiwan, Province of China
TZ	Tanzania, United Republic of
UA	Ukraine
UG	Uganda
UM	United States Minor Outlying Islands
US	United States of America
UY	Uruguay
UZ	Uzbekistan
VA	Holy See
VC	Saint Vincent and the Grenadines
VE	Venezuela (Bolivarian Republic of)
VG	Virgin Islands (British)
VI	Virgin Islands (U.S.)
VN	Viet Nam
VU	Vanuatu
WF	Wallis and Futuna
WS	Samoa
YE	Yemen
XI	Northern Ireland
YT	Mayotte
ZA	South Africa
ZM	Zambia
ZW	Zimbabwe

2.6.2 DeactivationReasonType

Value	Name
1	Product destroyed
2	Product stolen

3	UI destroyed
4	UI stolen
5	UI unused
6	Other

2.6.3 EventState

Value	Name	Description
1	Received	Initial state. The Data Acquisition component has just received the event and stores it.
2	Valid	The Data Processing component has verified that the format and contents are correct.
3	Invalid	The Data Processing component has found some issues regarding the format or the contents. Event is promoted to invalid for further analysis by the storage provider.
4	Routed	The Data Processing component has routed (or copied) successfully the event to the other Data Storage.
5	ConsolidationInProgress	The Data Processing attempts to consolidate the information included in the event, if possible.
6	Consolidated	If the consolidation has been done, it is then promoted to Consolidated.
7	Orphaned	If the consolidation has not been possible because some prior events were missing, it is promoted to Orphaned.
8	Cancelled	Final state if the System receives a recall message regarding this event.

2.6.4 EventType

Value	Name
REO	Registration of an Economic operator
REOD	Registration Data of an Economic operator
CEO	Correction for an economic operator identifier code
DEO	De-registration of economic operator identifier code
RFA	Request for a facility identifier code
RFAD	Data for a facility identifier code
CFA	Correction of information concerning the facility identifier code
DFA	De-registration of facility identifier code
RMA	Request for a machine identifier code
RMAD	Data for a machine identifier code
CMA	Correction of information concerning the machine identifier code
DMA	De-registration of machine identifier code
ICV	Identifier code verification

ICM	Validation of the IRU Message successful transmission to the Primary repository
ULO	Flat file and registry File upload
PLO	Partial Flat file and registry transmission
ISU	Request for unit level UIs
IRU	Response for unit level UIs
ISA	Request for reporting the issuance of serial numbers at aggregated level
IRA	Response for reporting the issuance of serial numbers at aggregated level
IDA	Request for deactivation of UIs
EUA	Application of unit level UIs on unit packets
EPA	Application of aggregated level UIs on aggregated packaging
EDP	Dispatch Event
ERP	Reception event
ETL	Trans-loading event
EUD	Message to report an UI disaggregation
EVR	Report the delivery carried out with a vending van to retail outlet
EIV	Message to report an invoice
EPO	Purchase order
EPR	Payment record
RCL	Recall messages
LUP	Download Offline flat file
CTM	Connectivity Test Messages

2.6.5 FacilityType

Value	Name
1	Manufacturing site with warehouse
2	Standalone warehouse
3	First retail outlet
4	Other

2.6.6 InvoiceType

Value	Name
1	Original

2	Correction
3	Other

2.6.7 NotificationType

Value	Name	Description
1	Informative	The notification only includes descriptive information, but not related to any error or abnormal situation.
2	Warning	The notification includes information about some alert or warning to be considered.
3	Alarm	The notification includes information about some alarm triggered by the System.
4	InternalError	The notification includes information about some error that has occurred within the System.
5	Other	The notification includes information about some other situation, not listed above, that has occurred within the System.

2.6.8 PaymentType

Value	Name
1	Bank transfer
2	Bank card
3	Cash
4	Other

2.6.9 RecallReasonType

Value	Name
1	Reported event did not materialise
2	Message contained erroneous information
3	Other

2.6.10 RegisterStatus

Value	Name
1	Registered
2	De-registered

2.6.11 TobaccoProductType

Value	Name
1	Cigarette
2	Cigar
3	Cigarillo
4	Roll your own tobacco
5	Pipe tobacco
6	Waterpipe tobacco
7	Oral tobacco

8	Nasal tobacco
9	Chewing tobacco
10	Novel tobacco product
11	Other

2.6.12 TransportMode

Value	Name
0	Other
1	Sea Transport
2	Rail transport
3	Road transport
4	Air transport
5	Postal consignment
6	Fixed transport installations
7	Inland waterway transport

2.6.13 UniqueIdentifierState

Value	Name	Description
1	Generated	The ID Issuer reports the issue of some codes and the Secondary repository creates a unique identifier record with the initial state (i.e. Generated).
2	Activated	The unique identifier, after being verified by the manufacturer, matches one unique identifier stored in the Secondary repository under the status "Generated". Additionally, the information contained in the date element of information matches the valid activation date for that unique identifier.
3	Deactivated	The manufacturer reports the deactivation of that unique identifier. Other cause of deactivation is when manufacturers tries to activate a unique identifier whose date element of information does not match the valid activation date for that unique identifier.
4	Expired	The Secondary repository promotes to "Expired" the codes that have been issued, but their activation has not been reported within a certain period of time (i.e. expiration time).
5	Delivered	The distributor or wholesaler reports that this tobacco product item has been successfully dispatched to the final retailer.

2.6.14 UniqueIdentifierType

Value	Name	Description
1	UnitPacket	Unique identifier at unit packet level
2	AggregatedPackaging	Unique identifier at aggregated packaging level

3 Messages

3.1 Message types to be exchanged

Described in the Regulation Annex II "Key messages to be sent by the economic operators"

5 categories of messages, related to:

- Identifier codes for economic operators, facilities and machines
- Unique identifiers for unit level UIs and aggregated level UIs
- Recording and transmission of information on product movements
- Transactional events
- Recalls

The following table summarizes the JSON formatted messages.

Message Type	Annex II Reference	Message description
REO	(1.1)	Registration of an Economic operator
REOD		Registration Data of an Economic operator
CEO	(1.2)	Correction for an economic operator identifier code
DEO	(1.3)	De-registration of economic operator identifier code
RFA	(1.4)	Request for a facility identifier code
RFAD		Data for a facility identifier code
CFA	(1.5)	Correction of information concerning the facility identifier code
DFA	(1.6)	De-registration of facility identifier code
RMA	(1.7)	Request for a machine identifier code
RMAD		Data for a machine identifier code
CMA	(1.8)	Correction of information concerning the machine identifier code
DMA	(1.9)	De-registration of machine identifier code
ICV		Identifier code verification
ICM		Validation of the delivery of an IRU message
ULO		Flat file and registry File upload
ULOD		Flat file and registry File upload callback
PLO		Partial Flat file and registry transmission
ISU	(2.1)	Request for unit level UIs
IRU		Response for unit level UIs

IRUD		Callback for the Message to report the issuance of serial numbers at unit packet level
ISA	(2.2)	Request for reporting the issuance of serial numbers at aggregated level
IRA		Request for reporting the issuance of serial numbers at aggregated level
IDA	(2.3)	Request for deactivation of UIs
EUA	(3.1)	Application of unit level UIs on unit packets
EPA	(3.2)	Application of aggregated level UIs on aggregated packaging
EDP	(3.3)	Dispatch Event
ERP	(3.4)	Reception event
ETL	(3.5)	Trans-loading event
EUD	(3.6)	Message to report an UI disaggregation
EVR	(3.7)	Report the delivery carried out with a vending van to retail outlet
EIV	(4.1)	Message to report an invoice
EPO	(4.2)	Purchase order
EPR	(4.3)	Payment record
RCL	(5.0)	Recall messages
LUP		Download Offline flat file
LUQ		Query Messages
LDI		Lookup Dispatch Interface
CTM		Connectivity Test Messages

3.1.1 Optional II2MN II2DW interfaces

The ID Issuer defines the communication between the EO and the ID issuer corresponding to interfaces II2MN and II2DW.

The proposed messages presented in this Data Dictionary are sample messages to illustrate the overall flow of data from the EO to the Secondary repository. These messages should be considered as a Guideline with no obligation of implementation.

All messages part of the II2MN and II2DW interfaces are marked as optional in this document.

3.1.2 Message and endpoints

		Message support
Primary Repository End Point		
Primary Endpoint	The primary endpoint	IRU,IRA,IDA,EUA,EPA,EDP,ERP,ETL,EUD,EVR,EIV,EPO,EPR,RCL,CTM
Router Endpoints		
Router	The authentication endpoint	
Router	The resource endpoint	IRU,IRA,IDA,EUA,EPA,EDP,ERP,ETL,EUD,EVR,EIV,EPO,EPR,RCL
Router	The flat file upload	ULO, PLO
Router	The verification endpoint	ICV, LDI
Secondary Repository Endpoints		
Secondary Repository	The resource endpoint	IRU,IRA,IDA,EUA,EPA,EDP,ERP,ETL,EUD,EVR,EIV,EPO,EPR,RCL
Secondary Repository	The Offline flat file download	LUP, LUQ

3.2 Common schema elements

3.2.1 Basic information block concerning the request

Basic information block concerning the request - schema					
Field	Description	Data Type	Cardinality	Priority	Values
Message_Type	The identifier of the type of message	Text(Limited to set of known message_types)	S	M	See above types of messages list
Code	The internal code of acknowledgment of the message. Used for recall too.	Text(50)	S	M	property is nullable
RejectionData	The failure data recorded in the primary should the validation fail.	FailureData (See below table)	S	O	This should only be filled if the primary validation fails.
Reception_Time	System reception Time added by the Router or the Primary Repository	Time(ms)	S	M for Router and Primary providers (Does not apply to EO)	

Note 1: The reception Time is added by the entry point traceability system (Router or primary repository). The reception Time provided by the router to the primary repositories should be maintained and the primary repositories should accept the field and forward it to the secondary repository.

Note 2: The Code should be set to null for the initial request.

RejectionData - schema					
Field	Description	Data Type	Cardinality	Priority	Values
ResponseText	The response of the primary	Text(5000)	S	M	
Errors	List of the errors. Array containing Error_Code, Error_Descr, Error_InternalId, Error_Data (string)	Array of objects	S	M	

If the secondary repository receives a message with this "RejectionData" non null, it will not process the message and will instead record / audit the failure. This for later analysis, used to find possible illicit trade.

3.2.2 Basic information block concerning the response

Basic information block concerning the response - schema					
Field	Description	Data Type	Cardinality	Priority	Values
Message_Type	The identifier of the type of message that the response refers to	Text	S	M	See above types of messages list
Error	Indicates the failure of the message reception	Boolean	S	M	0 – No 1- Yes
Errors	Array containing Error_Code, Error_Data (string), Error_Descr, Error_InternalID	Array of objects	S	M if Error = 1	System error catalogue at Error! Reference source not found.
Code	Unique identifier of the message. Used for recall too.	Text(50)	S	M	
Checksum	The calculated checksum of the data received	Text(5000)	S	M	

3.2.3 Basic Error block description

Data Type	Description	Type	Example or regular expression
Error_Code	Error code describing the error.	Text(30)	
Error_Data	Text field containing error related data such as values of attributes, list of UIs For all lists, use the # character as separator.	Text(5000)	
Error_Descr	Description of the error code, that must contain the related	Text(5000)	

	controls, related RecallCode and fields when applicable.		
Error_Inter nalID	Optional internal ID of the error. This internal ID can be used for maintenance or audit purpose.	Text(50)	

```
{
  ...
  "Errors": [
    {
      "Error_Code": "UI_NOT_EXIST",
      "Error_Descr": "Text describing the error code",
      "ErrorData": "CF12D12AB887#CFEEAB2AB887#CFEED12AB887#AB1212AB6395"
    }
  ],
  ...
}
```

3.2.4 Response Information block

Basic information block concerning the response - schema					
Field	Description	Data Type	Cardinalit y	Priority	Values
Information_ Type	The identifier of the type of information	Text(5000)	S	M	
Data	Indicates the failure of the message reception	Text(5000)	S	M	0 – No 1- Yes
Data_List	Array of strings	Text(string limit = 5000)	M	O	

```
{
  ...
  "Information": [
    {
      "Info_Type": "TotalupUI",
      "Data": "5000"
    }
  ],
  ...
}
```

3.2.4.1 Information_Type

Information_Type	Description
TotalupUI	Total number of upUI present in the event. This optional field is supported on the following requests

Information_Type	Description
	- EPA – (3.2) Application of aggregated level UIs on aggregated packaging - EDP – (3.3) Dispatch of tobacco products from a facility - ERP – (3.4) Arrival of tobacco products at a facility - ETL – (3.5) Trans-loading event - EVR – (3.7) Report the delivery carried out with a vending van to retail outlet

3.2.5 Empty array and null values

3.2.5.1 Empty array

An array structure is represented as square brackets surrounding zero or more values (or elements).

```
{
  ...
  "Errors": [],
  ...
}
```

3.2.5.2 Null value

A JSON null value MUST be a literal named null.

```
{
  ...
  "Code": null,
  ...
}
```

3.2.6 Decimal points

According to the JSON Standard RFC7159 a JSON decimal separator value MUST be a period ".".

```
{
  ...
  "DecimalValue": 35.21
  ...
}
```

3.2.7 Common Error codes

HTTP status	Error Code	Error Description
401	SECURITY_INVALID_OR_EXPIRED_TOKEN	Invalid or Expired security token Please note that in this case the code or internal ID is not returned, as the message has not reached the processing service yet.

400	INVALID_SIGNATURE	Invalid signature
400	REQUIRED_FIELD_FAILED_VALIDATION MAX_LENGTH_FAILED_VALIDATION MIN_LENGTH_FAILED_VALIDATION ENTRY_LENGTH_FAILED_VALIDATION	When one or multiple fields do not contain valid format
400	PAYLOAD_NOT_UNIQUE	When the message has already been processed successfully.
400	INVALID_REQUEST_FORMAT	This error is returned when at least one of the mandatory fields are missing.
400	INVALID_MESSAGE_TYPE	When the field "Message_Type" is out of the defined list.
400	INVALID_INPUT_FORMAT	When the body of the message doesn't contain a valid JSON.
500	SYSTEM_ERROR	Internal system error.

3.3 Message Validation

3.3.1 Overview

Validation is the process to accept or reject an incoming message.

Upon the reception of reported events on UI, a certain number of calculated information called metadata are computed and managed internally on the Secondary repository and Router. The UI metadata consists of

- The **UI state information** (indicating if the UI is in stock in a location, in transit and other)
- The **UI Location FID** (current location or last known location)
- The **UI Aggregation context** (if the UI is part of an aggregation)
- The **UI Event history**

This metadata is internally used by the Secondary repository and the Router to perform the validation in real time and allows the system to meet the response time regulatory SLA.

Once the event is validated and accepted by the router or the secondary repository, the metadata for UIs are updated.

3.3.1.1 Principle: Duplication of validation

The complete traceability system should be considered as one system and the validation is performed at the first component of the system.

- Messages processed by the Router and transmitted to the Primary repository, should not be validated at the Primary repository level.

- Messages processed by the Primary repository and forwarded to the Secondary repository, is validated in order to ensure internal data integrity between systems.




Figure 1 Validation Overview

3.3.1.2 Validation response

The Https status of the response provide information on the way the receiving system is handling the data.

- Http status **200 – 202**: the message is processed successfully
- Http status **299**: the message contains one or more errors (validation failure), the message is processed even with the errors. (some processing might be limited). The response contains the list of failed validations.
- Http status **400**: the message contains one or more validation errors. The message will NOT be processed. An audit of the message and its corresponding response will be stored on the EU Secondary. The response contains the list of failed validations.

http status 299 is used in multiple circumstances. This warning status is used to informing the sending system of an unrecognized UI during the “Transition Period” as well as out of sequence event during the grace period. This status is also used in case a message is reported outside the 24hour (defined on the validation VAL_EVT_24H). The response message contains the list of validations failures that caused the warning.

3.3.1.3 Technical and business validation

The validation process is composed by a technical aspect and business validation. The technical validation ensures that the message follows the

general format and message structure including field availability and predefined values. This validation is performed on all components. The business validation is performed after the technical validation and focuses on the state of business data.

3.3.1.4 Message transmission overview

The following diagram describes the different message transmission and response options.




Figure 2 EU secondary validation system diagram

Note that the technical validation is not represented in the following diagram. Only the business validation. It is clear that messages that fail the technical validation (wrong format, not authorized) will be rejected by all systems with an http status 400.

3.3.1.4.1 Secondary to Primary Feedback

The Secondary repository performs the full validation (technical and business validation) all messages from the different primary repositories as described in the list of Specification.

The information provided by the primary repository is used to update the internal state of the different UI. The states are then used during the validation enforcement on the router.

The Secondary repository is running all the validation in order to confirm the coherence of the state changes.

In case the secondary validation process returns a negative response, the secondary repository will reject the message (http status 400)

The Meta data associated with the UI is not updated if the message is rejected (error 400).

If a message is rejected by the secondary repository, the primary repository can retransmit the same message (same payload and same RecallCode) as an attempt to get it accepted.

3.3.1.4.2 Router to Primary

The router performs the validation of the messages received. Depending on the type of messages, the message is then forwarded to the Primary repository. The primary repository will accept the messages and always (messages that are passing or failing the business validations) return a http 200 or 202 to the router.

3.3.1.4.3 Router and Primary to EO

The messages from the Economic operators are validated at the first point of entry. For the manufacturer and importer, the messages are transmitted to the primary repositories.

The messages from the distributors are validated by the router based on the information processed on the secondary repository.

Depending on the content of the message, the EO might receive a successful response (http 200 or 202) a warning (http 299) or a rejection data (http 400).

3.3.2 Timestamps

	Event Time	Message Time Long	Reception Time	Record Time
Source	Provided by EO system	Provided by EO system	Provided by Primary repository or Router	Established by the Secondary repository
Precision	hour	second	milliseconds	milliseconds
		Used for sequence validation	Used for sequence validation as a replacement of the Message Time Long	Used for audit purposes
Note		Note: the Message time can be the Event Time on the second precision	Note: the Message time can be the Event Time on the second precision	

3.3.3 Type of validation

3.3.3.1 *Security validation*

The security validation is the first part of the technical validation ensuring that connecting systems are authenticated and authorized to transmit data to the traceability system.

Control	Description	Scope
VAL_SEC_HASH	Integrity check of the checksum	All messages
VAL_SEC_TOKEN	Oauth Security Token validation	All messages

3.3.3.2 *Message Structure validation*

The technical validation ensures that the messages are following the technical guidelines and allows the system to successfully access the message data accurately.

Control	Description	Scope
VAL_MSG_JSON	JSON structure validation	All JSON messages
VAL_MSG_XML	XML structure validation	All EPCS EDI messages
VAL_MSG_TYPE	Message type validation	All messages
VAL_FIE_MAN	Mandatory Field validation (per message type)	All messages
VAL_FIE_FORMAT	Field format validation	All messages
VAL_FIE_REF	Existence of correctly reference enumerations. (As defined in data dictionary)	All messages

3.3.3.3 *Message Transmission validation*

The transmission controls are established in order to prevent technical duplication and processing of messages.

Control	Description	Scope
VAL_MSG_DUPLICATE	Message payload already processed successfully by the Router or Primary should be rejected.	IRU - IDA - EUA - EPA - EDP - ERP- ETL- EUD- EVR - EIV - EPO - EPR
VAL_MSG_CODE_DUPLICATE	Message identified by a Recallcode that has already been processed successfully should be rejected.	All messages

3.3.3.4 *Unique Identifiers validation*

The following validations are performed on each UI that is present in a message.

3.3.3.4.1 Message level validation

The UI present in a message should be present only once. If the UI is present multiple times, the message will be rejected as non-compliant.

Control	Description	Scope
VAL_UI_MULT_MSG	Multiple duplicate UI present in the messages. For EPA (message 3.2), the validation on the parent UI should also be performed in order to avoid first level cyclical reference.	IRU - IDA - EUA - EPA - EDP - ERP- ETL- EUD- EVR - EIV - EPO - EPR

3.3.3.4.2 Application Validation

Validation that the upUI(s) is only applied once to a upUI(L)

Control	Description	Scope
VAL_UI_EXIST_APP	upUIs has been received as part of an IRU message. This validation fails if the upUIs is not found and has not been reported.	EUA - IDA
VAL_UI_DUPLICATE_APP	UI validity Check if the upUIs has already been applied to a upUI(L)	EUA
VAL_UI_FID_APP	Validation of the FID defined in the IRU message (2.1).	EUA

3.3.3.4.3 Existence

The following control ensures that the UI (upUI and aUI) comply with the regulation and could participate in product movement or transaction event reporting.

Control	Description	Scope
VAL_UI_EXIST_UPUI	UI existence upUI exists and has been successfully applied	EPA (Children) - EDP - ERP- ETL- EVR - EIV - EPO - EPR
VAL_UI_EXIST_AUI	aUI existence aUI has been aggregated (part of an EPA)	IDA -EPA (Children) - EDP - ERP- ETL- EVR - EIV - EPO - EPR
VAL_UI_EXIST_UPUI_SEQ	UI validity - upUI exists and has been successfully applied - upUI has not been part of any deactivation message.	EPA (Children) - EDP - ERP- ETL- EVR

VAL_UI_EXIST_AUI_SEQ	aUI validity - aUI has been aggregated (part of an EPA) - and has not been disaggregated (including implicit disaggregation) - nor deactivated.	IDA –EPA (Children) – EDP – ERP- ETL- EVR
----------------------	---	---

3.3.3.4.4 upUI Expiration

As per the regulation, the upUI(s) that are issued by the ID Issuer and reported in the IRU messages have a limited application period.

Control	Description	Scope
VAL_UI_EXPIRY	Validation that the application or the aggregation date doesn't exceed the 6 months period after the code has been issued.	EUA, EPA

3.3.3.5 UI level Message sequence validation

3.3.3.5.1 Sequence Validation overview

The following tables describes the summary overview of allowed events related to a certain UI based on the last event received for that specific UI.

Note that the transactional events (4.x) are not described in the rows as there is no sequence validation implemented on these events

Legend:

- Yes (Green): the message could be accepted for that specific UI
- Yes (blue): The message is accepted, and a location validation control is applied.
- No: the message should be rejected

Control	Description	Scope
VAL_UI_ORD_SEQUENCE	The general sequence validation.	IRU – IRA- IDA- EUA- EPA- EDP- ERP- ETL- EUD- EVR

PREVIOUS MESSAGE on the UI present in the received message							
IRU 2.1	IRA 2.2	IDA 2.3	EUA 3.1	Import	EPA 3.2 parent UI	EPA 3.2 parent UI	EPA 3.2 Child

Message Received					
IRU 2.1	No	No	No	No	No
IRA 2.2	No	No	No	No	No
IDA 2.3	No	No	No	Yes	Yes
EUA 3.1	Yes	No	No	No	No
EUA 3.1 Import	Yes	No	No	No	No
EPA 3.2 parent UI	No	Yes	No	No	No
EPA 3.2 child UI (upUI)	No	No	No	Yes	Yes
EPA 3.2 child UI (aUI)	No	No	No	No	No
EDP 3.3 Export (type 1)	No	No	No	Yes	No
EDP 3.3 (type 2)	No	No	No	Yes	No
EDP 3.3 VM (type 3)	No	No	No	Yes	No
EDP 3.3 VV (type 4)	No	No	No	Yes	No
ERP 3.4	No	No	No	No	Yes
ERP 3.4 (Return)	No	No	No	No	No
ETL 3.5	No	No	No	No	No
ETL 3.5 (Export)	No	No	No	No	No
EUD 3.6	No	No	No	No	No
EVR 3.7	No	No	No	No	No
EIV 4.1	No	No	Yes	Yes	Yes
EPO 4.2	No	No	Yes	Yes	Yes
EPR 4.3	No	No	Yes	Yes	Yes

PREVIOUS MESSAGE on the UI present in the received message

Message Received	EDP 3.3 (type 1) Export	EDP 3.3 (type 2)	EDP 3.3 (type 3) VM	EDP 3.3 (type 4) VV	ERP 3.4	ERP 3.4 (Return)	ETL 3.5	ETL 3.5 Export	EUD 3.6	EUD 3.6 (aUI implicitly disaggregated) - reuse of aUI	EVR 3.7
IRU 2.1	No	No	No	No	No	No	No	No	No	No	No
IRA 2.2	No	No	No	No	No	No	No	No	No	No	No
IDA 2.3	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
EUA 3.1	No	No	No	No	No	No	No	No	No	No	No
EUA 3.1 Import	No	No	No	No	No	No	No	No	No	No	No
EPA 3.2 parent UI	No	No	No	No	No	No	No	No	Yes	No	No
EPA 3.2 child UI (upUI)	No	No	No	No	Yes	Yes	No	No	No	No	No
EPA 3.2 child UI (aUI)	No	No	No	No	Yes	Yes	No	No	No	No	No
EDP 3.3 Export (type 1)	No	No	No	No	Yes	Yes	No	No	No	No	No
EDP 3.3 (type 2)	No	No	No	No	Yes	Yes	No	No	No	No	No
EDP 3.3 VM (type 3)	No	No	No	No	Yes	Yes	No	No	No	No	No
EDP 3.3 VV (type 4)	No	No	No	No	Yes	Yes	No	No	No	No	No
ERP 3.4	No	Yes	No	No	No	No	Yes	No	No	No	No
ERP 3.4 (Return)	Yes	Yes	Yes	Yes	No	No	Yes	Yes	No	No	Yes
ETL 3.5	No	Yes	No	No	No	No	Yes	No	No	No	No
ETL 3.5 (Export)	Yes	No	No	No	No	No	No	Yes	No	No	No
EUD 3.6	No	No	No	No	Yes	Yes	No	No	No	Yes	No
EVR 3.7	No	No	No	Yes	No	No	No	No	No	No	No
EIV 4.1	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
EPO 4.2	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
EPR 4.3	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes

The type of the Dispatch event 3.3 EDP refers to the Destination_ID1 field.

- Type 1 – Non EU dest.
- Type 2 – EU destination other than VM – fixed quantity delivery
- Type 3 – EU VM(s)
- Type 4 – EU destination other than VM – delivery with VV

The type return of the ERP (3.4) is based on the Product_Return field

- 0 – No
- 1– Yes, The arrival is of type return

The field Destination_ID1 in the ETL (3.5) event indicates if the ETL is aimed at export or EU location.

- 0 – No
- 1 – Yes (export)

3.3.3.5.2 Application and deactivation sequence validation

Control	Description	Scope
VAL_UI_ORD_REACTIVATION	upUI(s) that has been deactivated should not allow any application event (EUA).	EUA
VAL_UI_ORD_DEACTIVATED	UI – presence of UI in a message after being deactivated.	EPA – EDP – ERP- ETL- EUD- EVR - IDA

3.3.3.5.3 Aggregation and Disaggregation Principles

Principle 1: All aggregation events are full aggregation. Once the aUI is aggregated, a subsequent aggregation event on the same parent aUI should be rejected.

Principle 2: All disaggregation events are full disaggregation. Once the aUI is disaggregated, no movement should be reported on that aUI (until the next disaggregation and aggregation event are reported.).

Principle 3: Implicit disaggregation. Disaggregation event reporting is mandatory only when the aUI is reused in a subsequent aggregation event (as a parent aUI). The implicit disaggregation is detected when at least one child UI is reported in an aggregation or product movement. The parent aUI of this child UI will be considered as disaggregated. In the case that the child UI is part of an aggregation hierarchy, all parent aUIs will be disaggregated.

As a consequence, once the implicit disaggregation is detected, no movement should be reported on that parent aUI (until the next aggregation event is reported).

Principle 4: All disaggregation must be performed at a location. No Disaggregation are allowed during the transport.

Note that implicit disaggregation might be triggered while in transit by a deactivation event IDA (2.3), a delivery carried out by vending van EVR (3.7) or an arrival ERP (3.4) of type Return.

3.3.3.5.4 Implicit disaggregation

Since disaggregation events are only mandatory when the parent aUI is reused, Implicit disaggregation event will happen.

3.3.3.5.4.1 Triggers

These events will be detected / triggered when a child UI is identified on one of the following messages: IDA (2.3), EPA (3.2), EDP (3.3), ERP (3.4) of type Return, EUD (3.6) and EVR (3.7).

Note that transactional events are not triggering any implicit disaggregation.

Example of implicit disaggregation triggered by EDP (3.3)




Figure 3 Implicit disaggregation triggered by EDP (3.3)

Example of implicit disaggregation triggered by EVR (3.7)




Figure 4 Implicit disaggregation triggered by EVR (3.7)

3.3.3.5.4.2 Disaggregated state

Once the UI is implicitly disaggregated, the UI should be considered disaggregated and should not be part of any subsequent product movement (3.x). The definition of implicit disaggregation is that the affected parent aUI is considered completely unlinked from all the children it had at the moment of the implicit disaggregation trigger ("Open"). If a reported UI has more than one linked parent at the moment of the reporting, all parents should be implicitly disaggregated, this includes grand-parents and recursively upwards linked UIs.

3.3.3.5.4.3 Recall

It is important to note that implicit disaggregation should be rolled back in case the event that triggered them is Recalled.

3.3.3.5.4.4 Explicit disaggregation after implicit disaggregation

The scope of the VAL_UI_ORD_IMPLDISAGG and VAL_UI_ORD_DISAGG have been removed from EUD (3.6). This means that it is possible to disaggregate an aUI after being part of an implicit disaggregation (as a parent).

3.3.3.5.5 Aggregation and Disaggregation Validation

Control	Description	Scope
VAL_UI_ORD_AGG_MULT	Validation that a parent UI has not been part of any prior aggregation event (as parent) without being part of a disaggregation event. This control prevents the reuse of an aUI without prior disaggregation.	EPA
VAL_UI_ORD_DISAGG	Validation that an aUI has been disaggregated cannot be part on any product movement prior of being aggregated.	EDP - ERP - ETL - EVR
VAL_UI_ORD_IMPLDISAGG	Validation that an aUI has been implicitly disaggregated cannot be part on any product movement prior of being part of an EUD message and then aggregated.	EDP - ERP - ETL - EVR- EPA (Children)

3.3.3.5.6 Location based Validation

3.3.3.5.6.1 UI Location update

The sequence validation also considers the implementation of location-based controls.

FID of the UI is updated upon processing of the following events.

- ERP (3.4)
- EUA (3.1) update of the location of the UI. The location of the UI should match the location defined in the IRU message.
- EPA (3.2) update of the newly created parent id
- EVR (3.7) In case of implicit disaggregation, only the UIs present in the event will have the location metadata updated.
- RCL (5.0) rolls back to the previous state

3.3.3.5.6.2 Location based controls

Control	Description	Scope
VAL_UI_ORD_AGG_FID	Validation that the aggregation and the disaggregation events must happen at the same facility (FID) where the products have been either created or arrived.	EPA - EUD

3.3.3.5.7 Dispatch and arrival Validation

Principle 5: The reporting on the Arrival should be done on the same UI that have been reported during the Dispatch/Transloading process. This is a consequence of principle 4. This means that an Arrival Event that contains child UI of UI reported during the Dispatch/Transloading Event will be rejected. The same UI must be reported.

Exception VAL UI ORD ARRIVAL RETURN: arrival of type return only affects the principle 5 but still enforce the event sequence validation.

Control	Description	Scope
VAL_UI_ORD_ARRIVAL	Validation that a UI is part of a prior reported dispatch or transloading event (EDP 3.3, ETL 3.5). This validation concerns the sequence of events. <u>Exception:</u> Imported products	ERP (Product_Return = 0)
VAL_UI_ORD_ARRIVAL_RETURN	Validation that a UI is part of a prior reported dispatch or transloading event (EDP 3.3, ETL 3.5, EVR 3.7) for the specified destination. This validation concerns the sequence of events. In this validation principle 5 doesn't apply.	ERP (Product_Return = 1)

3.3.3.5.7.1 imported goods Exception

The IRU (response to message 2.1 defined in Annex II) contains the import flag information. This flag will be used to assess if the exception should be implemented.

- a) Unit packs that contain the import flag information and that have been applied and eventually aggregated with EUA (message 3.1) and EPA (message 3.2) in a facility whose country is **outside** the EU must be reported in an arrival message with a facility whose country is inside the EU (the physical importation of the goods) before being part of any aggregation or logistic movement inside the EU.
- b) Unit packs that contain the import flag information and that have been applied and eventually aggregated with EUA (message 3.1) and EPA (message 3.2) in a facility whose country is **inside** the EU, must not report an arrival message. In this case, it is understood that the physical importation should have taken place between the IRU (message 2.1) and the application/activation of the UI EUA (message 3.1) and EPA (message 3.2).

3.3.3.5.7.2 Arrival of type return

The reporting of the arrival of type return can be performed on child UI. This operation is allowed and will trigger an implicit disaggregation.

3.3.3.5.7.3 Arrival and Return

Flows from the retail outlets, even in the context of message 3.7, are considered to constitute "product returns".

The flows constitute "product returns" even if the product is returned to the same facility as it was originally dispatched from or to another one.

3.3.3.5.7.4 Dispatch validation

Control	Description	Scope
VAL_UI_ORD_DISPATCH	Validation that a UI last location (FID) matches the source location (FID) of the dispatch event. The UI must have been: - Applied or aggregated on that specific location (FID) - Arrived on that location.	EDP

3.3.3.6 Message Event Time Validation

The following messages validation compares the event time (Event Time) to the actual reception time of the event by the first point of entry.

Control	Description	Scope
VAL_EVT_24H	Validation that the Events are reported within 24 hours from the occurrence of the event. This validation is performed on the Event Time compared to the Record Time of the Primary repository or the Router. NOTE: this validation will be reduced to 3 hours after 20 May 2028 This validation should not be blocking but rather generating a warning to the sender system	EUA – EPA – EVR – EIV – EPO – EPR
VAL_EVT_TIME	"Within 24 hours prior to the occurrence of the event" rule for dispatch and trans-loading event messages is a rule and the system shall reject non-compliant messages. Control is based on the "actual date – Event Time" time difference. This validation should not be blocking but rather generating a warning to the sender system	EDP – ETL

3.3.3.7 Identification Code validation

Identification codes are used in a number of messages. The validation of the existence and fact that the identification code is active is part of the business validation as described in the table below.

Control	Description	Scope
VAL_ENT_EXIST_EOID	Check if the EOID exists in the EU wide registry	ISU – ISA – IRU – IRA – IDA – EUA – EPA – EDP – ERP – ETL – EUD- EVR
VAL_ENT_EXIST_FID	Check if FID, exists in the EU wide registry	ISU – IRU – ISA – IRA – IRU – EUA – EPA – EDP – ERP – ETP – EUD – EVR
VAL_ENT_EXIST_MID	Check if MID, exists in the EU wide registry	ISU – IRU
VAL_ENT_ACTIVE_EOID	Check if EOID is marked as active in the repository	IRU – IRA – IDA – EUA – EPA – EDP

		- ERP - ETL - EUD- EVR
VAL_ENT_ACTIVE_FID	Check if FID is marked as active in the repository	ISU - ISA - IRU - IRA - EUA - EPA
VAL_ENT_ACTIVE_MID	Check if MID is marked as active in the repository	ISU - IRU
VAL_ENT_REL_EOID_FID	Check if EOID FID relation is defined in the EU wide registry	IRU - IRA
VAL_ENT_REL_FID_MID	Check if FID MID relation is defined in the EU wide registry	IRU - IRA

3.3.3.8 Recall Validation

3.3.3.8.1 General recall rules

The sequence validation on the product movement introduces additional controls on the recall process. In order to maintain the consistency of the history of the UI, only the recall of the last event for each UI will be authorized.

If a message to be recalled, contains a UI (any in the reported list) that has a subsequent event, the subsequent event must be recalled first.

For the sake of clarity, the following scenarios describe the process of recall. An EO report two product movements on a UI. (Event 1 and Event 2). If the EO wishes to recall Event 1, the EO has first to recall Event 2 and only after recall Event 1. Moreover, Event2 must be the last event occurred on all UIs contained in Event2 for Event2 could be recalled.

3.3.3.8.2 Transaction events

Transaction events (4.x) are not subject to this rule as they are not impacted by the sequence validation control and therefore, transaction events (4.x) can be recalled at any time.

3.3.3.8.3 Recall Validation Controls

Control	Description	Scope
VAL_RECALL_EXIST	Check if RecallCode exists	RCL
VAL_RECALL_LAST	Check if for all UIs related to the event identified by RecallCode is the very last unrecalled event occurred on all such UI including related implicitly disaggregated parents.	RCL

3.3.4 Validation Scope

	IRU (2.1)	IRA (2.2)	IDA (2.3)	EUA (3.1)	EPA (3.2)	EDP (3.3)	ERP (3.4)	ETL (3.5)	EUD (3.6)	EVR (3.7)	EIV (4.1)	EPO (4.2)	EPR (4.3)	RCL (5)
Technical validation														
VAL_SEC_HASH	X	X	X	X	X	X	X	X	X	X	X	X	X	X
VAL_SEC_TOKEN	X	X	X	X	X	X	X	X	X	X	X	X	X	X
VAL_MSG_JSON	X	X	X	X	X	X	X	X	X	X	X	X	X	X
VAL_MSG_XML														
VAL_MSG_TYPE	X	X	X	X	X	X	X	X	X	X	X	X	X	X
VAL_FIE_MAN	X	X	X	X	X	X	X	X	X	X	X	X	X	X
VAL_FIE_FORMAT	X	X	X	X	X	X	X	X	X	X	X	X	X	X
VAL_FIE_REF	X	X	X	X	X	X	X	X	X	X	X	X	X	X
VAL_MSG_DUPLICATE	X	X	X	X	X	X	X	X	X	X	X	X	X	X
VAL_MSG_CODE_DUPLICATE	X	X	X	X	X	X	X	X	X	X	X	X	X	X
VAL_UI_MULT_MSG	X	X	X	X	X	X	X	X	X	X	X	X	X	
Business rule validation														
UI creation														
VAL_UI_EXIST_APP			X	X										
VAL_UI_DUPLICATE_APP				X										
VAL_UI_EXIST_UPUI					X	X	X	X		X	X	X	X	
VAL_UI_EXIST_AUI					X	X	X	X	X	X	X	X	X	
VAL_UI_EXIST_UPUI_SEQ			X		X	X	X	X		X				
VAL_UI_EXIST_AUI_SEQ			X		X	X	X	X	X	X				
VAL_UI_EXPIRY				X	X									
Entity Validation														
VAL_ENT_EXIST_EOID	X	X	X	X	X	X	X	X	X	X	X	X	X	
VAL_ENT_EXIST_FID	X	X		X	X	X	X	X	X	X				
VAL_ENT_EXIST_MID	X													
VAL_ENT_ACTIVE_EOID	X	X	X	X	X	X	X	X	X	X				
VAL_ENT_ACTIVE_FID	X	X	R	X	R	R	R	R	R	R				
VAL_ENT_ACTIVE_MID	X													
VAL_ENT_REL_EOID_FID	X	X												
VAL_ENT_REL_FID_MID	X	X												
Sequence Validation														
VAL_UI_FID_APP				X										
VAL_UI_ORD_REACTIVATION				X										
VAL_UI_ORD_DEACTIVATED			X		X	X	X	X	X	X				
VAL_UI_ORD_AGG_MULT					X									
VAL_UI_ORD_DISAGG						X	X	X		X				
VAL_UI_ORD_IMPLDISAGG					X	X	X	X		X				
VAL_UI_ORD_AGG_FID					X				X					
VAL_UI_ORD_ARRIVAL							X							
VAL_UI_ORD_ARRIVAL_RETURN							X							
VAL_UI_ORD_DISPATCH						X								
VAL_UI_ORD_SEQUENCE			X	X	X	X	X	X	X	X				
Message Timing														
VAL_EVT_24H				X	X					X	X	X	X	
VAL_EVT_TIME						X		X						
Recall														
VAL_RECALL_EXIST														X
VAL_RECALL_LAST														X

X – validation on Primary, Secondary and Router

R – Validation on Router

3.3.5 Validation Responsibility

	Primary Repository Error http status for EO	Router Error http status for EO	Secondary Repository Error http status for Primary
Technical validation			
VAL_SEC_HASH	400	400	400
VAL_SEC_TOKEN	401	401	401
VAL_MSG_JSON	400	400	400
VAL_MSG_XML	400	400	400
VAL_MSG_TYPE	400	400	400
VAL_FIE_MAN	400	400	400
VAL_FIE_FORMAT	400	400	400
VAL_FIE_REF	400	400	400
VAL_MSG_DUPLICATE	400	400	400
VAL_MSG_CODE_DUPLICATE	400		400
Business rule validation			
VAL_UI_MULT_MSG	400	400	400
VAL_UI_EXIST_APP	400		400
VAL_UI_DUPLICATE_APP	400		400
VAL_UI_FID_APP	400		400
VAL_UI_EXIST_UPUI	400	400	400
VAL_UI_EXIST_AUI	400	400	400
VAL_UI_EXIST_UPUI_SEQ	400	400	400
VAL_UI_EXIST_AUI_SEQ	400	400	400
VAL_UI_EXPIRY	400		400
VAL_UI_ORD_REACTIVATION	400	400	400
VAL_UI_ORD_DEACTIVATED	400	400	400
VAL_UI_ORD_AGG_MULT	400	400	400
VAL_UI_ORD_DISAGG	400	400	400
VAL_UI_ORD_IMPLDISAGG	400	400	400
VAL_UI_ORD_AGG_FID	400	400	400
VAL_UI_ORD_ARRIVAL	400	400	400
VAL_UI_ORD_ARRIVAL_RETURN	400	400	400
VAL_UI_ORD_DISPATCH	400	400	400
VAL_UI_ORD_SEQUENCE	400	400	400
VAL_EVT_24H	299	299	
VAL_EVT_TIME	299	299	
VAL_ENT_EXIST_EOID	400	400	400
VAL_ENT_EXIST_FID	400	400	400
VAL_ENT_EXIST_MID	400	400	400
VAL_ENT_ACTIVE_EOID	400	400	400
VAL_ENT_ACTIVE_FID	400	400	400
VAL_ENT_ACTIVE_MID	400	400	400
VAL_ENT_REL_EOID_FID		400	400
VAL_ENT_REL_FID_MID		400	400
VAL_RECALL_EXIST	400	400	400
VAL_RECALL_LAST	400	400	400

3.3.6 Validation and Error Code

	Error Code	http Status
Technical validation		
VAL_SEC_HASH	INVALID_SIGNATURE	400
VAL_SEC_TOKEN	INVALID_OR_EXPIRED_TOKEN	401
VAL_MSG_JSON	INVALID_INPUT_FORMAT REQUIRED_FIELD_FAILED_VALIDATION MAX_LENGTH_FAILED_VALIDATION MIN_LENGTH_FAILED_VALIDATION ENTRY_LENGTH_FAILED_VALIDATION EXCISE_NUMBER_NOT_VALID NON_COMPATIBLE_UIS NOT_THE_SAME_NUMBER_OF_ITEMS	400
VAL_MSG_XML	FAILED_VALIDATION	400
VAL_MSG_TYPE	FAILED_VALIDATION	400
VAL_FIE_MAN	FAILED_VALIDATION	400
VAL_FIE_FORMAT	INVALID_INPUT_FORMAT	400
VAL_FIE_REF	FAILED_VALIDATION	400
VAL_MSG_DUPLICATE	PAYLOAD_NOT_UNIQUE	400
VAL_MSG_CODE_DUPLICATE	FAILED_VALIDATION	400
VAL_UI_MULT_MSG	MULTIPLE_UID UI_NOT_VALID UIS_NOT_VALID	400
Business rule validation		
UI creation		
VAL_UI_EXIST_APP	UIS_APPLICATION_ERROR	400
VAL_UI_DUPLICATE_APP	UIS_APPLICATION_ERROR	400
VAL_UI_EXIST_UPUI	UI_NOT_EXIST UI_NOT_VALID	400
VAL_UI_EXIST_AUI	UI_NOT_EXIST	400
VAL_UI_EXIST_UPUI_SEQ	UI_NOT_VALID	400
VAL_UI_EXIST_AUI_SEQ	UI_NOT_EXIST	400
VAL_UI_EXPIRY	UI_EXPIRED	400
Entity Validation		
VAL_ENT_EXIST_EOID	EOID_NOT_EXIST_OR_ACTIVE	400
VAL_ENT_EXIST_FID	FID_NOT_EXIST_OR_ACTIVE	400
VAL_ENT_EXIST_MID	MID_NOT_EXIST_OR_ACTIVE	400
VAL_ENT_ACTIVE_EOID	EOID_NOT_EXIST_OR_ACTIVE	400
VAL_ENT_ACTIVE_FID	FID_NOT_EXIST_OR_ACTIVE	400
VAL_ENT_ACTIVE_MID	MID_NOT_EXIST_OR_ACTIVE	400
VAL_ENT_REL_EOID_FID	FID_NOT_RELATED_TO_EOID	400
VAL_ENT_REL_FID_MID	MID_NOT_RELATED_TO_FID	400
Sequence Validation		
VAL_UI_FID_APP	FID_MISMATCH	400
VAL_UI_ORD_REACTIVATION	UI_DEACTIVATED	400
VAL_UI_ORD_DEACTIVATED	UI_DEACTIVATED	400
VAL_UI_ORD_AGG_MULT	MULTIPLE_AGGREGATION	400
VAL_UI_ORD_DISAGG	UI_ALREADY_DISAGGREGATED	400
VAL_UI_ORD_IMPLDISAGG	UI_ALREADY_DISAGGREGATED	400
VAL_UI_ORD_AGG_FID	LOCATION_MISMATCH	400
VAL_UI_ORD_ARRIVAL	ARRIVAL_NOTALLOWED	400
VAL_UI_ORD_ARRIVAL_RETURN	ARRIVAL_NOTALLOWED	400

VAL_UI_ORD_DISPATCH	LOCATION_MISMATCH	400
VAL_UI_ORD_SEQUENCE	UI_SEQUENCE_ERROR	400
Message Timing		
VAL_EVT_24H	OPERATION_WITHIN_24_HOURS	299
VAL_EVT_TIME	SHIPMENT_WITHIN_24_HOURS	299
Recall		
VAL_RECALL_EXIST	CODE_NOT_EXIST CODE_NOT_UNIQUE	400
VAL_RECALL_LAST	RECALL_NOT_LAST_EVENT	400

3.3.7 Transition Period Validation

3.3.7.1 *overview*

It has been recognized that during the transition period (20 May 2019 – 19 May 2020), as provided for under Article 37(1) of Implementing Regulation (EU) 2018/574, a number of UI, which were generated before the 20th of May 2019 and therefore not-registered in the system, might be present in the supply chain and could be accidentally scanned and included in product movement messages. In an effort to avoid full rejection of messages that may also contain valid UIs and non-valid legacy UIs, the following validation rule will be applied.

1. The receiving system (Primary repository, Router) identifies valid and non-registered UIs as per "VAL_UI_EXIST_UPUI" or "VAL_UI_EXIST_AUI" validation in the original message.
2. In case non-valid legacy UIs are identified, the system (Primary repository, Router) ONLY processes the valid UIs.
3. An error message is sent to the requesting system containing the list of non-valid legacy UIs. The error code ("UI_NOT_EXIST_TRANSITION_WARNING") indicates that message in question contains non-valid legacy UIs, which will not be processed by the system. Only valid UIs will be processed.
4. The requesting system, by receiving the validation result with the list of non-valid legacy UIs, have the possibility to recall the message.

3.3.7.2 *Related controls*

The following validation will not apply during the transition period

- VAL_UI_EXIST_AUI
- VAL_UI_EXIST_UPUI

Scope of messages subject to the transition period

- IDA (2.3) Request for deactivation of UIs
- EPA (3.2) Application of aggregated level UIs on aggregated packaging
- EDP (3.3) Dispatch Event
- ERP (3.4) Reception event
- ETL (3.5) Trans-loading event

- EUD (3.6) Message to report an UI disaggregation
- EVR (3.7) Report the delivery carried out with a vending van to retail outlet
- EIV (4.1) Message to report an invoice
- EPO (4.2) Purchase order

3.3.7.3 Primary and Router processing




Figure 5 Transition warning diagram

The primary and Router implementing the transition period receives the incoming event and apply the different validation controls. In case a UI doesn't match the control, the UI will be removed from the forwarded list and placed into the rejection data section of the message.

The primary repository must route events forwarded by the router with the Rejection Data information to the secondary repository.

3.3.7.4 Empty Event

In case all UI in an event are non valid UIs, the Primary or Router will remove all the UI from the main UI list and forward the "empty" message to the Secondary Repository as an error message (http 400) for audit purpose.

3.3.8 Sequence Validation Grace Period

3.3.8.1 Overview

For the Economic Operators (Manufacturers, Importers, distributors), the implementation of the sequence validation is an important technical upgrade. In order to allow Economic operators to finetune their systems, a sequence validation grace period is defined.

During the sequence validation grace period, the Router and Primary repository will only provide WARNING (http status 299) instead of an

ERROR (http status 400) in case of non-compliance and still accept the messages. These warning should be used by the EO to understand the errors and adapt their systems in order to comply with the new technical validation.

It is important to note that the “**sequence validation grace period**” is different from the “**transitions period**”. Both periods can overlap.

3.3.8.2 *UI Processing*

During the sequence validation grace period, If the UI doesn't pass the sequence validation, it will still be accepted, and the message processed. Because the sequence validation is not respected, the processing system (Primary repository or Router) will not be able to maintain an accurate state for that specific UI. The UI will be identified, and further events related to this UI will be accepted.

3.3.8.3 *End of grace period*

For UIs that have been issued and operated prior to the end of the Sequence Validation Grace Period, those might contain non-conform information. This means that the information used to implement the sequence validation, for these specific UI might not be sufficient to enforce the validation.

If the information available for these UIs, is not sufficient to assess the location and the state, the system should allow the product movement and bypass the validations.

3.3.8.4 *Related controls*

The following validation controls will be impacted by this sequence validation Grace Period

- VAL_UI_FID_APP
- VAL_UI_ORD_REACTIVATION
- VAL_UI_ORD_DEACTIVATED
- VAL_UI_ORD_AGG_MULT
- VAL_UI_ORD_DISAGG
- VAL_UI_ORD_IMPLDISAGG
- VAL_UI_ORD_AGG_FID
- VAL_UI_ORD_ARRIVAL
- VAL_UI_ORD_DISPATCH

3.3.8.5 *Primary and Router processing*

The primary and Router implementing the transition period receives the incoming event and apply the different sequence validation controls. In case a UI doesn't match the control, a warning response will be sent back to the sender system. The original message will be forwarded without any additional rejection data section linked to the sequence validation.

3.3.9 Secondary repository special processing of technical historical data.

3.3.9.1 Context

In some exceptional cases, if the primary repositories fail to report some events, the secondary validation will prevent the primary to report these events *a posteriori*.

The following edge cases have been identified.

- MAINT_01: Repacking scenario
- MAINT_02: Historical Transloading scenario
- MAINT_03: Arrival before Deactivation

In order to allow the secondary to be a copy of the primary repositories, the secondary repository will perform a limited update of the meta data. Only the event list will be updated

The metadata used for the validation (state and location) will not be updated in these specific cases.

The secondary will add specific audit trail during the processing of these specific cases.

The secondary will add specific information to the event allowing the competent authority to be informed of this specific processing.

Note that any other cases not exactly matching these scenarios will be rejected. (http status 400)

The primary repository will receive a successful answer (http status 202) and will not have to resend the message.

3.3.9.2 MAINT_01: Repacking scenario

The initial packing process for a certain aUI corresponds to the reporting of an Aggregation (EPA 3.2) event.

The repacking process consists of an explicit Disaggregation (EUD 3.6) event followed by a new Aggregation (EPA 3.2) event.

In unlikely event of an issue in the reporting of the original aggregation and disaggregation event, the final aggregation event will be processed by the secondary repository.

MSG Sequence	MSG Type	UIs	Primary ACK	Secondary ACK	Comments
1	EPA1 (3.2)	aUI	202	TIMEOUT	Message is not transmitted to Secondary due to

					technical reasons
2	EUD (3.6)	Same aUI	202	TIMEOUT	Message is not transmitted to Secondary due to technical reasons
3	EPA 2 (3.2)	Same aUI	202	202	

Message supported:

- aggregation message (EPA),
- disaggregation message (EUD).

Controls

- Messages must have been rejected by the regular endpoint.
- Control on the Existence of the aUI
- Control on the Reception Time or Message Time Long

3.3.9.3 MAINT_02: Historical Transloading scenario

ETL message

MSG Sequence	MSG Type	UIs	Primary ACK	Secondary ACK	Comments
1	EDP	Any	202	202	
2	ETL	Same as in EDP	202	TIMEOUT	Message is not transmitted to Secondary due to technical reasons
3	ERP	Same as in EDP	202	202	

Message supported:

- Transloading message (ETL 3.5),

Controls.

- Control on the MessageTimeLong that ETL was sent after an EDP (3.3)

- Control on the MessageTimeLong that ETL was sent before an ERP (3.4)

3.3.9.4 MAINT_03: Arrival before Deactivation

MSG Sequence	MSG Type	UIs	Primary ACK	Secondary ACK	Comments
1	EDP (3.3)	Any	202	202	
2	ERP (3.4)		202	TIMEOUT	Message is not transmitted to Secondary due to technical reasons
3	IDA (2.3)		202	202	

Message supported:

- Arrival message (ERP 3.4)

3.3.9.5 Recall clarification

Once the events are accepted, including events accepted with special processing (meaning that events have been accepted out of sequence), the recall validation will apply on the full event sequence.

By definition the events accepted with special processing are NOT the latest events for some UI present in the event. For that reason, the Recall process must first be applied on the latest event (based on the Reception_Time).

In the case of MAINT_02 where the ETL (3.5) transloading event has been reported after the ERP (3.4) Arrival event, the Recall must first be reported on the ERP and then another recall on the ETL.

MSG Sequence	MSG Type	UIs
1	EDP	Any
2	ETL	Same as in EDP
3	ERP	Same as in EDP

3.4 Identifier codes for economic operators, facilities and machines messages

3.4.1 REO - (1.1) Registration of an Economic operator

3.4.1.1 Description

Submit the information for the first registration of the economic operator.

3.4.1.2 Description of the fields

registration of economic operator – request					
Field	Description	Data Type	Cardinality	Priority	Values
BasicInfo_Req	Block of basic information elements	Component << Basic Information Request >>	S	M	Message_Type = REO
EO_Name1	Economic operator's registered name	Text(100)	S	M	
EO_Name2	Economic operator's alternative or abridged name	Text(100)	S	O	
EO_Address	address – street name, house number, postal code, city	Text(300)	S	O	
EO_Address_Name	Name part of the Address	Text(5000)	S	O	
EO_Address_StreetOne	Street part of the Address	Text(5000)	S	M	
EO_Address_StreetTwo	Second Element of the Street part of the Address	Text(5000)	S	O	
EO_Address_City	City	Text(5000)	S	M	
EO_Address_PostCode	PostalCode information	Text(5000)	S	O	
EO_CountryReg	Economic operator's country of registration	Country	S	M	See Country
EO_Email	Economic operator's email address; used to inform about registration process, incl. subsequent changes and other required correspondence	Text(5000) (Regex protected)	S	M	
VAT_R	Indication of the VAT registration status	Boolean	S	M	0 – No VAT registration 1 – VAT number exists
VAT_N	Economic operator's VAT number	Text(20)	S	M, if VAT_R = 1	

TAX_N	Economic operator's tax registration number	Text(20)	S	M, if VAT_R = 0	
EO_ExciseNumber1	Indication if the economic operator has an excise number issued by the competent authority for the purpose of identification of persons/premises	Boolean	S	M	0 – No SEED number 1 – SEED number exists
EO_ExciseNumber2	Economic operator's excise number issued by the competent authority for the purpose of identification of persons/premises	SEED	S	M, if EO_ExciseNumber1 = 1	
OtherEOID_R	Indication if the economic operator has been allocated an identifier by another ID Issuer	Boolean	S	M	0 – No 1 – Yes
OtherEOID_N	Economic operator identifier codes allocated by other ID Issuers	EOID	M	M, if OtherEOID_R = 1	
Reg_3RD	Indication if the registration is made on behalf of a retail outlet operator not otherwise involved in the tobacco trade	Boolean	S	M	0 – No 1 – Yes
Reg_EOID	Identifier of the economic operator that acts on behalf of a retail outlet operator not otherwise involved in the tobacco trade	EOID	S	M, if Reg_3RD = 1	
EO_OtherID	Optional identifier	Text(50)	S	O	
Extensibility	Optional extensibility field	Text(5000)	S	O	

3.4.1.3 Response:

Field	Description	Data Type	Cardinality	Priority	Values
BasicInfo_Resp	Block of basic information elements	Component << Basic Information Response >>	S	M	Message_Type = REO
EO_ID	Economic operator's registered ID	EOID	S	O	
EO_CODE	Economic operator's confirmation code provided in response	EO_CODE	S	O	

	to the registration of economic operator				
Extensibility	Optional extensibility field	Text(5000)	S	O	

3.4.1.4 Request sample

```
{
  "EO_Name1": "Example Legal Entity",
  "EO_Name2": "",
  "EO_Address": "59 Legal Street",
  "EO_CountryReg": "DE",
  "EO_Email": "email@test.com",
  "VAT_R": 1,
  "VAT_N": "VATNumber 1",
  "TAX_N": "Tax",
  "EO_ExciseNumber1": 1,
  "EO_ExciseNumber2": "LA111FD",
  "OtherEOID_R": false,
  "OtherEOID_N": [],
  "Reg_3RD": false,
  "Reg_EOID": "",
  "EO_OtherID": "GLNSAMPLE",
  "Message_Type": "REO",
  "Code": "873345b2-882f-4064-91f0-90669b46c30a",
  "EO_OtherID": "XFG6GN5J5JG98VJKFHJKKJ"
}
```

3.4.1.5 Successful response sample

HTTP Status 202

```
{
  "Code": "873345b2-882f-4064-91f0-90669b46c30a",
  "EO_CODE": "873345b2-882f-4064-91f0-90669b46c30a",
  "Message_Type": "REO",
  "Error": false,
  "Errors": null,
  "Checksum": "DFG65H"
}
```

3.4.1.6 Error response sample

Processing errors

HTTP status		
<< Common response code >>		
400	ALREADY_EXISTS	Indicated that the CRUD action in add a new entity failed, as the item already exist. This is when checking of the item id already exists.

3.4.2 REOD - Data Registration of an Economic operator

3.4.2.1 Description

The REOD message is the response to the REO message. This message can be issued in an asynchronous manner and contains the EO_ID.

3.4.2.2 Description of the fields

registration of economic operator – request					
Field	Description	Data Type	Cardinality	Priority	Values
BasicInfo_Req	Block of basic information elements	Component << Basic Information Request >>	S	M	Message_Type = REOD
EO_ID	Economic operator's registered ID	EOID	S	M	
EO_Name1	Economic operator's registered name	Text(100)	S	M	
EO_Name2	Economic operator's alternative or abridged name	Text(100)	S	O	
EO_Address	address – street name, house number, postal code, city	Text(300)	S	O	
EO_Address_Name	Name part of the Address	Text(5000)	S	O	
EO_Address_StreetOne	Street part of the Address	Text(5000)	S	M	
EO_Address_StreetTwo	Second Element of the Street part of the Address	Text(5000)	S	O	
EO_Address_City	City	Text(5000)	S	M	
EO_Address_PostCode	PostalCode information	Text(5000)	S	O	
EO_CountryReg	Economic operator's country of registration	Country	S	M	See Country
EO_Email	Economic operator's email address; used to inform about registration process, incl. subsequent changes and other required correspondence	Text(5000) (Regex protected)	S	M	
VAT_R	Indication of the VAT registration status	Boolean	S	M	2 – No VAT registration 3 – VAT number exists
VAT_N	Economic operator's VAT number	Text(20)	S	M, if VAT_R = 1	

TAX_N	Economic operator's tax registration number	Text(20)	S	M, if VAT_R = 0	
EO_ExciseNumber1	Indication if the economic operator has an excise number issued by the competent authority for the purpose of identification of persons/premises	Boolean	S	M	2 – No SEED number 3 – SEED number exists
EO_ExciseNumber2	Economic operator's excise number issued by the competent authority for the purpose of identification of persons/premises	SEED	S	M, if EO_ExciseNumber1 = 1	
OtherEOID_R	Indication if the economic operator has been allocated an identifier by another ID Issuer	Boolean	S	M	2 – No 3 – Yes
OtherEOID_N	Economic operator identifier codes allocated by other ID Issuers	EOID	M	M, if OtherEOID_R = 1	
Reg_3RD	Indication if the registration is made on behalf of a retail outlet operator not otherwise involved in the tobacco trade	Boolean	S	M	2 – No 3 – Yes
Reg_EOID	Identifier of the economic operator that acts on behalf of a retail outlet operator not otherwise involved in the tobacco trade	EOID	S	M, if Reg_3RD = 1	
EO_OtherID	Optional identifier	Text(50)	S	O	
EO_CODE	Economic operator's confirmation code provided in response to the registration of economic operator	EO_CODE	S	M	
Extensibility	Optional extensibility field	Text(5000)	S	O	

3.4.2.3 Response:

Field	Description	Data Type	Cardinality	Priority	Values
BasicInfo_Resp	Block of basic information elements	Component << Basic Information	S	M	Message_Type = REOD

		Response >>			
Extensibility	Optional extensibility field	Text(5000)	S	O	

3.4.2.4 Request sample

```
{
  "EO_ID": "QCUKR+1AB020054",
  "EO_Name1": "Example Legal Entity",
  "EO_Name2": "",
  "EO_Address": "59 Legal Street",
  "EO_CountryReg": "DE",
  "EO_Email": "email@test.com",
  "VAT_R": 1,
  "VAT_N": "VATNumber 1",
  "TAX_N": "Tax",
  "EO_ExciseNumber1": 1,
  "EO_ExciseNumber2": "LA111FD",
  "OtherEOID_R": false,
  "OtherEOID_N": [ "" ],
  "Reg_3RD": false,
  "Reg_EOID": "",
  "EO_OtherID": "GLNSAMPLE",
  "Message_Type": "REO",
  "Code": "873345b2-882f-4064-91f0-90669b46c30a",
  "EO_CODE": "873345b2-882f-4064-91f0-90669b46c30a",
  "EO_OtherID": "XFG6GN5J5JG98VJKFHJKKJ"
}
```

3.4.2.5 Successful response sample

HTTP Status 202

```
{
  "Code": "6854f9a6-a2b2-4c08-8000-0173f3c35567",
  "Message_Type": "REOD",
  "Error": false,
  "Errors": null,
  "Checksum": "G6HF5H"
}
```

3.4.2.6 Error response sample

Processing errors

HTTP status		
<< Common response code >>		

3.4.3 CEO – (1.2) Correction for an economic operator identifier code

3.4.3.1 Description

Submit the information of an economic operator known to the repository in order to update 1 or more properties. This information in entirety will overwrite the previous data held regarding the master data of this economic operator. Links (for example dispatches) to / from this EO_ID will be maintained.

3.4.3.2 Description of the fields

Field	Description	Data Type	Cardinality	Priority	Values
BasicInfo_Req	Block of basic information elements	Component << Basic Information Request >>	S	M	Message_Type = CEO
EO_ID	Economic operator identifier code	EOID	S	M	
EO_CODE	Economic operator's confirmation code provided in response to the registration of economic operator	EO_CODE	S	M	
EO_Name1	Economic operator's registered name	Text(100)	S	M	
EO_Name2	Economic operator's alternative or abridged name	Text(100)	S	O	
EO_Address	address – street name, house number, postal code, city	Text(300)	S	O	
EO_Address_Name	Name part of the Address	Text(5000)	S	O	
EO_Address_StreetOne	Street part of the Address	Text(5000)	S	M	
EO_Address_StreetTwo	Second Element of the Street part of the Address	Text(5000)	S	O	
EO_Address_City	City	Text(5000)	S	M	
EO_Address_PostCode	PostalCode information	Text(5000)	S	O	
EO_CountryReg	Economic operator's country of registration	Country	S	M	See Country
EO_Email	Economic operator's email address – used to inform about registration process, incl. subsequent changes	Text(5000) (Regex protected)	S	M	

VAT_R	Indication of the VAT registration status	Boolean	S	M	0 – No VAT registration 1 – VAT number exists
VAT_N	Economic operator's VAT number	Text(20)	S	M, if VAT_R = 1	
TAX_N	Economic operator's tax registration number	Text(20)	S	M, if VAT_R = 0	
EO_ExciseNumber1	Indication if the economic operator has an excise number issued by the competent authority for the purpose of identification of persons/premises	Boolean	S	M	0 – No SEED number 1 – SEED number exists
EO_ExciseNumber2	Economic operator's excise number issued by the competent authority for the purpose of identification of persons/premises	SEED	S	M, if EO_ExciseNumber1 = 1	
OtherEOID_R	Indication if the economic operator has been allocated an identifier by another ID Issuer	Boolean	S	M	0 – No 1 – Yes
OtherEOID_N	Economic operator identifier codes allocated by other ID Issuers	EOID	M	M, if OtherEOID_R = 1	
Reg_3RD	Indication if the registration is made on behalf of a retail outlet operator not otherwise involved in the tobacco trade	Boolean	S	M	0 – No 1 – Yes
Reg_EOID	Identifier of the economic operator that acts on behalf of a retail outlet operator not otherwise involved in the tobacco trade	EOID	S	M, if Reg_3RD = 1	
Extensibility	Optional extensibility field	Text(5000)	S	O	

3.4.3.3 Response:

correction of information concerning the economic operator – response

Field	Description	Data Type	Cardinality	Priority	Values
BasicInfo_Resp	Block of basic information elements	Component << Basic Information Response >>	S	M	Message_Type = CEO
Extensibility	Optional extensibility field	Text(5000)	S	O	

3.4.3.4 Request sample

```
{
  "Message_Type": "CEO",
  "Code": "873345b2-882f-4064-91f0-90669b46c30a",
  "EO_ID": "QCUKR+1AB020054",
  "EO_CODE": "873345b2-882f-4064-91f0-90669b46c30a",
  "EO_Name1": "registrationname",
  "EO_Name2": "",
  "EO_Address": "address 1",
  "EO_CountryReg": 27,
  "EO_Email": "email@test.com",
  "VAT_R": 1,
  "VAT_N": "VATNumber 1",
  "TAX_N": "Tax",
  "EO_ExciseNumber1": 1,
  "EO_ExciseNumber2": "LA111FD",
  "OtherEOID_R": false,
  "OtherEOID_N": [ "" ],
  "Reg_3RD": false,
  "Reg_EOID": ""
}
```

3.4.3.5 Successful response sample

HTTP Status 202

```
{
  "Code": "873345b2-882f-4064-91f0-90669b46c30a",
  "Message_Type": "CEO",
  "Error": false,
  "Errors": null,
  "Checksum": "G6HF5H"
}
```

3.4.3.6 Error response sample

Processing errors

HTTP status		
<< Common response code >>		

3.4.4 DEO – (1.3) De-registration of economic operator identifier code.

3.4.4.1 Description

De-registers a previously known operator identifier for a given EO_ID

3.4.4.2 Description of the fields

De-registration of economic operator – request					
Field	Description	Data Type	Cardinality	Priority	Values
BasicInfo_Req	Block of basic information elements	Component << Basic Information Request >>	S	M	Message_Type = DEO
EO_ID	Economic operator identifier code	EOID	S	M	
EO_CODE	Economic operator's confirmation code provided in response to the registration of economic operator	EO_CODE	S	M	
Reg_3RD	Indication if the registration is made on behalf of a retail outlet operator not otherwise involved in the tobacco trade	Boolean	S	M	0 – No 1 – Yes
Reg_EOID	Identifier of the economic operator that acts on behalf of a retail outlet operator not otherwise involved in the tobacco trade	EOID	S	M, if Reg_3RD = 1	
Extensibility	Optional extensibility field	Text(5000)	S	O	

3.4.4.3 Response:

correction of information concerning the economic operator – response					
Field	Description	Data Type	Cardinality	Priority	Values
BasicInfo_Resp	Block of basic information elements	Component << Basic Information Response >>	S	M	Message_Type = DEO
Extensibility	Optional extensibility field	Text(5000)	S	O	

3.4.4.4 Request sample

```
{
  "EO_ID": "QCUKR+1AB020054",
  "EO_CODE": "873345b2-882f-4064-91f0-90669b46c30a ",
  "Reg_3RD": false,
  "Reg_EOID": "Machine Id A",
  "Code": "873345b2-882f-4064-91f0-90669b46c30a",
  "Message_Type": "DEO"
}
```

3.4.4.5 Successful response sample

HTTP Status 202

```
{
  "Code": "873345b2-882f-4064-91f0-90669b46c30a",
  "Message_Type": "DEO",
  "Error": false,
  "Errors": null,
  "Checksum": "G6HF5H"
}
```

3.4.4.6 Error response sample

Processing errors

HTTP status	
<< Common response code >>	

3.4.5 RFA – (1.4) Request for a facility identifier code

3.4.5.1 Description

Add a previously unsent / registered facility. Defined as unseen by the existence of the facility id in the repository.

3.4.5.2 Description of the fields

Request:

Registration of facility – request					
Field	Description	Data Type	Cardinality	Priority	Values
BasicInfo_Req	Block of basic information elements	Component << Basic Information Request >>	S	M	Message_Type = RFA
EO_ID	Economic operator identifier code	EOID	S	M	
EO_CODE	Economic operator's confirmation code provided in response to the registration of economic operator	EO_CODE	S	M	
F_Address_Name	Name part of the Address	Text(5000)	S	O	
F_Address_StreetOne	Street part of the Address	Text(5000)	S	M	
F_Address_StreetTwo	Second Element of the Street part of the Address	Text(5000)	S	O	
F_Address_City	City	Text(5000)	S	M	
F_Address_PostCode	PostalCode information	Text(5000)	S	O	
F_Country	Facility's country	Country	S	M	See Country
F_Type	Type of facility	Integer	S	M	See FacilityType
F_Type_Other	Description of other facility type	Text(5000)	S	M, if F_Type = 4	
F_Status	Indication if a part of the facility has a bonded warehouse status	Boolean	S	M	0 – No 1 – Yes
F_ExciseNumber1	Indication if the facility has an excise number issued by the competent authority for the purpose of identification of persons/premises	Boolean	S	M	0 – No SEED number 1 – SEED number exists

F_ExciseNum ber2	Facility's excise number issued by the competent authority for the purpose of identification of persons/premises	SEED	S	M, if F_Excise Number1 = 1	
OtherFID_R	Indication if the facility has been allocated an identifier by another ID Issuer	Boolean	S	M	0 – No 1 – Yes (possible only for non-EU facilities)
OtherFID_N	Facility identifier codes allocated by other ID Issuers	FID	M	M, if OtherFID_R = 1	
Reg_3RD	Indication if the registration is made on behalf of a retail outlet operator not otherwise involved in the tobacco trade	Boolean	S	M	0 – No 1 – Yes (possible only if F_Type = 3)
Reg_EOID	Identifier of the economic operator that acts on behalf of a retail outlet operator not otherwise involved in the tobacco trade	EOID	S	M, if Reg_3RD = 1	
Extensibility	Optional extensibility field	Text(5000)	S	O	

3.4.5.3 Response

registration of facility – response					
Field	Description	Data Type	Cardinality	Priority	Values
BasicInfo_Resp	Block of basic information elements	Component << Basic Information Response >>	S	M	Message_Type = RFA
F_ID	Facility's identifier registered	FID	S	O	Present if synchronous implementation
Extensibility	Optional extensibility field	Text(5000)	S	O	

3.4.5.4 Request sample

```
{
  "EO_ID": "QCUKR+1AB020054",
  "EO_CODE": "873345b2-882f-4064-91f0-90669b46c30a",
  "F_ID": "QCUKR<1AB020054000048",
  "F_Country": 2,
  "F_Type": "RFA2",
  "F_Type_Other": null,
  "F_Status": false,
}
```

```
"F_ExciseNumber1": false,  
"F_ExciseNumber2": null,  
"OtherFID_R": false,  
"OtherFID_N": [],  
"Reg_3RD": false,  
"Reg_EOID": null,  
"Code": "873345b2-882f-4064-91f0-90669b46c30a",  
"Message_Type": "RFA"  
}
```

3.4.5.5 Successful response sample

HTTP Status 202

```
{
  "Code": "873345b2-882f-4064-91f0-90669b46c30a",
  "Message_Type": "RFA",
  "Error": false,
  "Errors": null,
  "Checksum": "G6HF5H"
}
```

3.4.5.6 Error response sample

Processing errors

HTTP status		
<< Common response code >>		

3.4.6 RFAD – Data Registration for a facility identifier code

3.4.6.1 Description

The RFAD message is the response to the RFA message. This message can be issued in an asynchronous manner and transmit the F_ID.

3.4.6.2 Description of the fields

Registration of facility – request					
Field	Description	Data Type	Cardinality	Priority	Values
BasicInfo_Req	Block of basic information elements	Component << Basic Information Request >>	S	M	Message_Type = RFAD
EO_ID	Economic operator identifier code	EOID	S	M	
F_ID	Facility code from the RFA code issuer call	FID	S	M	
EO_CODE	Economic operator's confirmation code provided in response to the registration of economic operator	EO_CODE	S	M	
F_Address_Name	Name part of the Address	Text(5000)	S	O	
F_Address_StreetOne	Street part of the Address	Text(5000)	S	M	

F_Address_StreetTwo	Second Element of the Street part of the Address	Text(5000)	S	O	
F_Address_City	City	Text(5000)	S	M	
F_Address_PostCode	PostalCode information	Text(5000)	S	O	
F_Country	Facility's country	Country	S	M	See Country
F_Type	Type of facility	Integer	S	M	See FacilityType
F_Type_Other	Description of other facility type	Text(5000)	S	M, if F_Type = 4	
F_Status	Indication if a part of the facility has a bonded warehouse status	Boolean	S	M	2 – No 3 – Yes
F_ExciseNumber1	Indication if the facility has an excise number issued by the competent authority for the purpose of identification of persons/premises	Boolean	S	M	2 – No SEED number 3 – SEED number exists
F_ExciseNumber2	Facility's excise number issued by the competent authority for the purpose of identification of persons/premises	SEED	S	M, if F_ExciseNumber1 = 1	
OtherFID_R	Indication if the facility has been allocated an identifier by another ID Issuer	Boolean	S	M	2 – No 3 – Yes (possible only for non-EU facilities)
OtherFID_N	Facility identifier codes allocated by other ID Issuers	FID	M	M, if OtherFID_R = 1	
Reg_3RD	Indication if the registration is made on behalf of a retail outlet operator not otherwise involved in the tobacco trade	Boolean	S	M	0 – No 1 – Yes (possible only if F_Type = 3)
Reg_EOID	Identifier of the economic operator that acts on behalf of a retail outlet operator not otherwise involved in the tobacco trade	EOID	S	M, if Reg_3RD = 1	
Extensibility	Optional extensibility field	Text(5000)	S	O	

3.4.6.3 *Response*

registration of facility – response					
Field	Description	Data Type	Cardinality	Priority	Values
BasicInfo_Resp	Block of basic information elements	Component << Basic Information Response >>	S	M	Message_Type = RFAD
Extensibility	Optional extensibility field	Text(5000)	S	O	

3.4.6.4 *Request sample*

```
{
  "EO_ID": "QCUKR+1AB020054",
  "EO_CODE": "873345b2-882f-4064-91f0-90669b46c30a",
  "F_ID": "QCUKR<1AB020054000048",
  "F_Country": 2,
  "F_Type": "RFA2",
  "F_Type_Other": null,
  "F_Status": false,
  "F_ExciseNumber1": false,
  "F_ExciseNumber2": null,
  "OtherFID_R": false,
  "OtherFID_N": [],
  "Reg_3RD": false,
  "Reg_EOID": null,
  "Code": "873345b2-882f-4064-91f0-90669b46c30a",
  "Message_Type": "RFAD"
}
```

3.4.6.5 *Successful response sample*

HTTP Status 202

```
{
  "Code": "873345b2-882f-4064-91f0-90669b46c30a",
  "Message_Type": "RFAD",
  "Error": false,
  "Errors": null,
  "Checksum": "G6HF5H"
}
```

3.4.6.6 *Error response sample*

Processing errors

HTTP status	
<< Common response code >>	

3.4.7 CFA – (1.5) Correction of information concerning the facility identifier code

3.4.7.1 Description

Submit the information of a facility known to the repository in order to update one or more properties. This information in entirety will overwrite the previous data held regarding the master data of this facility. Links (for example dispatches) to / from this F_ID will be maintained.

3.4.7.2 Description of the fields

correction of information concerning the facility – request					
Field	Description	Data Type	Cardinality	Priority	Values
BasicInfo_Req	Block of basic information elements	Component << Basic Information Request >>	S	M	Message_Type = CFA
EO_ID	Economic operator identifier code	EOID	S	M	
EO_CODE	Economic operator's confirmation code provided in response to the registration of economic operator	EO_CODE	S	M	
F_ID	Facility identifier code	FID	S	M	
EO_Address	address – street name, house number, postal code, city	Text(300)	S	O	
EO_Address_Name	Name part of the Address	Text(5000)	S	O	
EO_Address_StreetOne	Street part of the Address	Text(5000)	S	M	
EO_Address_StreetTwo	Second Element of the Street part of the Address	Text(5000)	S	O	
EO_Address_City	City	Text(5000)	S	M	
EO_Address_PostCode	PostalCode information	Text(5000)	S	O	
F_Country	Facility's country	Country	S	M	See Country
F_Type	Type of facility	Integer	S	M	See FacilityType
F_Type_Other	Description of other facility type	Text(5000)	S	M, if F_Type = 4	
F_Status	Indication if a part of the facility has a bonded warehouse status	Boolean	S	M	0 – No 1 – Yes

F_ExciseNumber1	Indication if the facility has an excise number issued by the competent authority for the purpose of identification of persons/premises	Boolean	S	M	0 – No SEED number 1 – SEED number exists
F_ExciseNumber2	Facility's excise number issued by the competent authority for the purpose of identification of persons/premises	SEED	S	M, if F_ExciseNumber1 = 1	
OtherFID_R	Indication if the facility has been allocated an identifier by another ID Issuer	Boolean	S	M	0 – No 1 – Yes (possible only for non-EU facilities)
OtherFID_N	Facility identifier codes allocated by other ID Issuers	FID	M	M, if OtherFID_R = 1	
Reg_3RD	Indication if the registration is made on behalf of a retail outlet operator not otherwise involved in the tobacco trade	Boolean	S	M	0 – No 1 – Yes (possible only if F_Type = 3)
Reg_EOID	Identifier of the economic operator that acts on behalf of a retail outlet operator not otherwise involved in the tobacco trade	EOID	S	M, if Reg_3RD = 1	
Extensibility	Optional extensibility field	Text(5000)	S	O	

3.4.7.3 Response

correction of information concerning the facility – response					
Field	Description	Data Type	Cardinality	Priority	Values
BasicInfo_Resp	Block of basic information elements	Component << Basic Information Response >>	S	M	Message_Type = CFA
Extensibility	Optional extensibility field	Text(5000)	S	O	

3.4.7.4 Request sample

```
{
  "EO_ID": "QCUKR+1AB020054",
  "EO_CODE": "873345b2-882f-4064-91f0-90669b46c30a ",
  "F_ID": "QCUKR<1AB020054000048",
  "F_Country": 2,
  "F_Type": "CFA",
  "F_Type_Other": null,
  "F_Status": false,
  "F_ExciseNumber1": false,
```

```
"F_ExciseNumber2": null,
"OtherFID_R": false,
"OtherFID_N": [],
"Reg_3RD": false,
"Reg_EOID": null,
"Code": "873345b2-882f-4064-91f0-90669b46c30a",
"Message_Type": "CFA"
}
```

3.4.7.5 *Successful response sample*

HTTP Status 202

```
{
  "Code": "873345b2-882f-4064-91f0-90669b46c30a",
  "Message_Type": "CFA",
  "Error": false,
  "Errors": null,
  "Checksum": "G6HF5H"
}
```

3.4.7.6 *Error response sample*

Processing errors

HTTP status		
	<< Common response code >>	

3.4.8 DFA – (1.6) De-registration of facility identifier code

3.4.8.1 Description

De-registers a previously known facility for a given F_ID

3.4.8.2 Description of the fields

de-registration of facility – request					
Field	Description	Data Type	Cardinality	Priority	Values
BasicInfo_Req	Block of basic information elements	Component << Basic Information Request >>	S	M	Message_Type = DFA
EO_ID	Economic operator identifier code	EOID	S	M	
EO_CODE	Economic operator's confirmation code provided in response to the registration of economic operator	EO_CODE	S	M	
F_ID	Facility identifier code	FID	S	M	
Reg_3RD	Indication if the deregistration is made on behalf of a retail outlet operator not otherwise involved in the tobacco trade	Boolean	S	M	0 – No 1 – Yes
Reg_EOID	Identifier of the economic operator that acts on behalf of a retail outlet operator not otherwise involved in the tobacco trade	EOID	S	M, if Reg_3RD = 1	
Extensibility	Optional extensibility field	Text(5000)	S	O	

3.4.8.3 Response:

de-registration of facility – response					
Field	Description	Data Type	Cardinality	Priority	Values
BasicInfo_Resp	Block of basic information elements	Component << Basic Information Response >>	S	M	Message_Type = DFA
Extensibility	Optional extensibility field	Text(5000)	S	O	

3.4.8.4 Request sample

```
{
  "EO_ID": "QCUKR+1AB020054",
```

```

"EO_CODE": "873345b2-882f-4064-91f0-90669b46c30a",
"F_ID": "QCUKR<1AB020054000048",
"Reg_3RD": false,
"Reg_EOID": null,
"Code": "873345b2-882f-4064-91f0-90669b46c30a",
"Message_Type": "DFA"
}

```

3.4.8.5 Successful response sample

HTTP Status 202

```

{
  "Code": "873345b2-882f-4064-91f0-90669b46c30a",
  "Message_Type": "DFA",
  "Error": false,
  "Errors": null,
  "Checksum": "G6HF5H"
}

```

3.4.8.6 Error response sample

Processing errors

HTTP status		
	<< Common response code >>	

3.4.9 RMA – (1.7) Request for a machine identifier code

3.4.9.1 Description

Submit the information for the first registration of a machine.

3.4.9.2 Description of the fields

Registration of manufacturing machine – request					
Field	Description	Data Type	Cardinality	Priority	Values
BasicInfo_Req	Block of basic information elements	Component << Basic Information Request >>	S	M	Message_Type = RMA
EO_ID	Economic operator identifier code	EOID	S	M	
EO_CODE	Economic operator's confirmation code provided in response to the registration of economic operator	EO_CODE	S	M	
F_ID	Facility identifier code	FID	S	M	
M_Producer	Machine producer	Text(200)	S	M	
M_Model	Machine model	Text(200)	S	M	

M_Number	Machine serial number	Text(200)	S	M	
M_Capacity	Maximum capacity over 24hour production cycle expressed in unit packets	Integer	S	M	
Extensibility	Optional extensibility field	Text(5000)	S	O	

3.4.9.3 Response:

registration of manufacturing machine – response					
Field	Description	Data Type	Cardinality	Priority	Values
BasicInfo_Resp	Block of basic information elements	Component << Basic Information Response >>	S	M	Message_Type = RMA
M_ID	Machine identifier received from the RMA request made to the code issuer.	MID	S	M	
Extensibility	Optional extensibility field	Text(5000)	S	O	

3.4.9.4 Request sample

```
{
  "EO_ID": "QCUKR+1AB020054",
  "M_ID": "QCUKR>1AB020054000012",
  "EO_CODE": "873345b2-882f-4064-91f0-90669b46c30a",
  "F_ID": "QCUKR<1AB020054000048",
  "M_Producer": "Producer1",
  "M_Model": "model1",
  "M_Number": "MachineNumber",
  "M_Capacity": 533,
  "Code": "873345b2-882f-4064-91f0-90669b46c30a",
  "Message_Type": "RMA"
}
```

3.4.9.5 Successful response sample

HTTP Status 202

```
{
  "Code": "873345b2-882f-4064-91f0-90669b46c30a",
  "Message_Type": "RMA",
  "Error": false,
  "Errors": null,
  "Checksum": "G6HF5H"
}
```

3.4.9.6 Error response sample

Processing errors

HTTP status		
<< Common response code >>		

3.4.10 RMAD– Data Request for a machine identifier code

3.4.10.1 Description

The RMAD message is the response to the RMA message. This message can be issued in an asynchronous manner and transmit the M_ID.

3.4.10.2 Description of the fields

Registration of manufacturing machine – request					
Field	Description	Data Type	Cardinality	Priority	Values
BasicInfo_Req	Block of basic information elements	Component << Basic Information Request >>	S	M	Message_Type = RMAD
EO_ID	Economic operator identifier code	EOID	S	M	
M_ID	Machine identifier received from the RMA request made to the code issuer.	EOID	S	M	
EO_CODE	Economic operator's confirmation code provided in response to the registration of economic operator	EO_CODE	S	M	
F_ID	Facility identifier code	FID	S	M	
M_Producer	Machine producer	Text(20)	S	M	
M_Model	Machine model	Text(20)	S	M	
M_Number	Machine serial number	Text(20)	S	M	
M_Capacity	Maximum capacity over 24hour production cycle expressed in unit packets	Integer	S	M	
Extensibility	Optional extensibility field	Text(5000)	S	O	

3.4.10.3 Response:

registration of manufacturing machine – response					
Field	Description	Data Type	Cardinality	Priority	Values
BasicInfo_Resp	Block of basic information elements	Component << Basic Information Response >>	S	M	Message_Type = RMAD

Extensibility	Optional extensibility field	Text(5000)	S	O	
---------------	------------------------------	------------	---	---	--

3.4.10.4 Request sample

```
{
  "EO_ID": "QCUKR+1AB020054",
  "M_ID": "QCUKR>1AB020054000012" ,
  "EO_CODE": "873345b2-882f-4064-91f0-90669b46c30a " ,
  "F_ID": "QCUKR<1AB020054000048",
  "M_Producer": "Producer1",
  "M_Model": "model1",
  "M_Number": "MachineNumber",
  "M_Capacity": 533,
  "Code": "873345b2-882f-4064-91f0-90669b46c30a",
  "Message_Type": "RMAD"
}
```

3.4.10.5 Successful response sample

HTTP Status 202

```
{
  "Code": "873345b2-882f-4064-91f0-90669b46c30a",
  "Message_Type": "RMAD",
  "Error": false,
  "Errors": null,
  "Checksum": "G6HF5H"
}
```

3.4.10.6 Error response sample

Processing errors

HTTP status	
<< Common response code >>	

3.4.11 CMA – (1.8) Correction of information concerning the machine identifier code

3.4.11.1 Description

Submit the information of a machine known to the repository in order to update one or more properties. This information in entirety will overwrite the previous data held regarding the master data of this machine. Links (for example dispatches) to / from this M_ID will be maintained.

3.4.11.2 Description of the fields

Field	Description	Data Type	Cardinality	Priority	Values
BasicInfo_Req	Block of basic information elements	Component << Basic Information Request >>	S	M	Message_Type = CMA
EO_ID	Economic operator identifier code	EOID	S	M	
EO_CODE	Economic operator's confirmation code provided in response to the registration of economic operator	EO_CODE	S	M	
F_ID	Facility identifier code	FID	S	M	
M_ID	Machine identifier code	MID	S	M	
M_Producer	Machine producer	Text(200)	S	M	
M_Model	Machine model	Text(200)	S	M	
M_Number	Machine serial number	Text(200)	S	M	
M_Capacity	Maximum capacity over 24hour production cycle expressed in unit packets	Integer	S	M	
Extensibility	Optional extensibility field	Text(5000)	S	O	

3.4.11.3 Response:

correction of information concerning the manufacturing machine – response					
Field	Description	Data Type	Cardinality	Priority	Values
BasicInfo_Resp	Block of basic information elements	Component << Basic Information Response >>	S	M	Message_Type = CMA
Extensibility	Optional extensibility field	Text(5000)	S	O	

3.4.11.4 Request sample

```
{
  "EO_ID": "QCUKR+1AB020054",
```

```

"EO_CODE": "873345b2-882f-4064-91f0-90669b46c30a",
"F_ID": "QCUKR<1AB020054000048",
"M_ID": "QCUKR>1AB020054000012",
"M_Producer": "Producer1",
"M_Model": "model1",
"M_Number": "MachineNumber",
"M_Capacity": 533,
"Code": "873345b2-882f-4064-91f0-90669b46c30a",
"Message_Type": "CMA"
}

```

3.4.11.5 Successful response sample

HTTP Status 202

```

{
  "Code": "873345b2-882f-4064-91f0-90669b46c30a",
  "Message_Type": "CMA",
  "Error": false,
  "Errors": null,
  "Checksum": "G6HF5H"
}

```

3.4.11.6 Error response sample

Processing errors

HTTP status		
<< Common response code >>		

3.4.12 DMA – (1.9) De-registration of machine identifier code

3.4.12.1 Description

De-registers a previously known machine for a given M_ID

3.4.12.2 Description of the fields

de-registration of manufacturing machine – request					
Field	Description	Data Type	Cardinality	Priority	Values
BasicInfo_Req	Block of basic information elements	Component << Basic Information Request >>	S	M	Message_Type = DMA
EO_ID	Economic operator identifier code	EOID	S	M	
EO_CODE	Economic operator's confirmation code provided in response to the registration of economic operator	EO_CODE	S	M	
F_ID	Facility identifier code	FID	S	M	

M_ID	Machine identifier code	MID	S	M	
Extensibility	Optional extensibility field	Text(5000)	S	O	

3.4.12.3 Response:

De-registration of manufacturing machine – response					
Field	Description	Data Type	Cardinality	Priority	Values
BasicInfo_Resp	Block of basic information elements	Component << Basic Information Response >>	S	M	Message_Type = DMA
Extensibility	Optional extensibility field	Text(5000)	S	O	

3.4.12.4 Request sample

```
{
  "EO_ID": "QCUKR+1AB020054",
  "EO_CODE": "873345b2-882f-4064-91f0-90669b46c30a",
  "F_ID": "QCUKR<1AB020054000048",
  "M_ID": "QCUKR>1AB020054000012",
  "Code": "873345b2-882f-4064-91f0-90669b46c30a",
  "Message_Type": "DMA"
}
```

3.4.12.5 Successful response sample

HTTP Status 202

```
{
  "Code": "873345b2-882f-4064-91f0-90669b46c30a",
  "Message_Type": "DMA",
  "Error": false,
  "Errors": null,
  "Checksum": "G6HF5H"
}
```

3.4.12.6 Error response sample

Processing errors

HTTP status		
<< Common response code >>		

3.4.13 ICV – Validate existence of EOID, FID and the MID.

3.4.13.1 Description

Provides the capability for ID Issuers and Primary repositories to check the existence and the activation status of Identifier codes (EOID, FID and MID) and the respective relations.

3.4.13.2 Description of the fields

Validate existence of EO-ID, F-ID and the M-ID.– request					
Field	Description	Data Type	Cardinality	Priority	Values
BasicInfo_Req	Block of basic information elements	Component << Basic Information Request >>	S	M	Message_Type = ICV
EO_IDS	A list of EOIDs to check for existence	EOID	M	O	
F_IDS	A list of FIDs to check for existence	FID	M	O	
M_IDS	A list of MIDs to check for existence	MID	M	O	
R_EOF	A list of relation of EOID and FID to check for existence	Text (Array limit = 2. String text limit = 5000)	M	O	
R_EOFM	A list of relation of EOID, FID and MID to check for existence	Text (Array limit = 3. String text limit = 5000)	M	O	
ICV_Type		Integer	S	O	1– request the Activation information, only available for ID Issuers - Other- only existence is provided

3.4.13.3 Response:

Validate existence of EO-ID, F-ID and the M-ID.– response					
Field	Description	Data Type	Cardinality	Priority	Values
BasicInfo_Resp	Block of basic information elements	Component << Basic Information Response >>	S	M	Message_Type = ICV
EO_IDS_EXIST	List of EO_IDs that exist	Boolean	M	O	0 – False 1 - True

F_IDS_EXIST	List of FO_IDs that exist	Boolean	M	O	0 – False 1 - True
M_IDS_EXIST	List of MO_IDs that exist	Boolean	M	O	0 – False 1 - True
EO_IDS_ACTIVE	List of EO_IDs that are active	Boolean	M	M – when ICV_TYPE = 1 only available for ID Issuer	0 – False 1 - True
F_IDS_ACTIVE	List of FO_IDs that are active	Boolean	M	M – when ICV_TYPE = 1 only available for ID Issuer	0 – False 1 - True
M_IDS_ACTIVE	List of MO_IDs that are active	Boolean	M	M – when ICV_TYPE = 1 only available for ID Issuer	0 – False 1 - True
R_EOF_EXIST	List of R_EOF that exist	Boolean	M	O	0 – False 1 - True
R_EOFM_EXIST	List of R_EOFM that exist	Boolean	M	O	0 – False 1 - True

3.4.13.4 Request sample

```
{
  "Message_Type": "ICV",
  "ICV_Type": 1,
  "EO_IDS": ["QCUKR+1AB020054", "QCBDR+1DE020055"],
  "F_IDS": ["QCUKR<1AB020054000048", "QCUKR<1AB020054000049"],
  "M_IDS": ["QCUKR>1AB020054000012", "QCUKR>1AB020054000013"],
  "R_EOF": [
    ["QCUKR+1AB020054", "QCUKR<1AB020054000048"],
    ["QCUKR+1AB020054", "QCUKR>1AB020054000012"]],
  "R_EOFM": [
    ["QCUKR+1AB020054", "QCUKR<1AB020054000048", "QCUKR>1AB020054000012"],
    ["QCUKR+1AB020054", "QCUKR>1AB020054000012", "QCUKR>1AB020054000012"]],
  "Code": null
}
```

3.4.13.5 Successful response sample

HTTP Status 202 (Primary repository)

```
{
  "Code": "873345b2-882f-4064-91f0-90669b46c30a",
  "Message_Type": "ICV",
  "EO_IDS_EXIST": [true, true],
  "F_IDS_EXIST": [true, true],
  "M_IDS_EXIST": [true, false],
  "R_EOF_EXIST": [true, false],
  "R_EOFM_EXIST": [true, false],
  "Error": false,
}
```



```

"Errors": null,
"Checksum": "G6HF5H"
}

```

Example here shows that the 2nd MID is the only one that does not exist in the EU wide registry. Also that the to the economic operator to facility relation is wrong on the 2nd. Also that the facility to machine relation is detected as wrong on the 2nd.

3.4.13.1 Successful response sample ICV_Type = 1

HTTP Status 202 (ID Issuer)

```

{
  "Code": "873345b2-882f-4064-91f0-90669b46c30a",
  "Message_Type": "ICV",
  "EO_IDS_EXIST": [true, true],
  "F_IDS_EXIST ": [true, true],
  "M_IDS_EXIST ": [true, false],
  "EO_IDS_ACTIVE": [true, true],
  "F_IDS_ACTIVE ": [true, true],
  "M_IDS_ACTIVE ": [true, false],
  "R_EOF_EXIST ": [true, false],
  "R_EOFM_EXIST ": [true, false],
  "Error": false,
  "Errors": null,
  "Checksum": "G6HF5H"
}

```

3.4.13.2 Error response sample

Processing errors

HTTP status		
<< Common response code >>		

3.5 Unique identifiers Messages

3.5.1 ISU – (2.1) Request for unit level UIs

3.5.1.1 Description

Request for reporting the issuance of serial numbers at unit packet level

3.5.1.2 Description of the fields

Request for unit level UIs – request					
Field	Description	Data Type	Cardinality	Priority	Values
BasicInfo_Request	Block of basic information elements	Component << Basic Information Request >>	S	M	Message_Type = ISU
EO_ID	Economic operator identifier code of the submitting entity (either EU manufacturer or EU importer)	EOID	S	M	
F_ID	Facility identifier code	FID	S	M	
Process_Type	Indication if the production process involves machinery	Boolean	S	M	0 – No (only for fully hand made products) 1 – Yes
M_ID	Machine identifier code	MID	S	M, if Process_Type = 1	
P_Type	Type of tobacco product	Integer	S	M	See TobaccoProductType
P_OtherType	Description of other type of tobacco product	Text(200)	S	M, if P_Type = 11 (other tobacco product)	
P_CN	Combined Nomenclature (CN) code	Text(200)	S	O	
P_weight	Average gross weight of unit packet, including packaging, in grams with 0,1 gram accuracy	lineDecimal	S	M	
P_Brand	Brand of tobacco product	Text(200)	S	M	
TP_ID	The identification number of the product used in the EU-CEG system.	TPID	S	M, if Intended_Market is an EU country	
TP_PN	Tobacco product number used in the EU-CEG system	PN	S	M, if Intended_Market is an EU country	
Intended_Market	Intended country of retail sale.	Country	S	M	
Intended_Route1	Indication if the product is intended to be moved across country borders with terrestrial transport.	Boolean	S	M	0 – No 1 – Yes
Intended_Route2	The first country of terrestrial transport after the product	Country	S	M, if Intended	

Request for unit level UIs – request					
Field	Description	Data Type	Cardinality	Priority	Values
	leaves the Member State of manufacturing or the Member State of importation.			_Route1 = 1	
Import	Indication if the product is imported into the EU	Boolean	S	M	0 – No 1 – Yes
Req_Quantity	Requested quantity of unit packet level UIs	Integer	S	M	
P_OtherID	Optional Product ID	Text(20)	S	O	

3.5.1.3 Response:

Request for unit level UIs – response					
Field	Description	Data Type	Cardinality	Priority	Values
BasicInfo_Resp	Block of basic information elements	Component << Basic Information Response >>	S	M	Message_Type = ISU

3.5.1.4 Request sample

```
{
  "EO_ID": "QCUKR+1AB020054",
  "F_ID": "QCUKR<1AB020054000049"
  "Process_Type": false,
  "M_ID": "Machine Id A",
  "P_Type": 2,
  "P_OtherType": null,
  "P_CN": "FG7H68FHF",
  "P_Brand": "Product brand A",
  "P_Weight": 10.0,
  "TP_ID": "1234",
  "TP_PN": "1234",
  "Intended_Market": "BG",
  "Intended_Route1": true,
  "Intended_Route2": "BG",
  "Import": false,
  "Req_Quantity": 2,
  "P_OtherID": "GTINSAMPLE",
  "Code": null,
  "Message_Type": "ISU"
}
```

3.5.1.5 Successful response sample

HTTP Status 202

```
{
  "Code": "873345b2-882f-4064-91f0-90669b46c30a",
  "Message_Type": "ISU",
  "Error": false,
  "Errors": null,
  "Checksum": "G6HF5H"
}
```

3.5.1.6 Error response sample

Processing errors

HTTP status		
<< Common response code >>		

Error body sample

```
{
  "Code": "873345b2-882f-4064-91f0-90669b46c30a",
  "Message_Type": null,
  "Error": true,
  "Errors": [
    {
      "Error_InternalID": "yndkFz7TBEO706frD38hzA",
      "Error_Code": "INVALID_REQUEST_FORMAT",
      "Error_Descr": "The EconomicOperatorIdentifier field is required."
    }
  ]
}
```

3.5.2 IRU – Message to report the issuance of serial numbers at unit packet level

3.5.2.1 Description

Request for reporting the issuance of serial numbers at unit packet level

3.5.2.2 Description of the fields

request for reporting the issuance of serial numbers at unit packet level – request					
Field	Description	Data Type	Cardinality	Priority	Values
BasicInfo_Request	Block of basic information elements	Component << Basic Information Request >>	S	M	Message_Type = IRU
Event_Time	Intended time of event occurrence	Time(s)	S	M	
Message_Time_long	Message sending Time	Time(L)	S	M	
EO_ID	Economic operator identifier code of the submitting entity (either EU manufacturer or EU importer)	EOID	S	M	
F_ID	Facility identifier code	FID	S	M	
Process_Type	Indication if the production process involves machinery	Boolean	S	M	0 – No (only for fully hand made products) 1 – Yes
M_ID	Machine identifier code	MID	S	M, if Process_Type = 1	

request for reporting the issuance of serial numbers at unit packet level – request					
Field	Description	Data Type	Cardinality	Priority	Values
P_Type	Type of tobacco product	Integer	S	M	See TobaccoProductType
P_OtherType	Description of other type of tobacco product	Text(200)	S	M, if P_Type = 11 (other tobacco product)	
P_CN	Combined Nomenclature (CN) code	Text(200)	S	O	
P_Brand	Brand of tobacco product	Text(200)	S	M	
P_weight	Average gross weight of unit packet, including packaging, in grams with 0,1 gram accuracy	Decimal	S	M	
TP_ID	The identification number of the product used in the EU-CEG system.	TPID	S	M, if Intended_Market is an EU country	
TP_PN	Tobacco product number used in the EU-CEG system	PN	S	M, if Intended_Market is an EU country	
Intended_Market	Intended country of retail sale.	Country	S	M	
Intended_Route1	Indication if the product is intended to be moved across country borders with terrestrial transport.	Boolean	S	M	0 – No 1 – Yes
Intended_Route2	The first country of terrestrial transport after the product leaves the Member State of manufacturing or the Member State of importation.	Country	S	M, if Intended_Route1 = 1	
Import	Indication if the product is imported into the EU	Boolean	S	M	0 – No 1 – Yes
Req_Quantity	Requested quantity of unit packet level UIs – for the current IRU message	Integer	S	M	
Order_Req_Quantity	Total Order Request quantity of unit packet level UIs.	Integer	S	O	
Order_number	Optional EO Request Order Number	Text(50)	S	O	
P_OtherID	Optional Product ID	Text(20)	S	O	
upUI	List of unit packet level UI issued by the ID Issuer.	upUI(L) without timestamp	M	M	

3.5.2.3 Response:

request for reporting the issuance of serial numbers at unit packet level – response					
Field	Description	Data Type	Cardinality	Priority	Values
BasicInfo_Resp	Block of basic information elements	Component << Basic Information Response >>	S	M	Message_Type = IRU

request for reporting the issuance of serial numbers at unit packet level – response					
Field	Description	Data Type	Cardinality	Priority	Values
RecallExpiry_Time	Calculation of the Expiry date	Time(L)	S	M	

3.5.2.4 Business Validation

	IRU (2.1)
Business rule validation	
Entity Validation	
VAL_ENT_EXIST_EOID	EO_ID
VAL_ENT_EXIST_FID	F_ID
VAL_ENT_EXIST_MID	M_ID
VAL_ENT_ACTIVE_EOID	EO_ID
VAL_ENT_ACTIVE_FID	F_ID
VAL_ENT_ACTIVE_MID	M_ID
VAL_ENT_REL_EOID_FID	EO_ID, F_ID * Note that the case of import will not require this validation.
VAL_ENT_REL_FID_MID	F_ID, M_ID

3.5.2.5 UI duplicate validation

The response to the 2.1 requests that is performed by the ID Issuer to the Router also known as IRU event. This event as all events are limited to 6MB. This hard limit implies that the IRU message contains for the current ID Issuers specifications between 180 000 and 230 000 upUIs depending on the size and structure of the upUIs.

The online validation is limited to 50 000 UI against the billions of UI. In an effort to not reduce the size of the IRU to 50 000 Uis it has been decided to split the validation into online validation and offline validation.

IRU online validation will focus on the technical validation. The response to the IRU will be don within the SLA (60 sec)

IRU offline validation is performed just after the online validation and takes a few minutes. During the offline validation the Secondary repository checks the unicity of the UI against the complete database. In case of success, the IRU message is forwarded to the primary repository

A detection of duplicate UI is considered as exceptional event and is managed on an operational exception. Dentsu Operation team contacts the ID Issuer team in order to address the issue. The IRU will NOT BE FORWARDED to the primary repository in order to avoid any propagation of the duplicates by generating potential side effects on the primary repositories.

3.5.2.6 Request sample

```
{
  "EO_ID": "QCUKR+1AB020054",
  "F_ID": "QCUKR<1AB020054000049",
  "Event_Time": "19032014",
  "Message_Time_Long": "2019-03-20T14:16:45Z",
  "Process_Type": 0,
  "M_ID": "Machine Id A",
  "P_Type": 2,
  "P_OtherType": null,
  "P_CN": "FG7H68FHF",
  "P_Brand": "Product brand A",
  "P_Weight": 10.0,
  "TP_ID": "1234",
  "TP_PN": "1234",
  "Intended_Market": "BG",
  "Intended_Route1": 1,
  "Intended_Route2": "BG",
  "Import": false,
  "Req_Quantity": 2,
  "upUI": ["DANXXXXXXXXXXXX1PR0123456789", "DANXXXXXXXXXXXX2PR0123456789"],
  "Code": null,
  "Message_Type": "IRU"
}
```

3.5.2.7 Successful response sample

HTTP Status 202

```
{
  "Code": "873345b2-882f-4064-91f0-90669b46c30a",
  "Message_Type": "IRU",
  "RecallExpiry_Time": "19092014",
  "Error": false,
  "Errors": null,
  "Checksum": "G6HF5H"
}
```

3.5.2.8 Error response sample

Processing errors

HTTP status	Error Code	Error Description
<< Common response code >>		
400	EOID_NOT_EXIST_OR_ACTIVE	VAL_ENT_EXIST_EOID
400	FID_NOT_EXIST_OR_ACTIVE	VAL_ENT_EXIST_FID
400	MID_NOT_EXIST_OR_ACTIVE	VAL_ENT_EXIST_MID
400	EOID_NOT_EXIST_OR_ACTIVE	VAL_ENT_ACTIVE_EOID
400	FID_NOT_EXIST_OR_ACTIVE	VAL_ENT_ACTIVE_FID
400	MID_NOT_EXIST_OR_ACTIVE	VAL_ENT_ACTIVE_MID
400	FID_NOT_RELATED_TO_EOID	VAL_ENT_REL_EOID_FID
400	MID_NOT_RELATED_TO_FID	VAL_ENT_REL_FID_MID

Error body sample

```
{
  "Code": null,
  "Message_Type": null,
  "Error": true,
  "Errors": [
    {
      "Error_InternalID": "yndkFz7TBEO706frD38hzA",
      "Error_Code": "INVALID_REQUEST_FORMAT",
      "Error_Descr": "The EconomicOperatorIdentifier field is required."
    }
  ]
}
```

3.5.3 IRUD – Message to report the issuance of serial numbers at unit packet level callback

3.5.3.1 Description

This IRUD callback message is a response to the original IRU message indicating the delivery status of IRU message.

3.5.3.2 Description of the fields

IRUD – request					
Field	Description	Data Type	Cardinality	Priority	Values
Message_Type	The identifier of the type of message	Text	S	M	Message_Type = IRUD
IRU_Code	IRU recallCode		S	M	
IRU_Status	The status of the delivery of a specific IRU message	Boolean	S	M	0 – False 1 – True
IRU_Status_Description	Description of the status or the error message	Text	S	O	
Error	Indicates the failure of the message reception	Boolean	S	M	0 – No 1- Yes
Errors	Array containing Error_Code, Error_Descr, InternalId	Text	S	M if Error = 1	

3.5.3.3 Response:

IRUD – response					
Field	Description	Data Type	Cardinality	Priority	Values
Message_Type	The identifier of the type of message	Text	S	M	Message_Type = IRUD
Code	Unique identifier of the message. Used for recall too.	Text(50)	S	M	
Error	Indicates the failure of the message reception	Boolean	S	M	0 – No 1- Yes
Errors	Array containing Error_Code, Error_Descr, InternalId	Text	S	M if Error = 1	

3.5.3.4 Request sample

```
{
  "Code": "873345b2-882f-4064-91f0-90669b46c30b",
  "Message_Type": "IRUD",
  "IRU_Code": "873345b2-882f-4064-91f0-90669b46c30a"
  "IRU_Status": 0,
  "IRU_Status_Description": "optional description",
  "Error": false,
  "Errors": null,
}
```

3.5.3.5 Successful response sample

HTTP Status 200

```
{
  "Message_Type": "IRUD",
  "Code": "873345b2-882f-4064-91f0-90669b46c30a",
  "Error": false,
  "Errors": null,
  "Checksum": "G6HF5H"
}
```

3.5.4 ISA – (2.2) Request for aggregated level UIs

3.5.4.1 Description

Request for reporting the issuance of serial numbers at aggregated level

3.5.4.2 Description of the fields

request for reporting the issuance of serial numbers at aggregated level – request					
Field	Description	Data Type	Cardinality	Priority	Values
BasicInfo_Req	Block of basic information elements	Component << Basic Information Request >>	S	M	Message_Type = ISA
EO_ID	Economic operator identifier code of the submitting entity	EOID	S	M	
F_ID	Facility identifier code	FID	S	M	
Req_Quantity	Requested quantity of aggregated level UIs	Integer	S	M	

3.5.4.3 Response:

request for reporting the issuance of serial numbers at aggregated level – response					
Field	Description	Data Type	Cardinality	Priority	Values
BasicInfo_Resp	Block of basic information elements	Component << Basic Information Response >>	S	M	Message_Type = ISA

3.5.4.4 Request sample

```
{
  "EO_ID": "QCUKR+1AB020054",
  "F_ID": "QCUKR<1AB020054000049",
  "Req_Quantity": 2,
  "Message_Type": "ISA",
  "Code": "873345b2-882f-4064-91f0-90669b46c30a",
}
```

3.5.4.5 Successful response sample

HTTP Status 202

```
{
  "Code": "873345b2-882f-4064-91f0-90669b46c30a",
  "Message_Type": "ISA",
  "Error": false,
  "Errors": null,
  "Checksum": "G6HF5H"
}
```

3.5.4.6 Error response sample

Processing errors

HTTP status		
<< Common response code >>		

3.5.5 IRA – Request for reporting the issuance of serial numbers at aggregated level

3.5.5.1 Description

Request for reporting the issuance of serial numbers at aggregated level

3.5.5.2 Description of the fields

request for reporting the issuance of serial numbers at aggregated level – request					
Field	Description	Data Type	Cardinality	Priority	Values
BasicInfo_Req	Block of basic information elements	Component << Basic Information Request >>	S	M	Message_Type = IRA
Event_Time	Intended time of event occurrence	Time(s)	S	M	
Message_Time_Long	Message sending Time	Time(L)	S	M	
EO_ID	Economic operator identifier code of the submitting entity	EOID	S	M	
F_ID	Facility identifier code	FID	S	M	
Req_Quantity	Requested quantity of aggregated level UIs	Integer	S	M	
aUI	List of aggregated level UIs	aUI	M	M	

3.5.5.3 Response:

request for reporting the issuance of serial numbers at aggregated level – response					
Field	Description	Data Type	Cardinality	Priority	Values
BasicInfo_Resp	Block of basic information elements	Component << Basic Information Response >>	S	M	Message_Type = IRA

3.5.5.4 Business Validation

IRA (2.2)	
Business rule validation	Fields in the scope of the control
Entity Validation	
VAL_ENT_EXIST_EOID	EO_ID
VAL_ENT_EXIST_FID	F_ID
VAL_ENT_ACTIVE_EOID	EO_ID
VAL_ENT_ACTIVE_FID	F_ID
VAL_ENT_REL_EOID_FID	EO_ID, F_ID
VAL_ENT_REL_FID_MID	EO_ID, F_ID

3.5.5.5 Request sample

```
{
  "EO_ID": "QCUKR+1AB020054",
  "F_ID": "QCUKR<1AB020054000049",
  "Event_Time": "19032014",
  "Message_Time_Long": "2019-03-20T14:16:45Z",
  "Req_Quantity": 2,
  "aUI": ["DANXXXXXXXXXXXXX1FA000001", "DANXXXXXXXXXXXXX2FA000001" ],
  "Message_Type": "IRA",
  "Code": "873345b2-882f-4064-91f0-90669b46c30a",
}
```

3.5.5.6 Successful response sample

HTTP Status 202

```
{
  "Code": "873345b2-882f-4064-91f0-90669b46c30a",
  "Message_Type": "IRA",
  "Error": false,
  "Errors": null,
  "Checksum": "G6HF5H"
}
```

3.5.5.7 Error response sample

HTTP status	Error Code	Error Description
<< Common response code >>		
400	EOID_NOT_EXIST_OR_ACTIVE	VAL_ENT_EXIST_EOID
400	FID_NOT_EXIST_OR_ACTIVE	VAL_ENT_EXIST_FID
400	EOID_NOT_EXIST_OR_ACTIVE	VAL_ENT_ACTIVE_EOID
400	FID_NOT_EXIST_OR_ACTIVE	VAL_ENT_ACTIVE_FID
400	FID_NOT_RELATED_TO_EOID	VAL_ENT_REL_EOID_FID

3.5.6 IDA – (2.3) Request for deactivation of UIs

3.5.6.1 Description

Changes the status of the UIs listed in the request to “deactivated”
The hierarchy below these UIs will be managed depending on the deactivation reason for the parent UI.

3.5.6.1.1 Product deactivation

If the deactivation reason was Deact_Reason1 = 1 (Product destroyed) or 2 (Product stolen) then the full hierarchy is deactivated.

Example of a Pallet product deactivation:




Figure 6 Implicit disaggregation triggered by a IDA Deact_Reason1 = 1 or 2

3.5.6.1.2 UI deactivation

If the deactivation reason was Deact_Reason1 = 3 (UI Destroyed), 4 (UI Stolen), 5 (UI Unused) or 6 (Other), then only the explicitly mentioned UIs are deactivated and therefore the stolen parents would be still existing in the Secondary as active. It is the responsibility of the Economic Operator to report the stolen UIs as stolen when they are aware of it (send a deactivation message for the stolen UIs)

Note that in these cases the Deactivation will also trigger an implicit disaggregation.

Example of UI deactivation for a pallet




Figure 7 Implicit disaggregation triggered by a IDA Deact_Reason1 = 3,4,5 or 6

3.5.6.2 Description of the fields

request for the deactivation of UIs – request					
Field	Description	Data Type	Cardinality	Priority	Values
BasicInfo_Request	Block of basic information elements	Component << Basic Information Request >>	S	M	Message_Type = IDA
Event_Time	Intended time of event occurrence	Time(s)	S	M	
Message_Time_long	Message sending Time	Time(L)	S	M	
EO_ID	Economic operator identifier code of the submitting entity	EOID	S	M	
Deact_Type	Deactivation of unit packet or aggregated level UIs	Integer	S	M	1 – Unit pack level UIs 2 – Aggregated level UIs
Deact_Reason1	Identification of the reason for deactivation	Integer	S	M	See DeactivationReasonType
Deact_Reason2	Description of other reason	Text(5000)	S	M, if Deact_Reason1 = 6 (other reason)	
Deact_Reason3	Additional description of the reason	Text(Limited to the set of known deactivation_types)	S	O	
Deact_upUI	List of unit packet level UIs to be deactivated	upUI(s)	M	M, if Deact_Type = 1	

request for the deactivation of UIs – request					
Field	Description	Data Type	Cardinality	Priority	Values
Deact_aUI	List of aggregated level UIs to be deactivated	aUI	M	M, if Deact_Type = 2	

3.5.6.3 Response:

request for the deactivation of UIs – response					
Field	Description	Data Type	Cardinality	Priority	Values
BasicInfo_Resp	Block of basic information elements	Component << Basic Information Response >>	S	M	Message_Type = IDA

3.5.6.1 Business Validation

IDA (2.3)	
Business rule validation	
UI creation	
VAL_UI_EXIST_APP	Deact_upUI,
VAL_UI_EXIST_UPUI_SEQ	Deact_upUI,
VAL_UI_EXIST_AUI_SEQ	Deact_aUI
Entity Validation	
VAL_ENT_EXIST_EOID	EO_ID
VAL_ENT_ACTIVE_EOID	EO_ID
Sequence Validation	
VAL_UI_ORD_DEACTIVATED	Deact_upUI, Deact_aUI

3.5.6.2 Implicit disaggregation trigger

The deactivation event can trigger an implicit disaggregation when a child UI is identified as part of the event.

3.5.6.3 Request sample

```
{
  "EO_ID": "QCUKR+1AB020054",
  "Event_Time": "19032014",
  "Message_Time_Long": "2019-03-20T14:16:45Z",
  "Deact_Type": 1,
  "Deact_Reason1": 1,
  "Deact_Reason2": "reason one",
  "Deact_Reason3": "reason two",
  "Deact_upUI": [ "DANXXXXXXXXXXXX1PR0123456789" ],
  "Deact_apUI": [],
  "Message_Type": "IDA",
  "Code": "873345b2-882f-4064-91f0-90669b46c30a",
}
```

3.5.6.4 Successful response sample

HTTP Status 202

```
{
  "Code": "873345b2-882f-4064-91f0-90669b46c30a",
  "Message_Type": "IDA",
  "Error": false,
  "Errors": null,
  "Checksum": "G6HF5H"
}
```

3.5.6.5 Error response sample

Processing errors

HTTP status	Error Code	Error Description
<< Common response code >>		
400	UIS_APPLICATION_ERROR	VAL_UI_EXIST_APP
400	UI_NOT_EXIST	VAL_UI_EXIST_UPUI_SEQ
400	UI_NOT_EXIST	VAL_UI_EXIST_AUI_SEQ
400	EOID_NOT_EXIST_OR_ACTIVE	VAL_ENT_EXIST_EOID
400	EOID_NOT_EXIST_OR_ACTIVE	VAL_ENT_ACTIVE_EOID
400		VAL_UI_ORD_DEACTIVATED

3.5.7 ICM – Validate the delivery of an IRU message.

3.5.7.1 Description

This optional message allows the ID Issuer to retrieve the state of the delivery of a specific IRU message.

3.5.7.2 Description of the fields

Validate the delivery of an IRU.- request					
Field	Description	Data Type	Cardinality	Priority	Values
BasicInfo_Req	Block of basic information elements	Component << Basic Information Request >>	S	M	Message_Type = ICM
IRU_Code	IRU recallCode		S	M	

3.5.7.3 Response:

Validate the delivery of an IRU.- response					
Field	Description	Data Type	Cardinality	Priority	Values

BasicInfo_Resp	Block of basic information elements	Component << Basic Information Response >>	S	M	Message_Type = ICM
IRU_Code	IRU recallCode		S	M	
IRU_Status	The status of the delivery of a specific IRU message	Boolean	S	M	0 – False 1 – True
IRU_Status_Description	Description of the status or the error message	Text	S	O	

3.5.7.4 Request sample

```
{
  "Message_Type": "ICM"
  "IRU_Code": "873345b2-882f-4064-91f0-90669b46c30a"
}
```

3.5.7.5 Successful response sample

HTTP Status 202

```
{
  "Code": "873345b2-882f-4064-91f0-90669b46c30b",
  "Message_Type": "ICM",
  "IRU_Code": "873345b2-882f-4064-91f0-90669b46c30a"
  "IRU_Status": 0,
  "IRU_Status_Description": "optional description",
  "Error": false,
  "Errors": null,
  "Checksum": "G6HF5H"
}
```

3.5.7.6 Error response sample

Processing errors

HTTP status	Error Code	Error Description
<< Common response code >>		

3.6 Reporting operational events (product movement information)

3.6.1 EUA – (3.1) Application of unit level UIs on unit packets

3.6.1.1 Description

Event notification when the code is applied / printed on unit packets.

3.6.1.2 Description of the fields

upUI application event					
Field	Description	Data Type	Cardinality	Priority	Values
BasicInfo_Request	Block of basic information elements	Component << Basic Information Request >>	S	M	Message_Type = EUA
Event_Time	Intended time of event occurrence	Time(s)	S	M	
Message_Time_long	Message sending Time	Time(L)	S	M	
EO_ID	Economic operator identifier code of the submitting entity	EOID	S	M	
F_ID	Facility identifier code	FID	S	M	
upUI_1	List of unit packet level UIs to be recorded (full length)	upUI(L)	M	M	
upUI_2	List of corresponding unit packet level UIs to be recorded (as visible in human readable format) indicated in the same order as upUI_1	upUI(s)	M	M	
upUI_comment	Comments by the reporting entity	Text(5000)	S	O	

3.6.1.3 Business validation

	EUA (3.1)
Technical validation	
VAL_UI_MULT_MSG	upUI_1, upUI_2
Business rule validation	
UI creation	
VAL_UI_EXIST_APP	upUI_1
VAL_UI_DUPLICATE_APP	upUI_1
VAL_UI_EXPIRY	upUI_1
Entity Validation	
VAL_ENT_EXIST_EOID	EO_ID
VAL_ENT_EXIST_FID	F_ID
VAL_ENT_ACTIVE_EOID	EO_ID
VAL_ENT_ACTIVE_FID	F_ID
Sequence Validation	
VAL_UI_FID_APP	F_ID with information for upUI_1
VAL_UI_ORD_REACTIVATION	upUI_1
Message Timing	
VAL_EVT_24H	Event_Time

3.6.1.4 Sequence validation

The following table represents the authorized transitions for a UI and specifically the previous message for the UI.

	IRU 2.1
Message Received	
EUA 3.1	Yes
EUA 3.1 Import	Yes

No	Next message not allowed for the UI (including different aggregation)
Yes	Next Message allowed
Yes (with Location Validation)	Next Message allowed with location validation

The EUA (3.1) application event must be preceded by an IRU event that reports the issued UIs.

3.6.1.5 Response:

upUI application event – response					
Field	Description	Data Type	Cardinality	Priority	Values
BasicInfo_Resp	Block of basic information elements	Component << Basic Information Response >>	S	M	Message_Type = EUA

3.6.1.6 Request sample

```
{
  "EO_ID": "QCUKR+1AB020054",
  "F_ID": "QCUKR<1AB020054000049",
  "Event_Time": "19032014",
  "Message_Time_Long": "2019-03-20T14:16:45Z",
  "upUI_1": [
    "DANXXXXXXXXXXXX1PR012345678919030110",
    "DANXXXXXXXXXXXX2PR012345678919030110"
  ],
  "upUI_2": [
    "DANXXXXXXXXXXXX1PR012345678919030110",
    "DANXXXXXXXXXXXX2PR012345678919030110"
  ],
  "upUI_comment": "Comments",
  "Message_Type": "EUA",
  "Code": "873345b2-882f-4064-91f0-90669b46c30a",
}
```

3.6.1.7 Successful response sample

HTTP Status 202

```
{
  "Code": "873345b2-882f-4064-91f0-90669b46c30a",
  "Message_Type": "EUA",
  "Error": false,
  "Errors": null,
  "Checksum": "G6HF5H"
}
```

3.6.1.8 Error response sample

HTTP status	Error Code	Error Description
<< Common response code >>		
400	MULTIPLE_UID	VAL_UI_MULT_MSG
400	UIS_APPLICATION_ERROR	VAL_UI_EXIST_APP
400	UIS_APPLICATION_ERROR	VAL_UI_DUPLICATE_APP
400	UI_NOT_EXIST	VAL_UI_EXPIRY
400	EOID_NOT_EXIST_OR_ACTIVE	VAL_ENT_EXIST_EOID
400	VAL_ENT_EXIST_FID	VAL_ENT_EXIST_FID
400	EOID_NOT_EXIST_OR_ACTIVE	VAL_ENT_ACTIVE_EOID
400	VAL_ENT_EXIST_FID	VAL_ENT_ACTIVE_FID
400	FID_MISMATCH	VAL_UI_FID_APP
400	UI_DEACTIVATED	VAL_UI_ORD_REACTIVATION
299	OPERATION_WITHIN_24_HOURS	VAL_EVT_24H

3.6.2 EPA – (3.2) Application of aggregated level UIs on aggregated packaging

3.6.2.1 Description

Event notification when the code is applied / printed on an aggregation container. This also records the items that are aggregated into this container.

3.6.2.2 Description of the fields

Application of aggregated level UIs on aggregated packaging - request					
Field	Description	Data Type	Cardinality	Priority	Values
BasicInfo_Request	Block of basic information elements	Component << Basic Information Request >>	S	M	Message_Type = EPA
EO_ID	Economic operator identifier code of the submitting entity	EOID	S	M	
F_ID	Facility identifier code	FID	S	M	
Event_Time	Time of event occurrence	Time(s)	S	M	
Message_Time_long	Message sending Time	Time(L)	S	M	
aUI	Aggregated level UI	aUI	S	M	
Aggregation_Type	Identification of aggregation type	Integer	S	M	1 – aggregation of only unit packet level UIs

Application of aggregated level UIs on aggregated packaging - request					
Field	Description	Data Type	Cardinality	Priority	Values
					2 – aggregation of only aggregated level UIs 3 – aggregation of both unit packet and aggregated level UIs
Aggregated_UIs1	List of unit packet level UIs subject to aggregation	upUI(L)	M	M, if Aggregation_Type = 1 or 3	
Aggregated_UIs2	List of aggregated level UIs subject to further aggregation	aUI	M	M, if Aggregation_Type = 2 or 3	
aUI_comment	Comments by the reporting entity	Text(5000)	S	O	
Information	Indicates the request of additional optional information	Boolean	S	O	0 – No 1- Yes

3.6.2.3 Business validation

	EPA (3.2)
Technical validation	
VAL_UI_MULT_MSG	aUI, Aggregated_UIs1
VAL_FIE_REF	aUI, Aggregated_UIs1. Error Descr for Circular Reference issue: The message contains UI values that form a circular reference
Business rule validation	
UI creation	
VAL_UI_EXIST_UPUI	Aggregated_UIs1
VAL_UI_EXIST_AUI	aUI, Aggregated_UIs2
VAL_UI_EXIST_UPUI_SEQ	Aggregated_UIs1
VAL_UI_EXIST_AUI_SEQ	Aggregated_UIs2
VAL_UI_EXPIRY	aUI, Aggregated_UIs1
Entity Validation	
VAL_ENT_EXIST_EOID	EO_ID
VAL_ENT_EXIST_FID	F_ID
VAL_ENT_ACTIVE_EOID	EO_ID
Sequence Validation	
VAL_UI_ORD_DEACTIVATED	aUI, Aggregated_UIs2
VAL_UI_ORD_AGG_MULT	aUI, Aggregated_UIs2
VAL_UI_ORD_IMPLDISAGG	aUI, Aggregated_UIs2
VAL_UI_ORD_AGG_FID	F_ID for Aggregated_UIs1 and Aggregated_UIs2
Message Timing	
VAL_EVT_24H	Event_Time

3.6.2.4 Sequence Validation

The following table represents the authorized transitions for a UI and specifically the previous message for the UI.

	IRA 2.2	EUA 3.1	EUA 3.1 Import	EPA 3.2 parent UI	EPA 3.2 parent UI Import	EPA 3.2 Child	ERP 3.4	ERP 3.4 (Return)	EUD 3.6
Message Received									
EPA 3.2 parent UI	Yes	No	No	No	No	No	No	No	Yes
EPA 3.2 child UI (upUI)	No	Yes	Yes	No	No	Yes	Yes	Yes	No
EPA 3.2 child UI (aUI)	No	No	No	Yes	Yes	Yes	Yes	Yes	No

No	Next message not allowed for the UI (including different aggregation)
Yes	Next Message allowed
Yes (with Location Validation)	Next Message allowed with location validation

A parent aUI can be

- Self generated parent UI. This event will correspond to the initial commissioning of the aUI.
- ID Issuer generated aUI reported using an IRA (2.2) event.
- As a aUI that is re-used. This aUI must be preceded by a EUD (3.6) (explicit) disaggregation event. Note that in the case of a reuse, the location validation is not performed. In other words, the aUI can be re aggregated in any location.

A Child UI can be reported if it is present in the location of the aggregation.

- A upUI can be applied, following a EUA (3.1) event.
- A upUI can be present in the location following a disaggregation event of a previous aggregation.
- An aUI can be present in the location following a disaggregation event of a previous aggregation where it was reported as child UI.
- A upUI or aUI that are still part of an valid aggregation as child UIs. The reporting of the aggregation event will trigger an implicit disaggregation of the initial aggregation.
- A upUI or aUI that are arrived ERP (3.4) event.

Location validation on the child UI Is performed for the aggregation as these UI should be in the location of the aggregation.

3.6.2.5 Implicit disaggregation trigger

This event can trigger an implicit disaggregation when a child UI is identified as part of the event.

Example: Implicit Disaggregation occurring when re-Aggregating




Figure 8 Implicit disaggregation triggered by an EPA (3.2) event

The second aggregation event (EPA 3.2) result in the creation of the new pallet with the same content as pallet 1 that is implicitly disaggregated.

3.6.2.6 Response:

Application of aggregated level UIs on aggregated packaging – response					
Field	Description	Data Type	Cardinality	Priority	Values
BasicInfo_Resp	Block of basic information elements	Component << Basic Information Response >>	S	M	Message_Type = EPA
Basic Information Block	Additional optional acknowledgment Information	Component << Basic Information Block >>	S	O	

3.6.2.7 Request sample

```
{
  "EO_ID": "QCUKR+1AB020054",
  "F_ID": "QCUKR<1AB020054000049",
  "Event_Time": "19032014",
  "Message_Time_Long": "2019-03-20T14:16:45Z",
  "Aggregation_Type": "1",
  "aUI": "DANXXXXXXXXXXXXX1FA00000119030110",
}
```

```

    "Aggregated_UIs1": ["DANXXXXXXXXXXXX1PR012345678919030110",
    "DANXXXXXXXXXXXX2PR012345678919030110",
    "DANXXXXXXXXXXXX3PR012345678919030110",
    "DANXXXXXXXXXXXX10FA00000119030110"],
    "Aggregated_UIs2": ["DANXXXXXXXXXXXX10FA00000119030110"],
    "aUI_comment": "Comments",
    "Message_Type": "EPA",
    "Code": "873345b2-882f-4064-91f0-90669b46c30a"
  }

```

3.6.2.8 Successful response sample

HTTP Status 202

```

{
  "Code": "873345b2-882f-4064-91f0-90669b46c30a",
  "Message_Type": "EPA",
  "Error": false,
  "Errors": null,
  "Checksum": "G6HF5H"
}

```

3.6.2.9 Error response sample

HTTP status	Error Code	Error Description
<< Common response code >>		
400	UIS_APPLICATION_ERROR	VAL_UI_EXIST_UPUI
400	UI_NOT_EXIST	VAL_UI_EXIST_AUI
400	UI_NOT_VALID	VAL_UI_EXIST_UPUI_SEQ
400	UI_NOT_EXIST	VAL_UI_EXIST_AUI_SEQ
400	UI_EXPIRED	VAL_UI_EXPIRY
400	EOID_NOT_EXIST_OR_ACTIVE	VAL_ENT_EXIST_EOID
400	FID_NOT_EXIST_OR_ACTIVE	VAL_ENT_EXIST_FID
400	EOID_NOT_EXIST_OR_ACTIVE	VAL_ENT_ACTIVE_EOID
400	FID_NOT_EXIST_OR_ACTIVE	VAL_UI_ORD_DEACTIVATED
400	MULTIPLE_AGGREGATION	VAL_UI_ORD_AGG_MULT
400	UI_ALREADY_DISAGGREGATED	VAL_UI_ORD_IMPLDISAGG
400	LOCATION_MISMATCH	VAL_UI_ORD_AGG_FID
299	OPERATION_WITHIN_24_HOURS	VAL_EVT_24H
400	FAILED_VALIDATION	VAL_FIE_REF

3.6.3 EDP – (3.3) Dispatch of tobacco products from a facility

3.6.3.1 Description

Record that the UIs listed in the call have been dispatched from the economic identifier.

3.6.3.2 Description of the fields

Dispatch of tobacco products from a facility event					
Field	Description	Data Type	Cardinality	Priority	Values
BasicInfo_Req	Block of basic information elements	Component << Basic Information Request >>	S	M	Message_Type = EDP
EO_ID	Economic operator identifier code of the submitting entity	EOID	S	M	
Event_Time	Time of event occurrence	Time (s)	S	M	
Message_Time_long	Message sending Time	Time (L)	S	M	
F_ID	Dispatch facility identifier code	FID	S	M	
Destination_ID1	Indication if the destination facility is located on the EU territory and if it is a vending machine (VM)	Integer	S	M	1 – Non EU dest. 2 – EU destination other than VM – fixed quantity delivery 3 – EU VM(s) 4 – EU destination other than VM – delivery with VV
Destination_ID2	Destination facility identifier code	FID	S	M, if Destination_ID1 = 2	
Destination_ID3	Destination facility identifier code(s) – possible multiple vending machines	FID	M	M, if Destination_ID1 = 3	
Destination_ID4	Destination id facility codes	FID	M	M, if Destination_ID1 = 4	
Destination_ID5	Destination facility's full address	Text(5000)	S	M, if Destination_ID1 = 1	
Destination_ID5_Address_Name	Destination facility's full address - Name part of the Address	Text(5000)	S	O	
Destination_ID5_Address_StreetOne	Destination facility's full address - Street part of the Address	Text(5000)	S	M, if Destination_ID1 = 1	
Destination_ID5_Address_StreetTwo	Destination facility's full address - Second Element of the Street part of the Address	Text(5000)	S	O	
Destination_ID5_Address_City	Destination facility's full address - City	Text(5000)	S	M, if Destination_ID1 = 1	
Destination_ID5_Address_PostCode	Destination facility's full address - PostalCode information	Text(5000)	S	O	

Dispatch of tobacco products from a facility event					
Field	Description	Data Type	Cardinality	Priority	Values
Transport_mode	Mode of transport by which the product leaves the facility, see: Commission Regulation (EC) No 684/2009, Annex II, Code List 7	Integer	S	M	See TransportMode in section Error! Reference source not found.
Transport_vehicle	Identification of the mode of transport (i.e. number plates, train number, plane/flight number, ship name or other identification)	Text(5000)	S	M	'n/a' is permitted value if Transport_mode = 0 and product movement takes place between adjacent facilities and is delivered manually
Transport_cont1	Indication if the transport is containerised and uses an individual transport unit code (e.g. SSCC)	Boolean	S	M	0 – No 1 – Yes
Transport_cont2	Individual transport unit code of the container	ITU	S	M, if Transport_cont1 = 1	
Transport_s1	Indication if the dispatch takes place with the logistic/postal operator who operates its own track and trace system accepted by the Member State of the dispatch facility. Only for small quantities of tobacco products (net weight of the products dispatched below 10 kg) destined for exports to third countries	Boolean	S	M	0 – No 1 – Yes
Transport_s2	The logistic operator's tracking number	Text(5000)	S	M, if Transport_s1 = 1	
EMCS	Dispatch under the Excise Movement and Control System (EMCS)	Boolean	S	M	0 – No 1 – Yes
EMCS_ARC	Administrative Reference Code (ARC)	ARC	S	M, if EMCS = 1	
SAAD	Dispatch with a simplified accompanying document, see: Commission Regulation (EEC) No 3649/92	Boolean	S	M	0 – No 1 – Yes
SAAD_number	Reference number of the declaration and/or authorization which has to be given by the competent authority in the Member State of destination before the movement starts	T Text(5000)	S	M, if SAAD = 1	
Exp_Declaration	Indication if the Movement Reference	Boolean	S	M	0 – No 1 – Yes

Dispatch of tobacco products from a facility event					
Field	Description	Data Type	Cardinality	Priority	Values
	Number (MRN) has been issued by the customs office				
Exp_DeclarationNumber	Movement Reference Number (MRN)	MRN	S	M, if Exp_Declaration = 1	
UI_Type	Identification of UI types in the dispatch (recorded at the highest level of available aggregation)	Integer	S	M	1 – only unit packet level UIs 2 – only aggregated level UIs 3 – both unit packet and aggregated level UIs
upUIs	List of unit packet level UIs subject to the dispatch	upUI(L)	M	M, if UI_Type = 1 or 3	
aUIs	List of aggregated level UIs subject to the dispatch	aUI	M	M, if UI_Type = 2 or 3	
Dispatch_comment	Comments by the reporting entity	Text(5000)	S	O	
Information	Indicates the request of additional optional information	Boolean	S	O	0 – No 1- Yes

3.6.3.3 Business validation

	EDP (3.3)
Technical validation	
VAL_MSG_JSON	EXCISE_NUMBER_NOT_VALID
VAL_UI_MULT_MSG	upUIs, aUIs
Business rule validation	
UI creation	
VAL_UI_EXIST_UPUI	upUIs
VAL_UI_EXIST_AUI	aUIs
VAL_UI_EXIST_UPUI_SEQ	upUIs
VAL_UI_EXIST_AUI_SEQ	aUIs
Entity Validation	
VAL_ENT_EXIST_EOID	EO_ID
VAL_ENT_EXIST_FID	F_ID, Destination_ID2, Destination_ID3, Destination_ID4
VAL_ENT_ACTIVE_EOID	EO_ID
VAL_ENT_ACTIVE_FID (Router only)	F_ID, Destination_ID2, Destination_ID3, Destination_ID4
Sequence Validation	
VAL_UI_ORD_DEACTIVATED	upUIs, aUIs
VAL_UI_ORD_DISAGG	aUIs
VAL_UI_ORD_IMPLDISAGG	aUIs
VAL_UI_ORD_DISPATCH	upUIs, aUIs
Message Timing	
VAL_EVT_TIME	Event_Time

3.6.3.4 Sequence validation

The following table represents the authorized transitions for a UI and specifically the previous message for the UI.

The type of the Dispatch event 3.3 EDP refers to the Destination_ID1 field.

- Type 1 – Non EU dest.
- Type 2 – EU destination other than VM – fixed quantity delivery
- Type 3 – EU VM(s)
- Type 4 – EU destination other than VM – delivery with VV


Message Received	EUA 3.1		EPA 3.2 parent UI			ERP 3.4	
	EUA 3.1	EUA 3.1 Import	EPA 3.2 parent UI	EPA 3.2 parent UI Import	EPA 3.2 Child	ERP 3.4	ERP 3.4 (Return)
EDP 3.3 Export (type 1)	Yes	No	Yes	No	Yes	Yes	Yes
EDP 3.3 (type 2)	Yes	No	Yes	No	Yes	Yes	Yes
EDP 3.3 VM (type 3)	Yes	No	Yes	No	Yes	Yes	Yes
EDP 3.3 VV (type 4)	Yes	No	Yes	No	Yes	Yes	Yes

No	Next message not allowed for the UI (including different aggregation)
Yes	Next Message allowed
Yes (with Location Validation)	Next Message allowed with location validation


Products can be dispatched from a location only if they have been applied (EUA 3.1) or aggregated (EPA 3.2) in that specific location or if they have been previously reported as arrived in that location. This means that Dispatch events should follow an Arrival, an Aggregation or an Application message, and the origin of the Dispatch must correspond to the location of previous Arrival, Aggregation or Application event.

3.6.3.4.1 Expected sequences

- ERP – 3.4 message > EDP – 3.3 message



- EPA – 3.2 message > EDP – 3.3 message




3.6.3.4.2 Example of sequence errors for EDP (3.3):

- **UI_SEQUENCE_ERROR:**

The error is generated when UIs scanned at Dispatch are not part of a prior Delivery/Arrival, Aggregation or Application message.

The UIs are considered as “in transit” and cannot be dispatched again. The prior Delivery/Arrival of the UIs in the location might have not be reported or the UIs might have already been dispatched from the location.

Example of EDP (3.3) with prior ERP (3.4) not reported:




- **LOCATION_MISMATCH**

The error is generated when the facility of origin of the Dispatch does not match the current location of the UIs reported in the Dispatch message.

There might have been a misreporting in the previous Delivery/Arrival messages leading to a wrong location of the UIs or the current Dispatch does not report the correct facility of origin.

Example of EDP (3.3) with wrong FID:




3.6.3.4.3 Import scenario

The imported goods that have been applied and aggregated require to be part of an Arrival (ERP 3.4) event.

3.6.3.5 Implicit disaggregation trigger

This event can trigger an implicit disaggregation when a child UI is identified as part of the event.

Example of an Implicit Disaggregation occurring when Dispatching



3.6.3.6 *Response:*

Response:

Dispatch event – response					
Field	Description	Data Type	Cardinality	Priority	Values
BasicInfo_Resp	Block of basic information elements	Component << Basic Information Response >>	S	M	Message_Type = EDP
Basic Information Block	Additional optional acknowledgment Information	Component << Basic Information Block >>	S	O	

3.6.3.7 *Request sample*

```
{
  "EO_ID": "QCUKR+1AB020054",
  "F_ID": "QCUKR<1AB020054000049",
  "Event_Time": "19032014",
  "Message_Time_Long": "2019-03-20T14:16:45Z",
  "Destination_ID1": "1",
  "Destination_ID2": "FacilityIdB",
  "Destination_ID3": [ " FacilityIdB ", " FacilityIdB " ],
  "Destination_ID4": [ " FacilityIdB " ],
  "Destination_ID5": "FacilityIdA",
  "Transport_vehicle": "1",
  "Transport_cont1": 1,
  "Transport_cont2": "1",
  "Transport_s1": 1,
  "Transport_s2": "1",
  "EMCS": false,
  "EMCS_ARC": null,
  "SAAD": 1,
  "SAAD_number": 1,
  "Exp_Declaration": 1,
  "Exp_DeclarationNumber": 1,
  "UI_Type": 3,
  "upUIs": [ "DANXXXXXXXXXXXXX1PR012345678919030110",
"DANXXXXXXXXXXXXX2PR012345678919030110" ],
  "aUIs": [ "DANXXXXXXXXXXXXX1FA00000119030110" ],
  "Dispatch_comment": "Comments",
  "Message_Type": "EDP",
  "Code": "873345b2-882f-4064-91f0-90669b46c30a"
}
```

3.6.3.8 *Successful response sample*

HTTP Status 202

```
{
  "Code": "873345b2-882f-4064-91f0-90669b46c30a",
  "Message_Type": "EDP",
  "Error": false,
  "Errors": null,
}
```

```
"Checksum": "G6HF5H"
}
```

3.6.3.9 Error response sample

Processing errors

HTTP status		
<< Common response code >>		
400	EXCISE_NUMBER_NOT_VALID	VAL_FIE_FORMAT
400	MULTIPLE_UID	VAL_UI_MULT_MSG
400	UI_NOT_EXIST UI_NOT_VALID	VAL_UI_EXIST_UPUI
400	UI_NOT_EXIST	VAL_UI_EXIST_AUI
400	UI_NOT_VALID	VAL_UI_EXIST_UPUI_SEQ
400	UI_NOT_EXIST	VAL_UI_EXIST_AUI_SEQ
400	Eoid_NOT_EXIST_OR_ACTIVE	VAL_ENT_EXIST_Eoid
400	FID_NOT_EXIST_OR_ACTIVE	VAL_ENT_EXIST_FID
400	Eoid_NOT_EXIST_OR_ACTIVE	VAL_ENT_ACTIVE_Eoid
400	FID_NOT_EXIST_OR_ACTIVE	VAL_ENT_ACTIVE_FID (Router only)
400	UI_DEACTIVATED	VAL_UI_ORD_DEACTIVATED
400	UI_ALREADY_DISAGGREGATED	VAL_UI_ORD_DISAGG or VAL_UI_ORD_IMPLDISAGG
400	LOCATION_MISMATCH	VAL_UI_ORD_DISPATCH
299	SHIPMENT_WITHIN_24_HOURS	VAL_EVT_TIME
400	UI_SEQUENCE_ERROR	VAL_UI_ORD_SEQUENCE

3.6.4 ERP – (3.4) Arrival of tobacco products at a facility

3.6.4.1 Description

Record that the UIs listed in the call have been received to an economic identifier.

3.6.4.2 Description of the fields

Arrival of tobacco products at a facility					
Field	Description	Data Type	Cardinality	Priority	Values
BasicInfo_Req	Block of basic information elements	Component << Basic Information Request >>	S	M	Message_Type = ERP
EO_ID	Economic operator identifier code of the submitting entity	EOID	S	M	
F_ID	Arrival facility identifier code	FID	S	M	
Event_Time	Time of event occurrence	Times(s)	S	M	
Message_Time_Long	Message sending Time	Times(L)	S	M	
Product_Return	Indication if the arriving products are a return following complete or partial non-delivery	Boolean	S	M	0 – No 1 – Yes
UI_Type	Identification of UI types received (recorded at the highest level of available aggregation)	Integer	S	M	1 – only unit packet level UIs 2 – only aggregated level UIs 3 – both unit packet and aggregated level UIs
upUIs	List of unit packet level UIs received	upUI(L)	M	M, if UI_Type = 1 or 3	
aUIs	List of aggregated level UIs received	aUI	M	M, if UI_Type = 2 or 3	
Arrival_comment	Comments by the reporting entity	Text	S	O	
Information	Indicates the request of additional optional information	Boolean	S	O	0 – No 1- Yes

3.6.4.3 Business Validation

	ERP (3.4)
Technical validation	
VAL_UI_MULT_MSG	upUIs , aUIs
Business rule validation	
UI creation	
VAL_UI_EXIST_UPUI	upUIs
VAL_UI_EXIST_AUI	aUIs
VAL_UI_EXIST_UPUI_SEQ	upUIs
VAL_UI_EXIST_AUI_SEQ	aUIs
Entity Validation	
VAL_ENT_EXIST_EOID	EO_ID

VAL_ENT_EXIST_FID	F_ID
VAL_ENT_ACTIVE_EOID	EO_ID
Sequence Validation	
VAL_UI_ORD_DEACTIVATED	upUIs, aUIs
VAL_UI_ORD_DISAGG	aUIs
VAL_UI_ORD_IMPLDISAGG	aUIs
VAL_UI_ORD_ARRIVAL	upUIs, aUIs
VAL_UI_ORD_ARRIVAL_RETURN	upUIs, aUIs

3.6.4.4 Sequence validation

The following table represents the authorized transitions for a UI and specifically the previous message for the UI.

	EUA 3.1 Import	EPA 3.2 parent UI Import	EDP 3.3 (type 1) Export	EDP 3.3 (type 2)	EDP 3.3 (types 3) VM	EDP 3.3 (type 4) VV	ETL 3.5 Export	ETL 3.5 Export	EVR 3.7
Message Received									
ERP 3.4	Yes	Yes	No	Yes	No	No	Yes	No	No
ERP 3.4 (Return)	No	No	Yes	Yes	Yes	Yes	Yes	Yes	Yes

No	Next message not allowed for the UI (including different aggregation)
Yes	Next Message allowed
Yes (with Location Validation)	Next Message allowed with location validation

The type return of the ERP (3.4) is based on the Product_Return field

- 0 – No
- 1– The arrival is a type return


Events must be transmitted in sequence: Arrivals are expected to be reported in proper events sequence, following a dispatch, a transloading, or as a (partial) return from Vending Van delivery or from retail outlets.

3.6.4.4.1 Import scenario

In the case of Imported good, the newly applied (EUA 3.1) or aggregated (EPA 3.2) UIs must be part of an arrival event.


3.6.4.4.2 Arrival after Dispatch

- EDP – 3.3 (type 2) message > ERP – 3.4 message




3.6.4.4.3 Arrival after Transloading

- ETL – 3.5 message > ERP – 3.4 message



3.6.4.4.4 Arrival after dispatch carried out by vending van

- EVR – 3.7 messages > ERP of type return – 3.4 message



Events must be reported within respecting Principle 4: All disaggregation must be performed at a location. No Disaggregation are allowed during the transport.

Events must be reported within respecting Principle 5: The reporting on the Arrival should be done on the same UI that have been reported during the Dispatch/Transloading process. This is a consequence of Principle 4. This means that an Arrival Event that contains child UI of UI reported during the Dispatch/Transloading Event will be rejected. The same UI must be reported.

Exception to principle 5: Arrival of type return can be reported at a different level than the previous dispatch/transloading/delivery with VV

3.6.4.4.5 Arrival of type return

The Arrival of type return is the proper reporting event for exported goods, goods in transit (dispatched or in transloading)

3.6.4.4.6 Examples of sequence errors for ERP (3.4)

ARRIVAL_NOTALLOWED

The error is generated because UIs in the Arrival message were not part of a previous EDP (3.3) or ETL (3.5) message. The previous Economic Operator should be contacted to verify its message of Dispatch/Transloading.

Note: in case of product return, the ERP (3.4) can be reported after an EVR (3.7), this will not trigger ARRIVAL_NOTALLOWED.

Example of ERP (3.4) rejected because the previous EDP (3.3) has not been reported:




Figure 9 Arrival sequence error ARRIVAL_NOTALLOWED

UI_SEQUENCE_ERROR

The error is generated when UIs scanned at Arrival are not the same that the ones scanned in the prior Dispatch/Transloading event.

According to principle 5, the UIs must be scanned at Arrival at the highest level of aggregation, before being implicitly or explicitly disaggregated.

If the error is generated when Arrival is reported at the highest available aggregation level, the previous Economic Operator should be contacted to verify at which level it reported Dispatch/Transloading.

Exception: Arrivals of type return will not generate this error because implicit disaggregation is allowed for them

Example of ERP (3.4) rejected because it is not reported at the right level of aggregation:




Figure 10 Arrival sequence error UI_SEQUENCE_ERROR

3.6.4.5 Implicit disaggregation trigger

The Arrival of type Return (Product_Return = "true") ERP (3.4) can trigger an implicit disaggregation when a child UI is identified as part of the event.

Note that an arrival message that contains a child UI will cause a sequence validation error UI_SEQUENCE_ERROR if the Product_Return flag is set to false.

3.6.4.6 Response:

Arrival of tobacco products at a facility- response					
Field	Description	Data Type	Cardinality	Priority	Values
BasicInfo_Resp	Block of basic information elements	Component << Basic Information Response >>	S	M	Message_Type = ERP
Basic Information Block	Additional optional acknowledgment Information	Component << Basic Information Block >>	S	O	

3.6.4.7 Request sample

```
{
  "EO_ID": "QCUKR+1AB020054",
  "F_ID": "QCUKR<1AB020054000049",
  "Event_Time": "19032014",
  "Message_Time_Long": "2019-03-20T14:16:45Z",
  "Product_Return": "true",
  "UI_Type": "1",
  "upUIs": [ "DANXXXXXXXXXXXX1PR012345678919030110", "
DANXXXXXXXXXXXX2PR012345678919030110" ],
  "aUIs": [ "DANXXXXXXXXXXXX1PR012345678919030110" ],
  "Arrival_comment": "Comments",
  "Message_Type": "ERP",
  "Code": "873345b2-882f-4064-91f0-90669b46c30a"
```

}

3.6.4.8 Successful response sample

HTTP Status 202

```
{
  "Code": "873345b2-882f-4064-91f0-90669b46c30a",
  "Message_Type": "ERP",
  "Error": false,
  "Errors": null,
  "Checksum": "G6HF5H"
}
```

3.6.4.9 Error response sample

HTTP status	Error Code	Error Description
<< Common response code >>		
400	MULTIPLE_UID	VAL_UI_MULT_MSG
400	UI_NOT_EXIST	VAL_UI_EXIST_UPUI
400	UI_NOT_VALID	
400	UI_NOT_EXIST	VAL_UI_EXIST_AUI
400	UI_NOT_VALID	VAL_UI_EXIST_UPUI_SEQ
400	UI_NOT_EXIST	VAL_UI_EXIST_AUI_SEQ
400	EOID_NOT_EXIST_OR_ACTIVE	VAL_ENT_EXIST_EOID
400	FID_NOT_EXIST_OR_ACTIVE	VAL_ENT_EXIST_FID
400	EOID_NOT_EXIST_OR_ACTIVE	VAL_ENT_ACTIVE_EOID
400	UI_DEACTIVATED	VAL_UI_ORD_DEACTIVATED
400	UI_ALREADY_DISAGGREGATED	VAL_UI_ORD_DISAGG or VAL_UI_ORD_IMPLDISAGG
400	ARRIVAL_NOTALLOWED	VAL_UI_ORD_ARRIVAL or VAL_UI_ORD_ARRIVAL_RETURN
400	UI_SEQUENCE_ERROR	VAL_UI_ORD_SEQUENCE

3.6.5 ETL – (3.5) Trans-loading

3.6.5.1 Description

Event to show that UIs have been moved from one transport mechanism to another.

3.6.5.2 Description of the fields

Trans-loading event					
Field	Description	Data Type	Cardinality	Priority	Values
BasicInfo_Req	Block of basic information elements	Component << Basic Information Request >>	S	M	Message_Type = ETL

Trans-loading event					
Field	Description	Data Type	Cardinality	Priority	Values
EO_ID	Economic operator identifier code of the submitting entity	EOID	S	M	
Event_Time	Intended time of event occurrence	Time(s)	S	M	
Message_Time_long	Message sending Time	Time(L)	S	M	
Destination_ID1	Indication if the destination facility is located on the EU territory	Integer	S	M	0 – No 1 – Yes
Destination_ID2	Destination facility identifier code	FID	S	M, if Destination_ID1 = 1	
Destination_ID3	Destination facility's full address	Text(5000)	S	M, if Destination_ID1 = 0	
Destination_ID3_Address_Name	Destination facility's full address - Name part of the Address	Text(5000)	S	O	
Destination_ID3_Address_StreetOne	Destination facility's full address - Street part of the Address	Text(5000)	S	M, if Destination_ID1 = 0	
Destination_ID3_Address_StreetTwo	Destination facility's full address - Second Element of the Street part of the Address	Text(5000)	S	O	
Destination_ID3_Address_City	Destination facility's full address - City	Text(5000)	S	M, if Destination_ID1 = 0	
Destination_ID3_Address_PostalCode	Destination facility's full address - PostalCode information	Text(5000)	S	O	
Transport_mode	Mode of transport to which the product is trans-loaded, see: Commission Regulation (EC) No 684/2009, Annex II, Code List 7	Integer	S	M	See TransportMode
Transport_vehicle	Identification of the vehicle (i.e. number plates, train number, plane/flight number, ship name or other identification)	Text(5000)	S	M	
Transport_cont1	Indication if the transport is containerised and uses an individual transport unit code (e.g. SSCC)	Boolean	S	M	0 – No 1 – Yes
Transport_cont2	Individual transport unit code of the container	ITU	S	M, if Transport_cont1 = 1	
EMCS	Dispatch under the Excise Movement and Control System (EMCS)	Boolean	S	M	0 – No 1 – Yes
EMCS_ARC	Administrative Reference Code (ARC)	ARC	S	M, if EMCS = 1	
UI_Type	Identification of UI types subject to the trans-loading (recorded at the highest level of available aggregation)	Integer	S	M	1 – only unit packet level UIs 2 – only aggregated level UIs

Trans-loading event					
Field	Description	Data Type	Cardinality	Priority	Values
					3 – both unit packet and aggregated level UIs
upUIs	List of unit packet level UIs subject to the trans-loading	upUI(L)	M	M, if UI_Type = 1 or 3	
aUIs	List of aggregated level UIs subject to the trans-loading	aUI	M	M, if UI_Type = 2 or 3	
Transloading_comment	Comments by the reporting entity	Text(5000)	S	O	
Information	Indicates the request of additional optional information	Boolean	S	O	0 – No 1- Yes

3.6.5.3 Business validation

	ETL (3.5)
Technical validation	
VAL_UI_MULT_MSG	upUIs, aUIs
Business rule validation	
UI creation	
VAL_UI_EXIST_UPUI	upUIs
VAL_UI_EXIST_AUI	aUIs
VAL_UI_EXIST_UPUI_SEQ	upUIs
VAL_UI_EXIST_AUI_SEQ	aUIs
Entity Validation	
VAL_ENT_EXIST_EOID	EO_ID
VAL_ENT_EXIST_FID	Destination_ID2
VAL_ENT_ACTIVE_EOID	EO_ID
Sequence Validation	
VAL_UI_ORD_DEACTIVATED	upUIs, aUIs
VAL_UI_ORD_DISAGG	aUIs
VAL_UI_ORD_IMPLDISAGG	aUIs
Message Timing	
VAL_EVT_TIME	Event_Time

3.6.5.4 Sequence validation

The field Destination_ID1 in the ETL event indicates if the ETL is aimed at export or EU location.

- 0 – No
- 1 – Yes

EDP				
3.3	EDP	EDP	EDP	
(type	3.3	3.3	3.3	
1)	(type	(types	(type	
Export	2)	3) VM	4) VV	ETL 3.5 ETL 3.5 Export

Message Received						
ETL 3.5	No	Yes	No	No	Yes	No
ETL 3.5 (Export)	Yes	No	No	No	No	Yes

No	Next message not allowed for the UI (including different aggregation)
Yes	Next Message allowed
Yes (with Location Validation)	Next Message allowed with location validation

ETL (3.5) can only be preceded by EDP (3.3) of type 1 or 2 or another ETL (3.5)
The ETL (3.5) event is not subject to any location validation

3.6.5.5 Response:

Trans-loading event – response					
Field	Description	Data Type	Cardinality	Priority	Values
BasicInfo_Resp	Block of basic information elements	Component << Basic Information Response >>	S	M	Message_Type = ETL
Basic Information Block	Additional optional acknowledgment information	Component << Basic Information Block >>	S	O	

3.6.5.6 Request sample

```
{
  "EO_ID": "QCUKR+1AB020054",
  "Event_Time": "19032014",
  "Message_Time_Long": "2019-03-20T14:16:45Z",
  "Destination_ID1": 1,
  "Destination_ID2": "FGHZ7G",
  "Destination_ID3": "",
  "Transport_mode": 1,
  "Transport_vehicle": 1,
  "Transport_cont1": 1,
  "Transport_cont2": "code",
  "EMCS": 1,
  "EMCS_ARC": "ref",
  "UI_Type": 1,
  "upUIs": [ "DANXXXXXXXXXXXX1PR012345678919030110", "
DANXXXXXXXXXXXX2PR012345678919030110" ],
  "aUIs": [ "DANXXXXXXXXXXXX10FA00000119030110" ],
  "Transloading_comment": "Comments",
  "Message_Type": "ETL",
  "Code": "873345b2-882f-4064-91f0-90669b46c30a"
}
```

3.6.5.7 Successful response sample

HTTP Status 202

```
{
  "Code": "873345b2-882f-4064-91f0-90669b46c30a",
  "Message_Type": "ETL",
  "Error": false,
  "Errors": null,
  "Checksum": "G6HF5H"
}
```

3.6.5.8 Error response sample

HTTP status		
<< Common response code >>		
400	MULTIPLE_UID	VAL_UI_MULT_MSG
400	UI_NOT_EXIST UI_NOT_VALID	VAL_UI_EXIST_UPUI
400	UI_NOT_EXIST	VAL_UI_EXIST_AUI
400	UI_NOT_VALID	VAL_UI_EXIST_UPUI_SEQ
400	UI_NOT_EXIST	VAL_UI_EXIST_AUI_SEQ
400	EOID_NOT_EXIST_OR_ACTIVE	VAL_ENT_EXIST_EOID
400	FID_NOT_EXIST_OR_ACTIVE	VAL_ENT_EXIST_FID
400	EOID_NOT_EXIST_OR_ACTIVE	VAL_ENT_ACTIVE_EOID
400	UI_DEACTIVATED	VAL_UI_ORD_DEACTIVATED
400	UI_ALREADY_DISAGGREGATED	VAL_UI_ORD_DISAGG or VAL_UI_ORD_IMPLDISAGG
299	SHIPMENT_WITHIN_24_HOURS	VAL_EVT_TIME

3.6.6 EUD – (3.6) Disaggregation of aggregated level UIs

3.6.6.1 Description

Event showing that an aggregation no longer exists.

3.6.6.2 Description of the fields

aUI disaggregation event					
Field	Description	Data Type	Cardinality	Priority	Values
BasicInfo_Req	Block of basic information elements	Component << Basic Information Request >>	S	M	Message_Type = EUD
EO_ID	Economic operator's identifier	EOID	S	M	
F_ID	Facility's identifier	FID	S	M	
Event_Time	Time of event occurrence	Time(s)	S	M	

Message_Time_long	Message sending Time	Time(L)	S	M	
aUI	Aggregated level UI subject to disaggregation	aUI	S	M	
disaUI_comment	Comments by the reporting entity	Text(5000)	S	O	

3.6.6.3 Business validation

	EUD (3.6)
Business rule validation	
UI creation	
VAL_UI_EXIST_AUI	aUI
VAL_UI_EXIST_AUI_SEQ	aUI
Entity Validation	
VAL_ENT_EXIST_EOID	EO_ID
VAL_ENT_EXIST_FID	F_ID
VAL_ENT_ACTIVE_EOID	EO_ID
Sequence Validation	
VAL_UI_ORD_DEACTIVATED	aUI
VAL_UI_ORD_AGG_FID	aUI (ONLY for aUI that have not been implicitly disaggregated)

3.6.6.4 Sequence validation

The following table represents the authorized transitions for a UI and specifically the previous message for the UI.

	EPA EPA 3.2 parent UI Import EPA 3.2 Child			ERP 3.4 (Return)		EUD 3.6 (aUI implicitly disaggregated) - reuse of aUI	
Message Received							
EUD 3.6	Yes	Yes	Yes	Yes	Yes	No	Yes

No	Next message not allowed for the UI (including different aggregation)
Yes	Next Message allowed
Yes (with Location Validation)	Next Message allowed with location validation

3.6.6.4.1 Clarification of the location validation

The disaggregation event is subject to the location validation (VAL_UI_ORD_AGG_FID). In other words, the aUI that are been disaggregated must be in the same facility.

There is exception for aUI that have been already disaggregated implicitly.

3.6.6.4.2 Clarification on the impact of Implicit disaggregation

The reporting of a disaggregation event (EUD 3.6) on an aUI that have been previously implicitly disaggregated (by any the reporting of an event that allows the triggering of the implicit disaggregation mechanism) doesn't correspond to any physical movement. Therefore, the location validation control VAL_UI_ORD_AGG_FID will not be applied.




Figure 11 reporting of disaggregation event on aUI that are implicitly disaggregated.

3.6.6.5 Implicit disaggregation trigger

This event can trigger an implicit disaggregation when a child UI is identified as part of the event.

3.6.6.6 Response:

aUI disaggregation event– response

Field	Description	Data Type	Cardinality	Priority	Values
BasicInfo_Resp	Block of basic information elements	Component << Basic Information Response >>	S	M	Message_Type = EUD

3.6.6.7 Request sample

```
{
  "EO_ID": "QCUKR+1AB020054",
  "F_ID": "QCUKR<1AB020054000049",
  "Event_Time": "19032014",
  "Message_Time_Long": "2019-03-20T14:16:45Z",
  "aUI": "DANXXXXXXXXXXXX10FA00000119030110",
  "disaUI_comment": "Comments",
  "Message_Type": "EUD",
  "Code": "873345b2-882f-4064-91f0-90669b46c30a"
}
```

3.6.6.8 Successful response sample

HTTP Status 202

```
{
  "Code": "873345b2-882f-4064-91f0-90669b46c30a",
  "Message_Type": "EUD",
  "Error": false,
  "Errors": null,
  "Checksum": "G6HF5H"
}
```

3.6.6.9 Error response sample

HTTP status	Error Code	Error Description
<< Common response code >>		
400	UI_NOT_EXIST	VAL_UI_EXIST_AUI
400	UI_NOT_VALID	VAL_UI_EXIST_AUI_SEQ
400	EUID_NOT_EXIST_OR_ACTIVE	VAL_ENT_EXIST_EUID
400	FID_NOT_EXIST_OR_ACTIVE	VAL_ENT_EXIST_FID
400	EUID_NOT_EXIST_OR_ACTIVE	VAL_ENT_ACTIVE_EUID
400	UI_DEACTIVATED	VAL_UI_ORD_DEACTIVATED
400	LOCATION_MISMATCH	VAL_UI_ORD_AGG_FID

3.6.7 EVR – (3.7) Report the delivery carried out with a vending van to retail outlet

3.6.7.1 Description

Event sent when UIs have been distributed via a van delivery.

3.6.7.2 Description of the fields

Vending Van event					
Field	Description	Data Type	Cardinality	Priority	Values
BasicInfo_Req	Block of basic information elements	Component << Basic Information Request >>	S	M	Message_Type = EVR
EO_ID	Economic operator identifier code of the submitting entity	EOID	S	M	
F_ID	Facility identifier code of retail outlet	FID	S	M	
Event_Time	Time of event occurrence	Time(s)	S	M	
Message_Time_long	Message sending Time	Time(L)	S	M	
UI_Type	Identification of UI types delivered (recorded at the highest level of available aggregation)	Integer	S	M	1 – only unit packet level UIs 2 – only aggregated level UIs 3 – both unit packet and aggregated level UIs
upUIs	List of unit packet level UIs delivered	upUI(L)	M	M, if UI_Type = 1 or 3	
aUIs	List of aggregated level UIs delivered	aUI	M	M, if UI_Type = 2 or 3	
Delivery_comment	Comments by the reporting entity	Text(5000)	S	O	
Information	Indicates the request of additional optional information	Boolean	S	O	0 – No 1 – Yes

3.6.7.3 Business validation

	EVR (3.7)
Technical validation	
VAL_UI_MULT_MSG	upUIs, aUIs
Business rule validation	

UI creation	
VAL_UI_EXIST_UPUI	upUIs
VAL_UI_EXIST_AUI	aUIs
VAL_UI_EXIST_UPUI_SEQ	upUIs
VAL_UI_EXIST_AUI_SEQ	aUIs
Entity Validation	
VAL_ENT_EXIST_EOID	EO_ID
VAL_ENT_EXIST_FID	F_ID
VAL_ENT_ACTIVE_EOID	EO_ID
Sequence Validation	
VAL_UI_ORD_DEACTIVATED	upUIs, aUIs
VAL_UI_ORD_DISAGG	aUIs
VAL_UI_ORD_IMPLDISAGG	aUIs
Message Timing	
VAL_EVT_24H	Event_Time

3.6.7.4 Sequence Validation

The following table represents the authorized transitions for a UI and specifically the previous message for the UI.

	EDP 3.3 (type 1) Export	EDP 3.3 (type 2)	EDP 3.3 (types 3) VM	EDP 3.3 (type 4) VV
Message Received				
EVR 3.7	No	No	No	Yes

No	Next message not allowed for the UI (including different aggregation)
Yes	Next Message allowed
Yes (with Location Validation)	Next Message allowed with location validation

For each UI in the event, An EVR must be preceded by a Dispatch event (EDP 3.3) of type 4. Any other combination will result in a Sequence Error

Note that the omission of the reporting of the Dispatch event (EDP 3.3) will result in a SEQUENCE_ERROR

3.6.7.5 Implicit disaggregation trigger

This event can trigger an implicit disaggregation when a child UI is identified as part of the event.

Implicit Disaggregation occurring when Delivering to Retail Outlet (EVR 3.7)




Figure 12 Implicit disaggregation trigger

3.6.7.6 Response:

Vending Van event – response					
Field	Description	Data Type	Cardinality	Priority	Values
BasicInfo_Resp	Block of basic information elements	Component << Basic Information Response >>	S	M	Message_Type = EVR
Basic Information Block	Additional optional acknowledgment Information	Component << Basic Information Block >>	S	O	

3.6.7.7 Request sample

```
{
  "EO_ID": "QCUKR+1AB020054",
  "F_ID": "QCUKR<1AB020054000049",
  "Event_Time": "19032014",
  "Message_Time_Long": "2019-03-20T14:16:45Z",
  "UI_Type": 1,
  "upUIs": [ "DANXXXXXXXXXXXXX1PR012345678919030110", "
DANXXXXXXXXXXXXX2PR012345678919030110" ],
  "aUIs": [ "DANXXXXXXXXXXXXX10FA00000119030110" ],
  "Delivery_comment": "Comments",
  "Message_Type": "EVR",
  "Code": "873345b2-882f-4064-91f0-90669b46c30a"
}
```

3.6.7.8 Successful response sample

HTTP Status 202

```
{
  "Code": "873345b2-882f-4064-91f0-90669b46c30a",
  "Message_Type": "EVR",
  "Error": false,
  "Errors": null,
  "Checksum": "G6HF5H"
}
```

3.6.7.9 Error response sample

HTTP status		
<< Common response code >>		
400	MULTIPLE_UID	VAL_UI_MULT_MSG
400	UI_NOT_EXIST UI_NOT_VALID	VAL_UI_EXIST_UPUI
400	UI_NOT_EXIST	VAL_UI_EXIST_AUI
400	UI_NOT_VALID	VAL_UI_EXIST_UPUI_SEQ
400	UI_NOT_EXIST	VAL_UI_EXIST_AUI_SEQ
400	EOID_NOT_EXIST_OR_ACTIVE	VAL_ENT_EXIST_EOID
400	FID_NOT_EXIST_OR_ACTIVE	VAL_ENT_EXIST_FID
400	EOID_NOT_EXIST_OR_ACTIVE	VAL_ENT_ACTIVE_EOID
400	UI_DEACTIVATED	VAL_UI_ORD_DEACTIVATED
400	UI_ALREADY_DISAGGREGATED	VAL_UI_ORD_DISAGG or VAL_UI_ORD_IMPLDISAGG
299	SHIPMENT_WITHIN_24_HOURS	VAL_EVT_24H

3.7 EPCIS Reporting operational events (product movement information)

3.7.1 General

3.7.1.1 ISO 8859-15 character set.

The payload of each field identified in Annex II as Data Type "Text" is restricted to the ISO 8859-15 character set. this applies to the following EPCIS fields, by message:

		EPCIS Fields
EUA	3.1 Commissioning	<fit:messageType> <fit:comment>
EPA	3.2 Packing	<fit:messageType> <fit:comment>
EDP	3.3 Dispatch	<fit:messageType> <fit:comment>
ERP	3.4 Receiving	<fit:destinationID5name> <fit:destinationID5streetAddressOne> <fit:destinationID5streetAddressTwo> <fit:destinationID5city> <fit:destinationID5postalCode> <fit:transportVehicle> <fit:transportS2> <fit:saadNumber> <fit:comment>
ETL	3.5 Transloading	<fit:messageType> <fit:comment>
EUD	3.6 Unpacking	<fit:messageType> <fit:comment>
EVR	3.7 Arriving	<fit:messageType> <fit:comment>

3.7.1.2 Message identification

Each message will be sent to the interface with a new "eventID" field that will contain a UUID generated by the sender party. This UUID will be then used as the recallCode for the event, instead of the repositories system generating a code.

```
<!-- added UUID -->
<baseExtension>
  <eventID>urn:uuid:d24aa483-94b5-4c65-ac3f-8b908ff61647</eventID>
</baseExtension>
```

3.7.1.3 Document and Events

Only one Event per document should be transmitted.

3.7.1.4 Responses

In alignment with the EPCIS v1.2 Capture Interface standard, the interface returns an empty payload and only replies with the relevant HTTP code of the result of the message validation.

As a result of this, by usage of this interface any HTTP Code 2xx will be an accepted message and any 4xx or 5xx HTTP Code will mean the message was rejected or erroneous.

As of now due to this limitation in the standard the exact reason for the error will not be returned. If future versions of the EPCIS standard remove this limitation the interface might be updated.

3.7.2 EPCIS - EUA – (3.1) Application of unit level UIs on unit packets

3.7.2.1 Description

Application of unit level UIs on unit packets will be captured as an EPCIS Object Event (business step "Commissioning")

3.7.2.2 Description of the fields

EPCIS EUA - Application of unit level UIs on unit packets	
Field	Values
<ObjectEvent>	<i>nested</i>
<action>	ADD
<eventTime>	Reference: Event_Time
<eventTimeZoneOffset>	Time zone offset from UTC in effect at the time and place the event occurred.
<baseExtension>	"<eventID>" tag containing a UUID that must be generated by the sender and will be used as the recallCode for the message. Example: <pre><eventID>urn:uuid:d24aa483-94b5-4c65-ac3f-8b908ff61647</eventID></pre>
<epcList>	One or more packs, each identified by UPUI EPC URI.
<readPoint>	GLN identifying the facility, <id> expressed as SGLN EPC URI, qualified by <fit:fid> extension to the readPoint, linking the SGLN of the readPoint to the Facility Identifier code, represented by the concatenated GS1 element strings AI(7040) and AI (414), where AI (414) corresponds to the first two segments of the readPoint's SGLN EPC URI, for example: <pre><fit:fid>(7040)5f(414)1234567890128</fit:fid></pre> <pre><readPoint></pre> <pre><id>urn:epc:id:sgln:1234567.89012.0</id></pre>

EPCIS EUA - Application of unit level UIs on unit packets	
Field	Values
<bizStep>	urn:epcglobal:cbv:bizstep:commissioning
<disposition>	urn:epcglobal:cbv:disp:active
<fit:messageType>	3-1
<fit:eoid>	Concatenation of GS1 element strings AI(7040) and AI (417), UIM and GLN representing Economic Operator identifier code of submitting entity, <fit:eoid epc="urn:epc:id:pgln:1234567.89012" gs1ElementString="(7040)5f(417)1234567890128"/>
<fit:upui2>	List of corresponding unit packet level UIs to be recorded (as visible in human readable format) indicated in the same order as upUI_1 – will be introduced to the revision of "FIT with EPCIS" in the form of the "fit:upui2" extension
<fit:comment>	Optional free text comments by reporting entity, limited to 1000 characters.

upUI_2 – The ampersand ("&"), greater-than (">") and less-than ("<") characters are expressed with **escape codes that differ** for URI syntax (i.e., for the EPC UPUI URIs) and XML syntax (i.e., for the human-readable encoding in the "hriOnPack" field), as follows:

character	URI escape code (for UPUI EPC)	XML escape code (for "hriOnPack")
&	%26	&
>	%3E	>
<	%3C	<

3.7.2.3 Request sample

```
<?xml version="1.0"?>
<epcis:EPCISDocument xmlns:epcis="urn:epcglobal:epcis:xsd:1" schemaVersion="1.2"
  xmlns:fit="https://gs1.org/cbv/fit" xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xsi:schemaLocation="urn:epcglobal:epcis:xsd:1 EPCglobal-epcis-1_2.xsd"
  creationDate="2019-03-11T16:46:00.000Z">

  <EPCISBody>
    <EventList>
      <!-- 3.1 -->
      <ObjectEvent>
        <eventTime>2018-12-03T09:09:00.000+01:00</eventTime>
        <eventTimeZoneOffset>+01:00</eventTimeZoneOffset>
        <!-- added UUID -->
        <baseExtension>
          <eventID>urn:uuid:d24aa483-94b5-4c65-ac3f-8b908ff61647</eventID>
        </baseExtension>
        <epcList>
          <epc>urn:epc:id:upui:1234567.054321.5vY)%3C%26Jp3*j7</epc>
          <epc>urn:epc:id:upui:1234567.054321.5vPxbrJk3th5</epc>
        </epcList>
      </ObjectEvent>
    </EventList>
  </EPCISBody>
</epcis:EPCISDocument>
```

```

    <epc>urn:epc:id:upui:1234567.054321.5vs*)%3Ek85Jp3*j7</epc>
    <epc>urn:epc:id:upui:1234567.054321.5v8rntU1;00U%3F</epc>
    <epc>urn:epc:id:upui:1234567.054321.5vB102bte175th</epc>
    <epc>urn:epc:id:upui:1234567.054321.5v4CDrco52241BRd</epc>
    <epc>urn:epc:id:upui:1234567.054321.5vittJekPgalpH</epc>
    <epc>urn:epc:id:upui:1234567.054321.5vaC1000FyakK</epc>
    <epc>urn:epc:id:upui:1234567.054321.5vgpuT4aHtd</epc>
    <epc>urn:epc:id:upui:1234567.054321.5vrLbDflilwiF</epc>
  </epcList>
  <action>ADD</action>
  <bizStep>urn:epcglobal:cbv:bizstep:commissioning</bizStep>
  <disposition>urn:epcglobal:cbv:disp:active</disposition>
  <readPoint>
    <id>urn:epc:id:sgln:1234567.54321.0</id>
    <fit:fid>(7040)5v9_(414)1234567543215</fit:fid>
  </readPoint>
  <fit:messageType>3-1</fit:messageType>
  <fit:eoid epc="urn:epc:id:pgln:1234567.89012"
    gs1ElementString="(7040)5f9_(417)1234567890128"/>
  <!-- Human-readable on-pack encodings below, corresponding to upUI_2(H) of Annex
II -->
  <fit:upui2 epc="urn:epc:id:upui:1234567.054321.5vY)%3C%26Jp3*j7"
    hriOnPack="(235)5vY)&lt;&amp;Jp3*j7(01)01234567543215(8008)18120308"/>
  <fit:upui2 epc="urn:epc:id:upui:1234567.054321.5vPxbrJk3th5"
    hriOnPack="(235)5vPxbrJk3th5(01)01234567543215(8008)18120308"/>
  <fit:upui2 epc="urn:epc:id:upui:1234567.054321.5vs*)%3Ek85Jp3*j7"
    hriOnPack="(235)5vs*)&gt;k85Jp3*j7(01)01234567543215(8008)18120308"/>
  <fit:upui2 epc="urn:epc:id:upui:1234567.054321.5v8rntU1;00U%3F"
    hriOnPack="(235)5v8rntU1;00U?(01)01234567543215(8008)18120308"/>
  <fit:upui2 epc="urn:epc:id:upui:1234567.054321.5vB102bte175th"
    hriOnPack="(235)5vB102bte175th(01)01234567543215(8008)18120308"/>
  <fit:upui2 epc="urn:epc:id:upui:1234567.054321.5v4CDrco52241BRd"
    hriOnPack="(235)5v4CDrco52241BRd(01)01234567543215(8008)18120308"/>
  <fit:upui2 epc="urn:epc:id:upui:1234567.054321.5vittJekPgalpH"
    hriOnPack="(235)5vittJekPgalpH(01)01234567543215(8008)18120308"/>
  <fit:upui2 epc="urn:epc:id:upui:1234567.054321.5vaC1000FyakK"
    hriOnPack="(235)5vaC1000FyakK(01)01234567543215(8008)18120308"/>
  <fit:upui2 epc="urn:epc:id:upui:1234567.054321.5vgpuT4aHtd"
    hriOnPack="(235)5vgpuT4aHtd(01)01234567543215(8008)18120308"/>
  <fit:upui2 epc="urn:epc:id:upui:1234567.054321.5vrLbDflilwiF"
    hriOnPack="(235)5vrLbDflilwiF(01)01234567543215(8008)18120308"/>
  <fit:comment>3.1 Application of unit level UIs on unit packets</fit:comment>
</ObjectEvent>

</EventList>
</EPCISBody>
</epcis:EPCISDocument>

```

3.7.3 EPCIS - EPA – (3.2) Application of aggregated level UIs on aggregated packaging

3.7.3.1 Description

Message 3.2, “Application of aggregated level UIs on aggregated packaging”, is captured in one or more EPCIS Aggregation Events –

iterative as necessary, to allow for “nesting” of hierarchical levels – with business step Packing, as follows.

3.7.3.2 Description of the fields

EPCIS EPA - Application of aggregated level UIs on aggregated packaging	
Field	Values
<AggregationEvent>	<i>nested</i>
<action>	ADD
<eventTime>	Reference: Event_Time
<eventTimeZoneOffset>	Time zone offset from UTC in effect at the time and place the event occurred.
<baseExtension>	“<eventID>” tag containing a UUID that must be generated by the sender and will be used as the recallCode for the message. Example: <eventID>urn:uuid:d24aa483-94b5-4c65-ac3f-8b908ff61647</eventID>
<parentID>	Parent ID, in SGTIN EPC URI or SSCC EPC URI
<childEPCs>	Child EPCs, in SGTIN/SSCC EPC UI or UPUi EPC URI
<readPoint>	GLN identifying the facility, <id> expressed as SGLN EPC URI, qualified by <fit:fid> extension to the readPoint, linking the SGLN of the readPoint to the Facility Identifier code, represented by the concatenated GS1 element strings AI(7040) and AI (414), where AI (414) corresponds to the first two segments of the readPoint’s SGLN EPC URI, for example: <fit:fid>(7040)5f(414)1234567890128</fit:fid> <readPoint> <id>urn:epc:id:sgln:1234567.89012.0</id>
<bizStep>	urn:epcglobal:cbv:bizstep:packing
<disposition>	urn:epcglobal:cbv:disp:active
<fit:messageType>	3-2
<fit:aggregationType>1</fit:aggregationType>	Reference: Aggregation Type
<fit:eoid>	Concatenation of GS1 element strings AI(7040) and AI (417), UIM and GLN representing Economic

EPCIS EPA - Application of aggregated level UIs on aggregated packaging	
Field	Values
	Operator identifier code of submitting entity, <fit:eoid epc="urn:epc:id:pgln:1234567.89012" gs1ElementString="(7040)5f(417)1234567890128"/>
<fit:comment>	Optional free text comments by reporting entity, limited to 1000 characters.

3.7.3.3 Request sample

```
<?xml version="1.0"?>
<epcis:EPCISDocument xmlns:epcis="urn:epcglobal:epcis:xsd:1" schemaVersion="1.2"
  xmlns:fit="https://gs1.org/cbv/fit" xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xsi:schemaLocation="urn:epcglobal:epcis:xsd:1 EPCglobal-epcis-1_2.xsd"
  creationDate="2019-03-11T16:46:00.000Z">

  <EPCISBody>
    <EventList>

      <!-- 3.2 -->
      <!-- 3.2.1 -->
      <AggregationEvent>
        <eventTime>2018-12-03T10:10:00.000+01:00</eventTime>
        <eventTimeZoneOffset>+01:00</eventTimeZoneOffset>
        <!-- added UUID -->
        <baseExtension>
          <eventID>urn:uuid:433a2eb3-8c8f-4412-a54d-9ba372c75ef1</eventID>
        </baseExtension>
        <parentID>urn:epc:id:sgtin:1234567.012345.9876543210</parentID>
        <childEPCs>
          <epc>urn:epc:id:upui:1234567.054321.5vY)%3C%26Jp3*j7</epc>
          <epc>urn:epc:id:upui:1234567.054321.5vPxbrJk3th5</epc>
          <epc>urn:epc:id:upui:1234567.054321.5vs*)%3Ek85Jp3*j7</epc>
          <epc>urn:epc:id:upui:1234567.054321.5v8rntU1;00U%3F</epc>
          <epc>urn:epc:id:upui:1234567.054321.5vB102bte175th</epc>
          <epc>urn:epc:id:upui:1234567.054321.5v4CDrco52241BRd</epc>
          <epc>urn:epc:id:upui:1234567.054321.5vittJekPgalpH</epc>
          <epc>urn:epc:id:upui:1234567.054321.5vaC1000FyakK</epc>
          <epc>urn:epc:id:upui:1234567.054321.5vgpuT4aHtd</epc>
          <epc>urn:epc:id:upui:1234567.054321.5vrLbDflilwiF</epc>
        </childEPCs>
        <action>ADD</action>
        <bizStep>urn:epcglobal:cbv:bizstep:packing</bizStep>
        <disposition>urn:epcglobal:cbv:disp:in_progress</disposition>
        <readPoint>
          <id>urn:epc:id:sgln:1234567.54321.0</id>
          <fit:fid>(7040)5v9_(414)1234567543215</fit:fid>
        </readPoint>
        <fit:messageType>3-2</fit:messageType>
        <fit:aggregationType>1</fit:aggregationType>
      </AggregationEvent>
    </EventList>
  </EPCISBody>
</epcis:EPCISDocument>
```

```

        <fit:eoid epc="urn:epc:id:pgln:1234567.89012"
            gs1ElementString="(7040)5f9_(417)1234567890128"/>
        <fit:comment>3.2.1 Application of aggregated level UIs on units to
carton</fit:comment>
    </AggregationEvent>

</EventList>
</EPCISBody>
</epcis:EPCISDocument>

```

```

<?xml version="1.0"?>
<epcis:EPCISDocument xmlns:epcis="urn:epcglobal:epcis:xsd:1" schemaVersion="1.2"
    xmlns:fit="https://gs1.org/cbv/fit" xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
    xsi:schemaLocation="urn:epcglobal:epcis:xsd:1 EPCglobal-epcis-1_2.xsd"
    creationDate="2019-03-11T16:46:00.000Z">

    <EPCISBody>
        <EventList>

            <!-- 3.2.2 -->
            <AggregationEvent>
                <eventTime>2018-12-03T11:11:00.000+01:00</eventTime>
                <eventTimeZoneOffset>+01:00</eventTimeZoneOffset>
                <!-- added UUID -->
                <baseExtension>
                    <eventID>urn:uuid:a1c9d58c-b7af-4f9e-9dbb-e5d88bf32ce2</eventID>
                </baseExtension>
                <parentID>urn:epc:id:sgtin:1234567.055555.5678901234</parentID>
                <childEPCs>
                    <epc>urn:epc:id:sgtin:1234567.012345.9876543210</epc>
                    <epc>urn:epc:id:sgtin:1234567.012345.8765432109</epc>
                    <epc>urn:epc:id:sgtin:1234567.012345.7654321098</epc>
                    <epc>urn:epc:id:sgtin:1234567.012345.6543210987</epc>
                    <epc>urn:epc:id:sgtin:1234567.012345.5432109876</epc>
                    <epc>urn:epc:id:sgtin:1234567.012345.4321098765</epc>
                    <epc>urn:epc:id:sgtin:1234567.012345.3210987654</epc>
                    <epc>urn:epc:id:sgtin:1234567.012345.2109876543</epc>
                    <epc>urn:epc:id:sgtin:1234567.012345.1098765432</epc>
                    <epc>urn:epc:id:sgtin:1234567.012345.1987654321</epc>
                    <epc>urn:epc:id:sgtin:1234567.012345.1234567890</epc>
                    <epc>urn:epc:id:sgtin:1234567.012345.2345678901</epc>
                    <epc>urn:epc:id:sgtin:1234567.012345.3456789012</epc>
                    <epc>urn:epc:id:sgtin:1234567.012345.4567890123</epc>
                    <epc>urn:epc:id:sgtin:1234567.012345.5678901234</epc>
                    <epc>urn:epc:id:sgtin:1234567.012345.6789012345</epc>
                    <epc>urn:epc:id:sgtin:1234567.012345.7890123456</epc>
                    <epc>urn:epc:id:sgtin:1234567.012345.8901234567</epc>
                    <epc>urn:epc:id:sgtin:1234567.012345.9012345678</epc>
                    <epc>urn:epc:id:sgtin:1234567.012345.1123456789</epc>
                </childEPCs>
                <action>ADD</action>
                <bizStep>urn:epcglobal:cbv:bizstep:packing</bizStep>
                <disposition>urn:epcglobal:cbv:disp:in_progress</disposition>
                <readPoint>
                    <id>urn:epc:id:sgln:1234567.54321.0</id>
                    <fit:fid>(7040)5v9_(414)1234567543215</fit:fid>

```



```

        </readPoint>
        <fit:messageType>3-2</fit:messageType>
        <fit:aggregationType>2</fit:aggregationType>
        <fit:eoid epc="urn:epc:id:pgln:1234567.89012"
          gs1ElementString="(7040)5v9_(417)1234567890128"/>
        <fit:comment>3.2.2 Application of aggregated level UIs on cartons to
          case</fit:comment>
      </AggregationEvent>

    </EventList>
  </EPCISBody>
</epcis:EPCISDocument>

```

```

<?xml version="1.0"?>
<epcis:EPCISDocument xmlns:epcis="urn:epcglobal:epcis:xsd:1" schemaVersion="1.2"
  xmlns:fit="https://gs1.org/cbv/fit" xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xsi:schemaLocation="urn:epcglobal:epcis:xsd:1 EPCglobal-epcis-1_2.xsd"
  creationDate="2019-03-11T16:46:00.000Z">

  <EPCISBody>
    <EventList>

      <!-- 3.2.3 -->
      <AggregationEvent>
        <eventTime>2018-12-04T12:12:00.000+01:00</eventTime>
        <eventTimeZoneOffset>+01:00</eventTimeZoneOffset>
        <!-- added UUID -->
        <baseExtension>
          <eventID>urn:uuid:6e6f0345-f1cb-460e-adf8-33db2a3844a4</eventID>
        </baseExtension>
        <parentID>urn:epc:id:sscc:1234567.0123456789</parentID>
        <childEPCs>
          <epc>urn:epc:id:sgtin:1234567.055555.5678901234</epc>
          <epc>urn:epc:id:sgtin:1234567.055555.6789012345</epc>
          <epc>urn:epc:id:sgtin:1234567.055555.7890123456</epc>
          <epc>urn:epc:id:sgtin:1234567.055555.8901234567</epc>
        </childEPCs>
        <action>ADD</action>
        <bizStep>urn:epcglobal:cbv:bizstep:packing</bizStep>
        <disposition>urn:epcglobal:cbv:disp:in_progress</disposition>
        <readPoint>
          <id>urn:epc:id:sgln:1234567.54321.0</id>
          <fit:fid>(7040)5v9_(414)1234567543215</fit:fid>
        </readPoint>
        <fit:messageType>3-2</fit:messageType>
        <fit:aggregationType>2</fit:aggregationType>
        <fit:eoid epc="urn:epc:id:pgln:1234567.89012"
          gs1ElementString="(7040)5f9_(417)1234567890128"/>
        <fit:comment>3.2.3 Application of aggregated level UIs on case to logistics
          unit</fit:comment>
      </AggregationEvent>

    </EventList>
  </EPCISBody>
</epcis:EPCISDocument>

```

3.7.4 EPCIS - EDP – (3.3) Dispatch of tobacco products from a facility

3.7.4.1 Description

Message 3.3, “Dispatch of tobacco products from a facility”, is captured in an EPCIS Object Event with business step Shipping, as follows.

3.7.4.2 Description of the fields

EPCIS EDP - Dispatch of tobacco products from a facility event	
Field	Values
<ObjectEvent>	<i>nested</i>
<eventTime>	Reference: Event_Time
<eventTimeZoneOffset>	Time zone offset from UTC in effect at the time and place the event occurred.
<baseExtension>	“<eventID>” tag containing a UUID that must be generated by the sender and will be used as the recallCode for the message. Example: <pre><eventID>urn:uuid:d24aa483-94b5-4c65-ac3f-8b908ff61647</eventID></pre>
<action>	OBSERVE
<epcList>	EPCs, in SGTIN/SSCC EPC UI or UPUI EPC URI Example: <pre><epc>urn:epc:id:upui:1234567.054321.5vY)%3C%26Jp3*j7</epc> <epc>urn:epc:id:sgtin:1234567.012345.9876543210</epc> <epc>urn:epc:id:sscc:1234567.0123456789</epc></pre>
<readPoint>	GLN identifying the facility, <id> expressed as SGLN EPC URI, qualified by <fit:fid> extension to the readPoint, linking the SGLN of the readPoint to the Facility Identifier code, represented by the concatenated GS1 element strings AI(7040) and AI (414), where AI (414) corresponds to the first two segments of the readPoint’s SGLN EPC URI, for example: <pre><fit:fid>(7040)5f(414)1234567890128</fit:fid></pre> <readPoint>

EPCIS EDP - Dispatch of tobacco products from a facility event	
Field	Values
	<id>urn:epc:id:sgln:1234567.89012.0</id>
<bizStep>	urn:epcglobal:cbv:bizstep:shipping
<disposition>	urn:epcglobal:cbv:disp:in_transit
<fit:messageType>	3-3
<fit:uiType>	Reference: UI_Type
<fit:eoid>	Concatenation of GS1 element strings AI(7040) and AI (417), UIM and GLN representing Economic Operator identifier code of submitting entity, <fit:eoid epc="urn:epc:id:pgl:1234567.89012" gs1ElementString="(7040)5f(417)1234567890128"/>
<fit:destinationID1>	Reference: Destination_ID1
<fit:destinationIDList>	List of <fit:destinationID type="X"> nodes, where X determines if it represents a "Destination_ID2, Destination_ID3 or Destination_ID4". Reference: Destination_ID2, Destination_ID3, Destination_ID4. Example: <fit:destinationID type="2" epc="urn:epc:id:sgln:0614141.00777.0" gs1ElementString="(7040)5v9_(414)0614141007776"/>
<fit:destinationID5name>	Reference: Destination_ID5_Address_Name
<fit:destinationID5streetAddressOne>	Reference: Destination_ID5_Address_StreetOne
<fit:destinationID5streetAddressTwo>	Reference: Destination_ID5_Address_StreetTwo
<fit:destinationID5city>	Reference: Destination_ID5_Address_City
<fit:destinationID5postalCode>	Reference: Destination_ID5_Address_PostCode
<fit:destinationID5countryCode>	Reference: Destination_ID5_countryCode
<fit:transportMode>	Reference: Transport_mode

EPCIS EDP - Dispatch of tobacco products from a facility event	
Field	Values
<fit:transportVehicle>	Reference: Transport_vehicle
<fit:transportCont2>	Reference: Transport_cont2 Note that Annex II field "transportCont1" (indication if the transport is containerized and uses an individual transport unit code) is rendered superfluous by the inclusion or omission of the "transportCont2" field in the EPCIS event. Inclusion of "transportCont2" implies a "Yes" value for "transportCont1"; omission of "transportCont2" implies a "No" value for "transportCont1".
<fit:transportS1>	Reference: Transport_s1 Note that you have to use "false" instead of "0" and "true" instead of "1"
<fit:transportS2>	Reference: Transport_s2
<fit:emcsARC>	Reference: EMCS_ARC Note that Annex II field "emcs" (Dispatch under the Excise Movement and Control System, EMCS) is rendered superfluous by the inclusion or omission of the "emcsARC" field in the EPCIS event. Inclusion of "emcsARC" implies a "Yes" value for "emcs"; omission of "emcsARC" implies a "No" value for "emcs".
<fit:saadNumber>	Reference: SAAD_number Note that Annex II field "saad" (Dispatch with a simplified accompanying document, per Commission Regulation EEC No 3649/92) is rendered superfluous by the inclusion or omission of the "transportCont2" field in the EPCIS event. Inclusion of "saadNumber" implies a "Yes" value for "saad"; omission of "saadNumber" implies a "No" value for "saad".
<fit:expDeclarationNumber>	Reference: Exp_DeclarationNumber

EPCIS EDP - Dispatch of tobacco products from a facility event	
Field	Values
	Note that Annex II field "expDeclaration" (Indication if the Movement Reference Number (MRN) has been issued by the customs office) is rendered superfluous by the inclusion or omission of the "expDeclarationNumber" field in the EPCIS event. Inclusion of "expDeclarationNumber" implies a "Yes" value for "expDeclaration"; omission of "expDeclarationNumber" implies a "No" value for "expDeclaration".
<fit:comment>	Optional free text comments by reporting entity, limited to 1000 characters.

3.7.4.3 Request sample

```
<?xml version="1.0"?>
<epcis:EPCISDocument xmlns:epcis="urn:epcglobal:epcis:xsd:1" schemaVersion="1.2"
  xmlns:fit="https://gs1.org/cbv/fit" xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xsi:schemaLocation="urn:epcglobal:epcis:xsd:1 EPCglobal-epcis-1_2.xsd"
  creationDate="2019-03-11T16:46:00.000Z">

  <EPCISBody>
    <EventList>

      <!-- 3.3 -->
      <ObjectEvent>
        <eventTime>2018-12-04T13:13:00.000+01:00</eventTime>
        <eventTimeZoneOffset>+01:00</eventTimeZoneOffset>
        <!-- added UUID -->
        <baseExtension>
          <eventID>urn:uuid:dc58edda-c24f-4416-9dc9-a5f41e58b76f</eventID>
        </baseExtension>
        <epcList>
          <epc>urn:epc:id:sscc:1234567.0123456789</epc>
        </epcList>
        <action>OBSERVE</action>
        <bizStep>urn:epcglobal:cbv:bizstep:shipping</bizStep>
        <disposition>urn:epcglobal:cbv:disp:in_transit</disposition>
        <readPoint>
          <id>urn:epc:id:sgln:1234567.54321.0</id>
          <fit:fid>(7040)5v9_(414)1234567543215</fit:fid>
        </readPoint>
        <fit:messageType>3-3</fit:messageType>
        <fit:uiType>2</fit:uiType>
        <fit:eoid epc="urn:epc:id:pgln:1234567.89012"
          gs1ElementString="(7040)5f9_(417)1234567890128"/>
        <fit:destinationID1>2</fit:destinationID1>
        <fit:destinationIDList>
```

```

        <fit:destinationID type="2" epc="urn:epc:id:sgln:0614141.00777.0"
            gs1ElementString="(7040)5v9_(414)0614141007776"/>
    </fit:destinationIDList>
    <fit:destinationID5name>Ramos Tobacco</fit:destinationID5name>
    <fit:destinationID5streetAddressOne>Plaza de Espaga,
        1</fit:destinationID5streetAddressOne>
    <fit:destinationID5streetAddressTwo/>
    <fit:destinationID5city>Mostoles</fit:destinationID5city>
    <fit:destinationID5postalCode>28934</fit:destinationID5postalCode>
    <fit:destinationID5countryCode>ES</fit:destinationID5countryCode>
    <fit:transportMode>3</fit:transportMode>
    <fit:transportVehicle>(E)IXX359</fit:transportVehicle>
    <fit:transportCont2>(00)012345671234567893</fit:transportCont2>
    <fit:transportS1>>false</fit:transportS1>
    <fit:transportS2>(00)012345671234567893</fit:transportS2>
    <fit:emcsARC>12ES00000000006107577</fit:emcsARC>
    <fit:saadNumber>3649/92sample</fit:saadNumber>
    <fit:expDeclarationNumber>01ES45671234567893</fit:expDeclarationNumber>
    <fit:comment>3.3 Dispatch of tobacco products from a facility</fit:comment>
</ObjectEvent>

</EventList>
</EPCISBody>
</epcis:EPCISDocument>

```

3.7.5 EPCIS - ERP – (3.4) Arrival of tobacco products at a facility

3.7.5.1 Description

Message 3.4, "Arrival of tobacco products from a facility", is captured in an EPCIS Object Event with business step Receiving, as follows

3.7.5.2 Description of the fields

EPCIS ERP - Reception event	
Field	Values
<ObjectEvent>	<i>nested</i>
<eventTime>	Reference: Event_Time
<eventTimeZoneOffset>	Time zone offset from UTC in effect at the time and place the event occurred.
<baseExtension>	"<eventID>" tag containing a UUID that must be generated by the sender and will be used as the recallCode for the message. Example: <eventID>urn:uuid:d24aa483-94b5-4c65-ac3f-8b908ff61647</eventID>
<action>	OBSERVE
<epcList>	EPCs, in SGTIN/SSCC EPC UI or UPUI EPC URI Example:

EPCIS ERP - Reception event	
Field	Values
	<epc>urn:epc:id:upui:1234567.054321.5vY)%3C%26Jp3*j7</epc> <epc>urn:epc:id:sgtin:1234567.012345.9876543210</epc> <epc>urn:epc:id:sscc:1234567.0123456789</epc>
<readPoint>	GLN identifying the facility, <id> expressed as SGLN EPC URI, qualified by <fit:fid> extension to the readPoint, linking the SGLN of the readPoint to the Facility Identifier code, represented by the concatenated GS1 element strings AI(7040) and AI (414), where AI (414) corresponds to the first two segments of the readPoint's SGLN EPC URI, for example: <fit:fid>(7040)5f(414)1234567890128</fit:fid> <readPoint> <id>urn:epc:id:sgln:1234567.89012.0</id>
<bizStep>	urn:epcglobal:cbv:bizstep:receiving
<disposition>	urn:epcglobal:cbv:disp:in_progress
<fit:messageType>	3-4
<fit:uiType>	Reference: UI_Type
<fit:eoid>	Concatenation of GS1 element strings AI(7040) and AI (417), UIM and GLN representing Economic Operator identifier code of submitting entity, <fit:eoid epc="urn:epc:id:pghn:1234567.89012" gs1ElementString="(7040)5f(417)1234567890128"/>
<fit:productReturn>	Reference: Product_return Note that you have to use "false" instead of "0" and "true" instead of "1"
<fit:comment>	Optional free text comments by reporting entity, limited to 1000 characters.

3.7.5.3 Request sample

```
<?xml version="1.0"?>
<epcis:EPCISDocument xmlns:epcis="urn:epcglobal:epcis:xsd:1" schemaVersion="1.2"
  xmlns:fit="https://gs1.org/cbv/fit" xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xsi:schemaLocation="urn:epcglobal:epcis:xsd:1 EPCglobal-epcis-1_2.xsd"
  creationDate="2019-03-11T16:46:00.000Z">
  <EPCISBody>
    <EventList>

      <!-- 3.4 -->
      <ObjectEvent>
        <eventTime>2018-12-05T16:16:00.000+01:00</eventTime>
        <eventTimeZoneOffset>+01:00</eventTimeZoneOffset>
        <!-- added UUID -->
        <baseExtension>
          <eventID>urn:uuid:e8f5f311-c7f6-4d3f-ac38-ffb4a8c2f879</eventID>
        </baseExtension>
        <epcList>
          <epc>urn:epc:id:sscc:1234567.0123456789</epc>
        </epcList>
        <action>OBSERVE</action>
        <bizStep>urn:epcglobal:cbv:bizstep:receiving</bizStep>
        <disposition>urn:epcglobal:cbv:disp:in_progress</disposition>
        <readPoint>
          <id>urn:epc:id:sgln:1234567.89012.0</id>
          <fit:fid>(7040)5f9_(414)1234567890128</fit:fid>
        </readPoint>
        <fit:messageType>3-4</fit:messageType>
        <fit:uiType>2</fit:uiType>
        <fit:eoid epc="urn:epc:id:pgln:1234567.89012"
          gs1ElementString="(7040)5f9_(417)1234567890128"/>
        <fit:productReturn>false</fit:productReturn>
        <fit:comment>3.4 Arrival of tobacco products at a facility</fit:comment>
      </ObjectEvent>

    </EventList>
  </EPCISBody>
</epcis:EPCISDocument>
```

3.7.6 EPCIS - ETL – (3.5) Trans-loading

3.7.6.1 Description

Message 3.5 is captured as an ObjectEvent OBSERVE with a new bizStep added in GS1 CBV 2.3 "transloading".

3.7.6.2 Description of the fields

EPCIS ETL - Trans-loading event	
Field	Values
<ObjectEvent>	<i>nested</i>
<eventTime>	Reference: Event_Time
<eventTimeZoneOffset>	Time zone offset from UTC in effect at the time and place the event occurred.
<baseExtension>	"<eventID>" tag containing a UUID that must be generated by the sender and will be used as the recallCode for the message. Example: <pre><eventID>urn:uuid:d24aa483-94b5-4c65-ac3f-8b908ff61647</eventID></pre>
<action>	OBSERVE
<epcList>	EPCs, in SGTIN/SSCC EPC UI or UPUI EPC URI Example: <pre><epc>urn:epc:id:upui:1234567.054321.5vY)%3C%26Jp3*j7</epc> <epc>urn:epc:id:sgtin:1234567.012345.9876543210</epc> <epc>urn:epc:id:sscc:1234567.0123456789</epc></pre>
<readPoint>	geoURI identifying the geo-coordinates of unloading
<bizStep>	urn:epcglobal:cbv:bizstep:transloading
<disposition>	urn:epcglobal:cbv:disp:in_transit
<fit:messageType>	3-5
<fit:eoid>	Concatenation of GS1 element strings AI(7040) and AI (417), UIM and GLN representing Economic Operator identifier code of submitting entity, <pre><fit:eoid epc="urn:epc:id:pgln:1234567.89012" gs1ElementString="(7040)5f(417)1234567890128"/></pre>
<fit:uiType>	Reference: UI_Type
<fit:destinationID1>	Reference: Destination_ID1
<fit:destinationIDList>	List of <fit:destinationID type="X"> nodes, where X determines if it represents a "Destination_ID2, Destination_ID3 or Destination_ID4". Reference: Destination_ID2, Destination_ID3, Destination_ID4.

EPCIS ETL - Trans-loading event	
Field	Values
	Example: <pre><fit:destinationID type="2" epc="urn:epc:id:sgln:0614141.00777.0 " gs1ElementString="(7040)5v9_(414)06 14141007776"/></pre>
<fit:destinationID5name>	Reference: Destination_ID5_Address_Name
<fit:destinationID5streetAddressOne>	Reference: Destination_ID5_Address_StreetOne
<fit:destinationID5streetAddressTwo/>	Reference: Destination_ID5_Address_StreetTwo
<fit:destinationID5city>	Reference: Destination_ID5_Address_City
<fit:destinationID5postalCode>	Reference: Destination_ID5_Address_PostCode
<fit:destinationID5countryCode>	Reference: Destination_ID5_countryCode
<fit:transportMode>	Reference: Transport_mode
<fit:transportVehicle>	Reference: Transport_vehicle
<fit:transportCont2>	Reference: Transport_cont2 Note that Annex II field "transportCont1" (indication if the transport is containerized and uses an individual transport unit code) is rendered superfluous by the inclusion or omission of the "transportCont2" field in the EPCIS event. Inclusion of "transportCont2" implies a "Yes" value for "transportCont1"; omission of "transportCont2" implies a "No" value for "transportCont1".
<fit:emcsARC>	Reference: EMCS_ARC Note that Annex II field "emcs" (Dispatch under the Excise Movement and Control System, EMCS) is rendered superfluous by the inclusion or omission of the "emcsARC" field in the EPCIS event. Inclusion of "emcsARC" implies a "Yes" value for "emcs"; omission of "emcsARC" implies a "No" value for "emcs".

EPCIS ETL - Trans-loading event	
Field	Values
<fit:comment>	Optional free text comments by reporting entity, limited to 1000 characters.

3.7.6.3 Request sample

```
<?xml version="1.0"?>
<epcis:EPCISDocument xmlns:epcis="urn:epcglobal:epcis:xsd:1" schemaVersion="1.2"
  xmlns:fit="https://gs1.org/cbv/fit" xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xsi:schemaLocation="urn:epcglobal:epcis:xsd:1 EPCglobal-epcis-1_2.xsd"
  creationDate="2019-03-11T16:46:00.000Z">

  <EPCISBody>
    <EventList>

      <!-- 3.5 -->
      <ObjectEvent>
        <eventTime>2018-12-05T15:15:00.000+01:00</eventTime>
        <eventTimeZoneOffset>+01:00</eventTimeZoneOffset>
        <!-- added UUID -->
        <baseExtension>
          <eventID>urn:uuid:f924f7d8-dcaa-4e30-b9b5-7154ba329176</eventID>
        </baseExtension>
        <epcList>
          <epc>urn:epc:id:sscc:1234567.0123456789</epc>
        </epcList>
        <action>OBSERVE</action>
        <!-- NEW BUSINESS STEP transloading for CBV 2.0 -->
        <bizStep>urn:epcglobal:cbv:bizstep:transloading</bizStep>
        <disposition>urn:epcglobal:cbv:disp:in_transit</disposition>
        <readPoint>
          <id>geo:40.45306,3.68835</id>
        </readPoint>
        <fit:messageType>3-5</fit:messageType>
        <fit:uiType>2</fit:uiType>
        <fit:eoid epc="urn:epc:id:pgln:1234567.89012"
          gs1ElementString="(7040)5v9_(417)1234567890128"/>
        <fit:destinationID1>2</fit:destinationID1>
        <fit:destinationIDList>
          <fit:destinationID type="2" epc="urn:epc:id:sgln:0614141.00777.0"
            gs1ElementString="(7040)5v9_(414)0614141007776"/>
          <fit:destinationID type="2" epc="urn:epc:id:sgln:0614141.00778.0"
            gs1ElementString="(7040)5v9_(414)0614141007783"/>
        </fit:destinationIDList>
        <fit:destinationID5name>Ramos Tobacco</fit:destinationID5name>
        <fit:destinationID5streetAddressOne>Plaza de Espaga,
          1</fit:destinationID5streetAddressOne>
        <fit:destinationID5streetAddressTwo/>
        <fit:destinationID5city>Mostoles</fit:destinationID5city>
        <fit:destinationID5postalCode>28934</fit:destinationID5postalCode>
        <fit:destinationID5countryCode>ES</fit:destinationID5countryCode>
        <fit:transportMode>3</fit:transportMode>
        <fit:transportVehicle>(E)IXX359</fit:transportVehicle>
        <fit:transportCont2>(00)012345671234567893</fit:transportCont2>
        <fit:emcsARC>12ES00000000006107577</fit:emcsARC>
      </ObjectEvent>
    </EventList>
  </EPCISBody>
</epcis:EPCISDocument>
```

```

        <fit:comment>3.5 Trans-loading</fit:comment>
    </ObjectEvent>

</EventList>
</EPCISBody>
</epcis:EPCISDocument>

```

3.7.7 EPCIS - EUD – (3.6) Disaggregation of aggregated level UIs

3.7.7.1 Description

Message 3.6, “Disaggregation of aggregated level UIs”, is captured in an EPCIS Aggregation Event (action DELETE) with business step Unpacking, as follows.

3.7.7.2 Description of the fields

EPCIS EUD - Message to report an UID disaggregation	
Field	Values
<AggregationEvent>	<i>Nested</i>
<eventTime>	Reference: Event_Time
<eventTimeZoneOffset>	Time zone offset from UTC in effect at the time and place the event occurred.
<baseExtension>	“<eventID>” tag containing a UUID that must be generated by the sender and will be used as the recallCode for the message. Example: <pre><eventID>urn:uuid:d24aa483-94b5-4c65-ac3f-8b908ff61647</eventID></pre>
<action>	DELETE
<bizStep>	urn:epcglobal:cbv:bizstep:unpacking
<disposition>	urn:epcglobal:cbv:disp:in_progress
<readPoint>	GLN identifying the facility, <id> expressed as SGLN EPC URI, qualified by <fit:fid> extension to the readPoint, linking the SGLN of the readPoint to the Facility Identifier code, represented by the concatenated GS1 element strings AI(7040) and AI (414), where AI (414) corresponds to the first two segments of the readPoint’s SGLN EPC URI, for example: <pre><fit:fid>(7040)5f(414)1234567890128</fit:fid></pre> <pre><readPoint></pre>

EPCIS EUD - Message to report an UID disaggregation	
Field	Values
	<id>urn:epc:id:sgln:1234567.89012.0</id>
<parentID>	Parent ID, in SGTIN EPC URI or SSCC EPC URI
<fit:messageType>	3-6
<fit:eoid>	Concatenation of GS1 element strings AI(7040) and AI (417), UIM and GLN representing Economic Operator identifier code of submitting entity, <fit:eoid epc="urn:epc:id:pgl:1234567.89012" gs1ElementString="(7040)5f(417)1234567890128"/>
<fit:comment>	Optional free text comments by reporting entity, limited to 1000 characters.

3.7.7.3 Request sample

```
<?xml version="1.0"?>
<epcis:EPCISDocument xmlns:epcis="urn:epcglobal:epcis:xsd:1" schemaVersion="1.2"
  xmlns:fit="https://gs1.org/cbv/fit" xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xsi:schemaLocation="urn:epcglobal:epcis:xsd:1 EPCglobal-epcis-1_2.xsd"
  creationDate="2019-03-11T16:46:00.000Z">

  <EPCISBody>
    <EventList>

      <!-- 3.6 -->
      <!-- 3.6.1 -->
      <AggregationEvent>
        <eventTime>2018-12-07T17:17:00.000+01:00</eventTime>
        <eventTimeZoneOffset>+01:00</eventTimeZoneOffset>
        <!-- added UUID -->
        <baseExtension>
          <eventID>urn:uuid:ec59466a-66d1-4977-ae71-c39cacc67c5b</eventID>
        </baseExtension>
        <parentID>urn:epc:id:sscc:1234567.0123456789</parentID>
        <action>DELETE</action>
        <bizStep>urn:epcglobal:cbv:bizstep:unpacking</bizStep>
        <disposition>urn:epcglobal:cbv:disp:in_progress</disposition>
        <readPoint>
          <id>urn:epc:id:sgln:1234567.89012.0</id>
          <fit:fid>(7040)5v9_(414)1234567890128</fit:fid>
        </readPoint>
        <fit:messageType>3-6</fit:messageType>
        <fit:eoid epc="urn:epc:id:pgl:1234567.89012"
          gs1ElementString="(7040)5f9_(417)1234567890128"/>
        <fit:comment>3.6.1 Disaggregation of aggregated level UIs from logistics unit to
```

```

        case</fit:comment>
    </AggregationEvent>

    </EventList>
</EPCISBody>
</epcis:EPCISDocument>

```

```

<?xml version="1.0"?>
<epcis:EPCISDocument xmlns:epcis="urn:epcglobal:epcis:xsd:1" schemaVersion="1.2"
  xmlns:fit="https://gs1.org/cbv/fit" xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xsi:schemaLocation="urn:epcglobal:epcis:xsd:1 EPCglobal-epcis-1_2.xsd"
  creationDate="2019-03-11T16:46:00.000Z">

  <EPCISBody>
    <EventList>

      <!-- 3.6.2 -->
      <AggregationEvent>
        <eventTime>2018-12-07T18:18:00.000+01:00</eventTime>
        <eventTimeZoneOffset>+01:00</eventTimeZoneOffset>
        <!-- added UUID -->
        <baseExtension>
          <eventID>urn:uuid:8f63493e-bfb9-4d31-a8b5-7dfe2859e8b1</eventID>
        </baseExtension>
        <parentID>urn:epc:id:sgtin:1234567.055555.5678901234</parentID>
        <!-- child EPCs (below) no longer explicitly mentioned in complete disaggregation -->
        <childEPCs>
          <epc>urn:epc:id:sgtin:1234567.012345.9876543210</epc>
          <epc>urn:epc:id:sgtin:1234567.012345.8765432109</epc>
          <epc>urn:epc:id:sgtin:1234567.012345.7654321098</epc>
          <epc>urn:epc:id:sgtin:1234567.012345.6543210987</epc>
          <epc>urn:epc:id:sgtin:1234567.012345.5432109876</epc>
          <epc>urn:epc:id:sgtin:1234567.012345.4321098765</epc>
          <epc>urn:epc:id:sgtin:1234567.012345.3210987654</epc>
          <epc>urn:epc:id:sgtin:1234567.012345.2109876543</epc>
          <epc>urn:epc:id:sgtin:1234567.012345.1098765432</epc>
          <epc>urn:epc:id:sgtin:1234567.012345.1987654321</epc>
          <epc>urn:epc:id:sgtin:1234567.012345.1234567890</epc>
          <epc>urn:epc:id:sgtin:1234567.012345.2345678901</epc>
          <epc>urn:epc:id:sgtin:1234567.012345.3456789012</epc>
          <epc>urn:epc:id:sgtin:1234567.012345.4567890123</epc>
          <epc>urn:epc:id:sgtin:1234567.012345.5678901234</epc>
          <epc>urn:epc:id:sgtin:1234567.012345.6789012345</epc>
          <epc>urn:epc:id:sgtin:1234567.012345.7890123456</epc>
          <epc>urn:epc:id:sgtin:1234567.012345.8901234567</epc>
          <epc>urn:epc:id:sgtin:1234567.012345.9012345678</epc>
          <epc>urn:epc:id:sgtin:1234567.012345.1123456789</epc>
        </childEPCs>
        <!--
        <childEPCs/>
        <action>DELETE</action>
        <bizStep>urn:epcglobal:cbv:bizstep:unpacking</bizStep>
        <disposition>urn:epcglobal:cbv:disp:in_progress</disposition>
        <readPoint>
          <id>urn:epc:id:sgln:1234567.89012.0</id>

```

```

        <fit:fid>(7040)5f9_(414)1234567890128</fit:fid>
    </readPoint>
    <fit:messageType>3-6</fit:messageType>
    <fit:eoid epc="urn:epc:id:pgln:1234567.89012"
        gs1ElementString="(7040)5f9_(417)1234567890128"/>
    <fit:comment>3.6.2 Disaggregation of aggregated level UIs from case to
        carton</fit:comment>
    </AggregationEvent>
</EventList>
</EPCISBody>
</epcis:EPCISDocument>

```

```

<?xml version="1.0"?>
<epcis:EPCISDocument xmlns:epcis="urn:epcglobal:epcis:xsd:1" schemaVersion="1.2"
    xmlns:fit="https://gs1.org/cbv/fit" xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
    xsi:schemaLocation="urn:epcglobal:epcis:xsd:1 EPCglobal-epcis-1_2.xsd"
    creationDate="2019-03-11T16:46:00.000Z">

    <EPCISBody>
        <EventList>

            <!-- 3.6.3 -->
            <AggregationEvent>
                <eventTime>2018-12-07T19:19:00.000+01:00</eventTime>
                <eventTimeZoneOffset>+01:00</eventTimeZoneOffset>
                <!-- added UUID -->
                <baseExtension>
                    <eventID>urn:uuid:42c6d3bd-f9e5-4145-b3c3-94c7c4b1490b</eventID>
                </baseExtension>
                <parentID>urn:epc:id:sgtin:1234567.012345.9876543210</parentID>
                <!-- child EPCs (below) no longer explicitly mentioned in complete disaggregation -->
                <childEPCs>
                    <epc>urn:epc:id:upui:1234567.054321.5vY)%3C%26Jp3*j7</epc>
                    <epc>urn:epc:id:upui:1234567.054321.5vPxbrJk3th5</epc>
                    <epc>urn:epc:id:upui:1234567.054321.5vs*)%3Ek85Jp3*j7</epc>
                    <epc>urn:epc:id:upui:1234567.054321.5v8rntU1;00U%3F</epc>
                    <epc>urn:epc:id:upui:1234567.054321.5vB102bte175th</epc>
                    <epc>urn:epc:id:upui:1234567.054321.5v4CDrco52241BRd</epc>
                    <epc>urn:epc:id:upui:1234567.054321.5vittJekPgalpH</epc>
                    <epc>urn:epc:id:upui:1234567.054321.5vaC1000FyakK</epc>
                    <epc>urn:epc:id:upui:1234567.054321.5vgpuT4aHtd</epc>
                    <epc>urn:epc:id:upui:1234567.054321.5vrLbDflilwiF</epc>
                </childEPCs>
            <!--
            <childEPCs/>
            <action>DELETE</action>
            <bizStep>urn:epcglobal:cbv:bizstep:unpacking</bizStep>
            <disposition>urn:epcglobal:cbv:disp:in_progress</disposition>
            <readPoint>
                <id>urn:epc:id:sgln:1234567.89012.0</id>
                <fit:fid>(7040)5v9_(414)1234567890128</fit:fid>
            </readPoint>
            <fit:messageType>3-6</fit:messageType>
            <fit:eoid epc="urn:epc:id:pgln:1234567.89012"
                gs1ElementString="(7040)5f9_(417)1234567890128"/>
            <fit:comment>3.6.3 Disaggregation of aggregated level UIs from carton to
                units</fit:comment>

```

```

</AggregationEvent>

</EventList>
</EPCISBody>
</epcis:EPCISDocument>

```

3.7.8 EPCIS - EVR – (3.7) Report the delivery carried out with a vending van to retail outlet

3.7.8.1 Description

Event sent when UIs have been distributed via a van delivery.

3.7.8.2 Description of the fields

EPCIS EVR - Report the delivery carried out with a vending van to retail outlet	
Field	Values
<ObjectEvent>	<i>Nested</i>
<eventTime>	Reference: Event_Time
<eventTimeZoneOffset>	Time zone offset from UTC in effect at the time and place the event occurred.
<baseExtension>	"<eventID>" tag containing a UUID that must be generated by the sender and will be used as the recallCode for the message. Example: <pre><eventID>urn:uuid:d24aa483-94b5-4c65-ac3f-8b908ff61647</eventID></pre>
<action>	OBSERVE
<bizStep>	urn:epcglobal:cbv:bizstep:receiving
<disposition>	urn:epcglobal:cbv:disp:in_progress
<readPoint>	GLN identifying the facility, <id> expressed as SGLN EPC URI, qualified by <fit:fid> extension to the readPoint, linking the SGLN of the readPoint to the Facility Identifier code, represented by the concatenated GS1 element strings AI(7040) and AI (414), where AI (414) corresponds to the first two segments of the readPoint's SGLN EPC URI, for example: <pre><fit:fid>(7040)5f(414)1234567890128</fit:fid></pre> <pre><readPoint></pre>

EPCIS EVR - Report the delivery carried out with a vending van to retail outlet	
Field	Values
	<id>urn:epc:id:sgln:1234567.89012.0</id>
<epcList>	EPCs, in SGTIN/SSCC EPC UI or UPUI EPC URI Example: <pre><epc>urn:epc:id:upui:1234567.054321.5vY)%3C%26Jp3*j7</epc> <epc>urn:epc:id:sgtin:1234567.012345.9876543210</epc> <epc>urn:epc:id:sscc:1234567.0123456789</epc></pre>
<fit:messageType>	3-7
<fit:eoid>	Concatenation of GS1 element strings AI(7040) and AI (417), UIM and GLN representing Economic Operator identifier code of submitting entity, <pre><fit:eoid epc="urn:epc:id:pgln:1234567.89012" gs1ElementString="(7040)5f(417)1234567890128"/></pre>
<fit:uiType>	Reference: UI_Type
<fit:productReturn>	Reference: Product_return Note that you have to use "false" instead of "0" and "true" instead of "1"
<fit:comment>	Optional free text comments by reporting entity, limited to 1000 characters.

3.7.8.3 Request sample

```
<?xml version="1.0"?>
<epcis:EPCISDocument xmlns:epcis="urn:epcglobal:epcis:xsd:1" schemaVersion="1.2"
  xmlns:fit="https://gs1.org/cbv/fit" xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xsi:schemaLocation="urn:epcglobal:epcis:xsd:1 EPCglobal-epcis-1_2.xsd"
  creationDate="2019-03-11T16:46:00.000Z">

  <EPCISBody>
    <EventList>

    <!-- 3.7 -->
```

```

<ObjectEvent>
  <eventTime>2018-12-07T20:20:00.000+01:00</eventTime>
  <eventTimeZoneOffset>+01:00</eventTimeZoneOffset>
  <!-- added UUID -->
  <baseExtension>
    <eventID>urn:uuid:7acb63af-49ea-42d0-893c-ae6a6c9a657c</eventID>
  </baseExtension>
  <epcList>
    <epc>urn:epc:id:sscc:1234567.0123456789</epc>
  </epcList>
  <action>OBSERVE</action>
  <bizStep>urn:epcglobal:cbv:bizstep:receiving</bizStep>
  <disposition>urn:epcglobal:cbv:disp:in_progress</disposition>
  <readPoint>
    <id>urn:epc:id:sgln:1234567.89012.0</id>
    <fit:fid>(7040)5v9_(414)1234567543215</fit:fid>
  </readPoint>
  <fit:messageType>3-7</fit:messageType>
  <fit:uiType>2</fit:uiType>
  <fit:eoid epc="urn:epc:id:pgln:1234567.89012"
    gs1ElementString="(7040)5f9_(417)1234567890128"/>
  <fit:productReturn>false</fit:productReturn>
  <fit:comment>3.7 Report of delivery carried out with a vending van to a retail
    outlet</fit:comment>
</ObjectEvent>
</EventList>
</EPCISBody>
</epcis:EPCISDocument>

```

3.8 Reporting transactional events (trade information)

3.8.1 EIV – (4.1) Issuing of the invoice

3.8.1.1 Description.

Added invoice details to a UI.

3.8.1.2 Description of the fields

Invoice reporting					
Field	Description	Data Type	Cardinality	Priority	Values
BasicInfo_Req	Block of basic information elements	Component << Basic Information Request >>	S	M	Message_Type = EIV
EO_ID	Economic operator identifier code of the submitting entity	EOID	S	M	
Event_Time	Time of event occurrence	Time(s)	S	M	
Message_Time_long	Message sending Time	Time(L)	S	M	
Invoice_Type1	Type of the invoice	Integer	S	M	See InvoiceType
Invoice_Type2	Description of the other type of the invoice	Text(5000)	S	M, if Invoice_Type1 = 3	
Invoice_Number	Number of the invoice	Text(5000)	S	M	
Invoice_Date	Date of the invoice	Date	S	M	
Invoice_Seller	Identity of the seller	EOID	S	M	
Invoice_Buyer1	Identification if the buyer is located in the EU	Boolean	S	M	0 – No 1 – Yes
Invoice_Buyer2	Identity of the buyer	EOID	S	M, if Invoice_Buyer1 = 1	
Buyer_Name	Buyer's registered legal name	Text(5000)	S	M, if Invoice_Buyer1 = 0	
Buyer_Address	Buyer's address	Text(5000)	S	M, if Invoice_Buyer1 = 0	
Buyer_Address_Name	Buyer's address - Name part of the Address	Text(5000)	S	O	
Buyer_Address_StreetOne	Buyer's address - Street part of the Address	Text(5000)	S	M, if Invoice_Buyer1 = 0	
Buyer_Address_StreetTwo	Buyer's address - Second Element of the Street part of the Address	Text(5000)	S	O	
Buyer_Address_City	Buyer's address - City	Text(5000)	S	M, if Invoice_Buyer1 = 0	

Invoice reporting					
Field	Description	Data Type	Cardinality	Priority	Values
Buyer_Address_PostCode	Buyer's address - PostalCode information	Text(5000)	S	O	
Buyer_CountryReg	Buyer's country of registration	Country	S	M, if Invoice_Buyer1 = 0	
Buyer_TAX_N	Buyer's tax registration number	Text(5000)	S	M, if Invoice_Buyer1 = 0	
First_Seller_EU	Identification if the invoice is issued by the first seller in the EU, i.e. the EU manufacturer or the importer, and the product is destined for the EU market	Boolean	S	M	0 – No 1 – Yes
Product_Items_1	List of TPIDs corresponding to the product items listed on the invoice	TPID	M	M, if First_Seller_EU = 1	
Product_Items_2	List of product numbers corresponding to the product items listed on the invoice (in the same order as product_Items_1)	PN	M	M, if First_Seller_EU = 1	
Product_Price	Net unit packet price per each pair of TPID and product number (in the same order as product_Items_1)	Decimal	M	M, if First_Seller_EU = 1	
Invoice_Net	Total net amount of the invoice	Decimal	S	M	
Invoice_Currency	Currency of the invoice	Currency	S	M	
UI_Type	Identification of UI types covered by the invoice (recorded at the highest level of available aggregation)	Integer	S	M	1 – only unit packet level UIs 2 – only aggregated level UIs 3 – both unit packet and aggregated level UIs
upUIs	List of unit packet level UIs covered by the invoice	upUI(L)	M	M, if UI_Type = 1 or 3	
aUIs	List of aggregated level UIs covered by the invoice	aUI	M	M, if UI_Type = 2 or 3	
Invoice_comment	Comments by the reporting entity	Text(5000)	S	O	

3.8.1.3 Response:

Invoice reporting– response					
Field	Description	Data Type	Cardinality	Priority	Values
BasicInfo_Resp	Block of basic information elements	Component << Basic Information Response >>	S	M	Message_Type = EIV

3.8.1.4 Request sample

```
{
  "EO_ID": "QCUKR+1AB020054",
  "Event_Time": "19032014",
  "Message_Time_Long": "2019-03-20T14:16:45Z",
  "Invoice_Type1": 1,
  "Invoice_Type2": "other type",
  "Invoice_Number": "INV000001",
  "Invoice_Date": "2018-08-23T07:32:20.7878086+00:00",
  "Invoice_Seller": "SellerId",
  "Invoice_Buyer1": false,
  "Invoice_Buyer2": null,
  "Buyer_Name": "Buyer1",
  "Buyer_Address": "BuyerAddress",
  "Buyer_CountryReg": "LU",
  "Buyer_TAX_N": "TAX0001",
  "First_Seller_EU": 1,
  "Product_Items_1": [ "11111-1111111", "11111-1111112" ],
  "Product_Items_2": [ "01234567891234", "01234567891235" ],
  "Product_Price": [ "16.99", "19.99" ],
  "Invoice_Net": 10099.99,
  "Invoice_Currency": "EUR",
  "UI_Type": 1,
  "upUIs": [ "DANXXXXXXXXXXXX1PR012345678919030110",
    "DANXXXXXXXXXXXX1PR012345678919030110" ],
  "aUIs": [ "DANXXXXXXXXXXXX10FA00000119030110" ],
  "Invoice_comment": "Comments",
  "Message_Type": "EIV",
  "Code": "873345b2-882f-4064-91f0-90669b46c30a"
}
```

3.8.1.5 Successful response sample

HTTP Status 202

```
{
  "Code": "873345b2-882f-4064-91f0-90669b46c30a",
  "Message_Type": "EIV",
  "Error": false,
  "Errors": null,
  "Checksum": "G6HF5H"
}
```

3.8.1.6 Error response sample

Processing errors

HTTP status	Error Code	Error Description
<< Common response code >>		

3.8.2 EPO – (4.2) Issuing of the order number

3.8.2.1 Description

Adds a purchase order event to a UI.

3.8.2.2 Description of the fields

Purchase order event					
Field	Description	Data Type	Cardinality	Priority	Values
BasicInfo_Req	Block of basic information elements	Component << Basic Information Request >>	S	M	Message_Type = EPO
EO_ID	Economic operator identifier code of the submitting entity	EOID	S	M	
Event_Time	Time of event occurrence	Time(s)	S	M	
Message_Time_Long	Message sending Time	Time(L)	S	M	
Order_Number	Number of the purchase order	Text	S	M	
Order_Date	Date of the purchase order	Date	S	M	
UI_Type	Identification of UI types covered by the purchase order (recorded at the highest level of available aggregation)	Integer	S	M	1 – only unit packet level UIs 2 – only aggregated level UIs 3 – both unit packet and aggregated level UIs
upUIs	List of unit packet level UIs covered by the purchase order	upUI(L)	M	M, if UI_Type = 1 or 3	
aUIs	List of aggregated level UIs covered by the purchase order	aUI	M	M, if UI_Type = 2 or 3	
Order_comment	Description of the reason for delayed recording of the purchase order	Text(5000)	S	O	

3.8.2.3 Response:

Purchase order – response					
Field	Description	Data Type	Cardinality	Priority	Values
BasicInfo_Resp	Block of basic information elements	Component << Basic Information Response >>	S	M	Message_Type = EPO

3.8.2.4 Request sample

```
{
  "EO_ID": "QCUKR+1AB020054",
  "Event_Time": "19032014",
  "Message_Time_Long": "2019-03-20T14:16:45Z",
  "Order_Number": "1234",
  "Order_Date": "2018-08-23T07:32:20.7878086+00:00",
  "UI_Type": 1,
  "upUIs": [ "DANXXXXXXXXXXXXX1PR012345678919030110",
    "DANXXXXXXXXXXXXX1PR012345678919030110" ],
  "aUIs": [ "DANXXXXXXXXXXXXX10FA00000119030110" ],
}
```

```
{
  "Order_comment": "Comments",
  "Message_Type": "EPO",
  "Code": "873345b2-882f-4064-91f0-90669b46c30a"
}
```

3.8.2.5 Successful response sample

HTTP Status 202

```
{
  "Code": "873345b2-882f-4064-91f0-90669b46c30a",
  "Message_Type": "EPO",
  "Error": false,
  "Errors": null,
  "Checksum": "G6HF5H"
}
```

3.8.2.6 Error response sample

Processing errors

HTTP status	Error Code	Error Description
<< Common response code >>		

3.8.3 EPR – (4.3) Receipt of the payment

3.8.3.1 Description

Adds a payment record event to a UI.

3.8.3.2 Description of the fields

Payment record event					
Field	Description	Data Type	Cardinality	Priority	Values
BasicInfo_Req	Block of basic information elements	Component << Basic Information Request >>	S	M	Message_Type = EPR
EO_ID	Economic operator identifier code of the submitting entity	EOID	S	M	
Event_Time	Time of event occurrence	Time(s)	S	M	
Message_Time_Logging	Message sending Time	Time(L)	S	M	
Payment_Date	Date of the payment receipt	Date	S	M	
Payment_Type	Type of payment	Integer	S	M	See PaymentType
Payment_Amount	Amount of the payment	Decimal	S	M	
Payment_Currency	Currency of the payment	Currency	S	M	
Payment_Payer1	Identification if the payer is located in the EU	Boolean	S	M	0 – No 1 – Yes
Payment_Payer2	Identity of the payer	EOID	S	M, if Payment_Payer1 = 1	
Payer_Name	Payer's registered legal name	Text(5000)	S	M, if Payment_Payer1 = 0	
Payer_Address	Buyer's address	Text(5000)	S	M, if Payment_Payer1 = 0	
Payer_Address_Name	Buyer's address - Name part of the Address	Text(5000)	S	O	
Payer_Address_StreetOne	Buyer's address - Street part of the Address	Text(5000)	S	M, if Payment_Payer1 = 0	
Payer_Address_StreetTwo	Payer's address - Second Element of the Street part of the Address	Text(5000)	S	O	
Payer_Address_City	Payer's address - City	Text(5000)	S	M, if Payment_Payer1 = 0	
Payer_Address_PostCode	Payer's address - PostalCode information	Text(5000)	S	O	
Payer_CountryRegistration	Payer's country of registration	Country	S	M, if Payment_Payer1 = 0	
Payer_TAX_N	Payer's tax registration number	Text(5000)	S	M, if Payment_Payer1 = 0	
Payment_Recipient	Identity of the recipient	EIOD	S	M	
Payment_Invoice	Indication if the payment corresponds to the existing invoice	Boolean	S	M	0 – No 1 – Yes

Payment record event					
Field	Description	Data Type	Cardinality	Priority	Values
Invoice_Paid	Number of the invoice paid with the payment	Text(5000)	S	M, if Payment_Invoice = 1	
UI_Type	Identification of UI types covered by the payment (recorded at the highest level of available aggregation)	Integer	S	M, if Payment_Invoice = 0	1 – only unit packet level UIs 2 – only aggregated level UIs 3 – both unit packet and aggregated level UIs
upUIs	List of unit packet level UIs covered by the payment	upUI(L)	M	M, if AND Payment_Invoice = 0 UI_Type = 1 or 3	
aUIs	List of aggregated level UIs covered by the payment	aUI	M	M, if AND Payment_Invoice = 0 UI_Type = 2 or 3	
Payment_comment	Comments by the reporting entity	Text(5000)	S	0	

3.8.3.3 Response:

Payment record – response					
Field	Description	Data Type	Cardinality	Priority	Values
BasicInfo_Resp	Block of basic information elements	Component << Basic Information Response >>	S	M	Message_Type = EPR

3.8.3.4 Request sample

```
{
  "EO_ID": "QCUKR+1AB020054",
  "Event_Time": "19032014",
  "Message_Time_Long": "2019-03-20T14:16:45Z",
  "Payment_Date": "2018-08-23T07:32:20.7878086+00:00",
  "Payment_Type": 1,
  "InvoiceType": 1,
  "UI_Type": 1,
  "Payment_Amount": 1.99,
  "Payment_Currency": "EUR",
  "Payment_Payer1": true,
  "Payment_Payer2": "PayerId",
  "Payer_Name": "PayerNmae",
  "Payer_Address": "Address",
  "Payer_CountryReg": "UK",
  "Payer_TAX_N": "TaxId",
  "Payment_Recipient": "PaymentRecipient",
  "Payment_Invoice": 1,
  "Invoice_Paid": "test",
  "upUIs": [ "DANXXXXXXXXXXXXX1PR012345678919030110",
    "DANXXXXXXXXXXXXX2PR012345678919030110" ],
  "aUIs": [ "DANXXXXXXXXXXXXX10FA00000119030110",
    "DANXXXXXXXXXXXXX20FA00000119030110" ],
}
```

```
"Payment_comment": "Comments",  
"Message_Type": "EPR",  
"Code": "873345b2-882f-4064-91f0-90669b46c30a"  
}
```

3.8.3.5 *Successful response sample*

HTTP Status 202

```
{  
  "Code": "873345b2-882f-4064-91f0-90669b46c30a",  
  "Message_Type": "EPR",  
  "Error": false,  
  "Errors": null,  
  "Checksum": "G6HF5H"  
}
```

3.8.3.6 Error response sample

Processing errors

HTTP status		
<< Common response code >>		

3.9 EDI - Reporting transactional events (trade information)

3.9.1 EDI - EIV – (4.1) Issuing of the invoice

3.9.1.1 Description.

Added invoice details to a UI.

Field	Comments	Data Type	Cardinality	Priority	Values	XML
Message_Type	Identification of message type	Text	S	M	4-1	<invoiceType>INVOICE</invoiceType>
EO_ID	Economic operator identifier code of the submitting entity	EOID	S	M		<contentOwner> <gln>4098765000010</gln> <additionalPartyIdentification additionalPartyIdentificationTypeCode="EOID">5v1_4098765000010</additionalPartyIdentification> </contentOwner>
Event_Time	Time of event occurrence	Time(s)	S	M		<creationDateTime>2019-04-11T08:15:00.000-05:00</creationDateTime>
Invoice_Type1	Type of the invoice	Integer	S	M	1 – Original 2 – Correction 3 – Other	Example Invoice A (Original): <documentStatusCode>ORIGINAL</documentStatusCode> <invoiceType>INVOICE</invoiceType> Example Invoice B (Other): <documentStatusCode>ORIGINAL</documentStatusCode>

						<invoiceType>OTHER</invoiceType>
Invoice_Type2	Description of the other type of the invoice	Text(5000)	S	M, if Invoice_Type1 = 3		Example Invoice B: (Other): <documentStatusCode>ORIGINAL</documentStatusCode> <invoiceType>OTHER</invoiceType> <invoiceTypeDescription languageCode="en">Description of another type of invoice</invoiceTypeDescription>
Invoice_Number	Number of the invoice	Text(5000)	S	M		<entityIdentification>IN19-548</entityIdentification>
Invoice_Date	Date of the invoice	Date	S	M		<creationDateTime>2019-04-11T08:15:00.000-05:00</creationDateTime>
Invoice_Seller	Identity of the seller	EOID	S	M		<additionalPartyIdentification additionalPartyIdentificationTypeCode="EOID">5v1_4098765000010</additionalPartyIdentification>
Invoice_Buyer1	Identification if the buyer is located in the EU	Boolean	S	M	0 – No 1 – Yes	<isBuyerBasedInEu>true</isBuyerBasedInEu>
Invoice_Buyer2	Identity of the buyer	EOID	S	M, if Invoice_Buyer1 = 1		<additionalPartyIdentification additionalPartyIdentificationTypeCode="EOID">5v1_5412345000013</additionalPartyIdentification>
Buyer_Name	Buyer's registered legal name	Text(5000)	S	M, if Invoice_Buyer1 = 0		<organisationDetails> <organisationName>ACME Stores</organisationName> </organisationDetails>
Buyer_Address	Buyer's address – street name, house number, postal code, city	Text(5000)	S	M, if Invoice_Buyer1 = 0		<city>Bruxelles</city> <postalCode>1050</postalCode> <streetAddressOne>Avenue Louise 326</streetAddressOne>

						<streetAddressTwo>Ixelles</streetAddressTwo>
Buyer_Country Reg	Buyer's country of registration	Countr y	S	M, if Invoice_Bu yer1 = 0		<countryCode>BE</countr yCode>
Buyer_TAX_N	Buyer's tax registration number	Text(50 00)	S	M, if Invoice_Bu yer1 = 0		<dutyFeeTaxRegistrationID > SE556667677001</dutyFe eTaxRegistrationID>
First_Seller_EU	Identification if the invoice is issued by the first seller in the EU, i.e. the EU manufacturer or the importer, and the product is destined for the EU market	Boolea n	S	M	0 – No 1 – Yes	<isFirstSellerBasedInEu>fal se</isFirstSellerBasedInEu >
Product_Items_ 1	List of TPIDs corresponding to the product items listed on the invoice	TPID	M	M, if First_Seller _EU = 1		<additionalTradelItemIdent ification additionalTradelItemIdent ificationTypeCode="TPID"> 02565-16-00555</ additionalTradelItemIdent ification <additionalTradelItemIdent ification <additionalTradelItemIdent ification additionalTradelItemIdent ificationTypeCode="TPID"> 03456-16-00636"</ additionalTradelItemIdent ification
Product_Items_ 2	List of product numbers corresponding to the product items listed on the invoice (in the same order as Product_Items_1)	PN	M	M, if First_Seller _EU = 1		<gtin>01234567543215</ gtin> <gtin>01234567890128</ gtin>
Product_Price	Net unit packet price per each pair of TPID and product number (in the same order as Product_Items_1)	Decima l	M	M, if First_Seller _EU = 1		<itemPriceInclusiveAllowa ncesCharges currencyCode="EUR">10< /itemPriceInclusiveAllowa ncesCharges> <itemPriceInclusiveAllowa ncesCharges currencyCode="EUR">20<

						/itemPriceInclusiveAllowancesCharges>
Invoice_Net	Total net amount of the invoice	Decimal	S	M		<totalTaxBasisAmount currencyCode="EUR">60</totalTaxBasisAmount>
Invoice_Currency	Currency of the invoice	Currency	S	M		<invoiceCurrencyCode>EUR</invoiceCurrencyCode>
UI_Type	Identification of UI types covered by the invoice (recorded at the highest level of available aggregation)	Integer	S	M	1 – only unit packet level UIs 2 – only aggregated level UIs 3 – both unit packet and aggregated level UIs	<euUniqueIDTypeCode>3</euUniqueIDTypeCode>
upUIs	List of unit packet level UIs covered by the invoice	upUI(L)	M	M, if UI_Type = 1 or 3		<unitPacketLevelUniqueIdentifier>5vY)<&Jp3*j701234567543215</unitPacketLevelUniqueIdentifier> <unitPacketLevelUniqueIdentifier>5vPxbrJk3th501234567890128</unitPacketLevelUniqueIdentifier>
aUIs	List of aggregated level UIs covered by the invoice	aUI	M	M, if UI_Type = 2 or 3		<aggregatedLevelUniqueIdentifier>106141412345678908</aggregatedLevelUniqueIdentifier>
Invoice_comment	Comments by the reporting entity	Text(5000)	S	O		<note languageCode="en">A comment about this invoice</note>

3.9.1.2 EDI invoiceMessage Example

```
<?xml version="1.0" encoding="UTF-8"?>
<invoice:invoiceMessage xmlns:invoice="urn:gs1:ecom:invoice:xsd:3" xmlns:eanucc="urn:eanucc:2"
xmlns:sh="http://www.unece.org/cefact/namespaces/StandardBusinessDocumentHeader"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance" xsi:schemaLocation="urn:gs1:ecom:invoice:xsd:3
../Schemas/gs1/ecom/Invoice.xsd">
  <sh:StandardBusinessDocumentHeader>
    <sh:HeaderVersion>1.0</sh:HeaderVersion>
    <sh:Sender>
      <sh:Identifier Authority="GS1">4098765000010</sh:Identifier/>
      <sh:ContactInformation>
        <sh:Contact>John Doe</sh:Contact>
        <sh:EmailAddress>John_Doe@purchasing.XYZretailer.com</sh:EmailAddress>
        <sh:FaxNumber>+1-212-555-1213</sh:FaxNumber>
        <sh:TelephoneNumber>+1-212-555-2122</sh:TelephoneNumber>
        <sh:ContactTypeIdentifier>Buyer</sh:ContactTypeIdentifier>
      </sh:ContactInformation>
    </sh:Sender>
```

```

    <sh:Receiver>
      <sh:Identifier Authority="GS1">5412345000013</ sh: Identifier>
      <sh:ContactInformation>
        <sh:Contact>Mary Smith</sh:Contact>
        <sh:EmailAddress>Mary_Smith@widgets.com</sh:EmailAddress>
        <sh:FaxNumber>+1-312-555-1214</sh:FaxNumber>
        <sh:TelephoneNumber>+1-312-555-2125</sh:TelephoneNumber>
        <sh:ContactTypeIdentifier>Seller</sh:ContactTypeIdentifier>
      </sh:ContactInformation>
    </sh:Receiver>
    <sh:DocumentIdentification>
      <sh:Standard>GS1</sh:Standard>
      <sh:TypeVersion>3.4</sh:TypeVersion>
      <sh:InstanceIdentifier>100002</sh:InstanceIdentifier>
      <sh:Type/>
      <sh:MultipleType>>false</sh:MultipleType>
      <sh:CreationDateAndTime>2006-01-10T12:00:01.000-05:00</sh:CreationDateAndTime>
    </sh:DocumentIdentification>
  </sh:StandardBusinessDocumentHeader>

```

<invoice>

```
<creationDateTime>2019-04-11T08:15:00.000-05:00</creationDateTime>
```

```
<documentStatusCode>ORIGINAL</documentStatusCode>
```

```
<invoiceIdentification>
```

```
<entityIdentification>IN19-548</entityIdentification>
```

```
<contentOwner>
```

```
<gln>4098765000010</gln>
```

```
<additionalPartyIdentification
```

```
additionalPartyIdentificationTypeCode="EOID">5v1_4098765000010</additionalPartyIdentification>
```

```
</contentOwner>
```

```
</invoiceIdentification>
```

```
<digitalSignature>
```

```
<Signature xmlns="http://www.w3.org/2000/09/xmldsig#">
```

```
xsi:schemaLocation="http://www.w3.org/2000/09/xmldsig# ../Schemas/xmldsig/xmldsig-core-schema.xsd">
```

```
<SignedInfo>
```

```
<CanonicalizationMethod Algorithm="http://www.w3.org/TR/2001/REC-xml-c14n-20010315"/>
```

```
<SignatureMethod Algorithm="http://www.w3.org/2000/09/xmldsig#dsa-sha1"/>
```

```
<Reference URI="http://example.org">
```

```
<Transforms>
```

```
<Transform Algorithm="http://www.w3.org/2000/09/xmldsig#enveloped-signature"/>
```

```
</Transforms>
```

```
<DigestMethod Algorithm="http://www.w3.org/2000/09/xmldsig#sha1"/>
```

```
<DigestValue>K8M/IPbKnuMDsOOUzuj75lQtzQl=</DigestValue>
```

```
</Reference>
```

```
</SignedInfo>
```

```
<SignatureValue>DpEylhQoiUKBoKWmYfajXO7LZxiDYgVtUtCNYtgwZgoChzorA2nhkQ==</SignatureValue>
```

```
<KeyInfo>
```

```
<KeyValue>
```

```
<DSAKeyValue>
```

```
<P>
```

```
rFto8uPQM6y34FLPmDh40BLJ1rVrC8VeRquuhPZ6jYNfkQuwxnu/wCvIAMhukPBLFET8bJf/b2ef+oqxZaj
Eb+88zlZoyG8g/wMfDBHTxz+CnowLahnCCTYBp5kt7G8qUobJuvjylwj1st7V9Lsu03iXMXtbiriUjFa5gURa
sN8=
```

```
</P>
```

```
<Q>
```

```
kEjAFpCe4lcUOdwpfzf+tBaUds=
```

```
</Q>
```

```
<G>
```

```
oe14R2OtyKx+s+60O5BRNMOYplg2TU/f15N3bsDErKOWtKXENK9FS7dWStreDxo2SSgOonqAd4FuJ/4u
va7GgNL4ULIqY7E+mW5iwJ7n/WTElh98mEocsLXkNh24HcH4BZfSCTruuzmCjydV1KSqX/Eux04HfCWY
mdxN3SQ/qqw=
```

```
</G>
```

```
<Y>
```

```

pA5NnZvcd574WRXuOA7ZfC/7Lqt4cB0MRLWtHubtJoVOao9ib5ry4rTk0r6ddnOvAIGKktutzK3ymvKleS3
DOrwZQgJ+/BDWDW8kO9R66o6rdjiSobBi/0c2V1+dkqOgjFmKz395mvCOZGhC7fqAVhHat2EjGPMfgSZ
yABa7+1k=
  </Y>
</DSAKeyValue>
  </KeyValue>
  <X509Data>
<X509Certificate>
  MIIDbTCCAyygAwIBAgIGAOCdrKxkMAKGBYqGSM44BAMwezELMAkGA1UEBhMCSUUxXzZAN
  BgNVBAGTBkR1YmxpbjElMCMGA1UEChMcQmFsdGltb3JlIFRIY2hub2xvZ2llcywgTHRkLjJERMA
  8GA1UECmMIWC9TZWN1cmUxITAFBgNVBAMTGFgVU2VjdXJlIDFwMjYmI0ERTQSBQTAe
  Fw0wMDA3MjcNzEzMzNaFw0wMTA3MjcNzEzMjZaMHwxZzAJBgNVBAYTAkFtMQ8wDQY
  DVQQIEwZEdWJsaW4xJTajBgNVBAoTHEJhbHRpbW9yZSB1ZWNobm9sb2dpZXMsIEx0ZC4xE
  TAPBgNVBAsTCFgVU2VjdXJlMSIwIAYDVQQDEXIYLV1NIY3VyZSAxMDI0LWJpdCBEU0EgY3JOMII
  BuDCCASwGBYqGSM44BAEwggEfAoGBAKxbaPLjODost+BSz5g4eNASyda1awvFXkarroT2eo2
  DRZELsMZ7v8AryADlbpDwSxRE/GyX/29nn/qKsWWoxG/vPM5WaMhvip8DHwwR08c/gp6M
  C2oZwgk2AaeZLexvKlKGybr48pci9bLe1fS7LtN4lzf7W4q4lIxWuYFEWrdFAhUAkeJAfPce4lcU
  Odwphpzf+tBaUdsCgYEAoe14R2OtyKx+s+6005BRNMOYplg2TU/f15N3bsDErKOWtKXENK9F
  S7dWStreDxo2SSgOonqAd4FuJ/4uua7GgNL4ULlqY7E+mW5iwJ7n/WTElh98mEocsLXNhh24
  HcH4BZfScTruuzmCyjdV1KSqX/Eux04HfCWYmdxN3SQ/qqwDgYUAAoGBAKQOTZ2b3Hee+Fk
  V7jgO2Xwv+y6reHAdDES1rR7m7SaFTmqPYm+a8uK05NK+nXZrwcBipLbrcyt8prypXktwzq8
  GUICfvwQ1g1vJDvUeuqOq3Y4kqGwYv9HNldfnZKjoxZis9/eZrwjmRoQu36gFYR2rdhlxjzH4E
  mcgAWu/tZozswOTAPBgNVHQ8BAf8EBQMDAIAAMBEGA1UdDgQKBAiA4IML4dndEDATBgN
  VHSMEDDAKgAiHoMnYnDxZUDAJBgqhkJOOAQDAzAAMCOCFQCEXa1E2ueJ8WMX5nP1ICCB
  WhxC2wIUGUCBb6M6Oj3NQAjbnZsdY63rKa0=
  </X509Certificate>
  </X509Data>
</KeyInfo>
</Signature>
</digitalSignature>
<invoiceType>INVOICE</invoiceType>
<invoiceCurrencyCode>EUR</invoiceCurrencyCode>
<note languageCode="en">A comment about this invoice</note>
<isBuyerBasedInEu>true</isBuyerBasedInEu>
<isFirstSellerBasedInEu>>false</isFirstSellerBasedInEu>
<buyer>
  <gln>5412345000013</gln>
  <additionalPartyIdentification
    additionalPartyIdentificationTypeCode="EOID">5v1_5412345000013</additionalPartyIdentification>
  <address>
    <city>Bruxelles</city>
    <countryCode>BE</countryCode>
    <postalCode>1050</postalCode>
    <streetAddressOne>Avenue Louise 326</streetAddressOne>
    <streetAddressTwo>Ixelles</streetAddressTwo>
  </address>
  <dutyFeeTaxRegistration>
    <dutyFeeTaxRegistrationID>SE556667677001</dutyFeeTaxRegistrationID>
    <dutyFeeTaxTypeCode>VAT</dutyFeeTaxTypeCode>
  </dutyFeeTaxRegistration>
  <organisationDetails>
    <organisationName>ACME Stores</organisationName>
  </organisationDetails>
</buyer>
<seller>
  <gln>4098765000010</gln>
  <additionalPartyIdentification
    additionalPartyIdentificationTypeCode="EOID">5v1_4098765000010</additionalPartyIdentification>
</seller>
<invoiceTotals>
  <totalInvoiceAmount currencyCode="EUR">71.4</totalInvoiceAmount>

```



```

<totalTaxBasisAmount currencyCode="EUR">60</totalTaxBasisAmount>
<totalLineAmountInclusiveAllowancesCharges
currencyCode="EUR">60</totalLineAmountInclusiveAllowancesCharges>
<totalTaxAmount currencyCode="EUR">11.4</totalTaxAmount>
<taxSubtotal>
  <dutyFeeTaxAmount currencyCode="EUR">11.4</dutyFeeTaxAmount>
  <dutyFeeTaxBasisAmount currencyCode="EUR">60</dutyFeeTaxBasisAmount>
  <dutyFeeTaxCategoryCode>STANDARD_RATE</dutyFeeTaxCategoryCode>
  <dutyFeeTaxPercentage>19.00</dutyFeeTaxPercentage>
  <dutyFeeTaxTypeCode>VALUE_ADDED_TAX</dutyFeeTaxTypeCode>
</taxSubtotal>
</invoiceTotals>
<invoiceLineItem>
  <lineItemNumber>1</lineItemNumber>
  <invoicedQuantity>2</invoicedQuantity>
  <amountInclusiveAllowancesCharges currencyCode="EUR">20</amountInclusiveAllowancesCharges>
  <itemPriceInclusiveAllowancesCharges currencyCode="EUR">10</itemPriceInclusiveAllowancesCharges>
  <transferOfOwnershipDate>2019-04-11</transferOfOwnershipDate>
  <transactionalTradeItem>
    <gtin>01234567543215</gtin>
    <additionalTradeItemIdentification additionalTradeItemIdentificationTypeCode="TPID"> 02565-16-00555</additionalTradeItemIdentification>
  </transactionalTradeItem>
  <invoiceLineTaxInformation>
    <dutyFeeTaxAmount currencyCode="EUR">3.8</dutyFeeTaxAmount>
    <dutyFeeTaxBasisAmount currencyCode="EUR">20</dutyFeeTaxBasisAmount>
    <dutyFeeTaxCategoryCode>STANDARD_RATE</dutyFeeTaxCategoryCode>
    <dutyFeeTaxPercentage>19.00</dutyFeeTaxPercentage>
    <dutyFeeTaxTypeCode>VALUE_ADDED_TAX</dutyFeeTaxTypeCode>
  </invoiceLineTaxInformation>
  <invoiceLineItemInformationAfterTaxes>
    <amountInclusiveAllowancesCharges
      currencyCode="EUR">23.8</amountInclusiveAllowancesCharges>
  </invoiceLineItemInformationAfterTaxes>
  <purchaseOrder>
    <entityIdentification>PO3352</entityIdentification>
    <creationDateTime>2011-03-11T11:00:00.000-05:00</creationDateTime>
    <lineItemNumber>1</lineItemNumber>
  </purchaseOrder>
  <euUniqueID>
    <unitPacketLevelUniqueIdentifier>5vY<&U7ghj701234567543215</unitPacketLevelUniqueIdentifier>
    <unitPacketLevelUniqueIdentifier>5vY<abU7ghj701234567543215</unitPacketLevelUniqueIdentifier>
    <aggregatedLevelUniqueIdentifier>106141412345678908</aggregatedLevelUniqueIdentifier>
  </euUniqueID>
</invoiceLineItem>
<invoiceLineItem>
  <lineItemNumber>2</lineItemNumber>
  <invoicedQuantity>2</invoicedQuantity>
  <amountInclusiveAllowancesCharges currencyCode="EUR">40</amountInclusiveAllowancesCharges>
  <itemPriceInclusiveAllowancesCharges currencyCode="EUR">20</itemPriceInclusiveAllowancesCharges>
  <transferOfOwnershipDate>2019-04-11</transferOfOwnershipDate>
  <transactionalTradeItem>
    <gtin>01234567890128</gtin>
    <additionalTradeItemIdentification additionalTradeItemIdentificationTypeCode="TPID">03456-16-00636</additionalTradeItemIdentification>
  </transactionalTradeItem>
  <invoiceLineTaxInformation>
    <dutyFeeTaxAmount currencyCode="EUR">7.6</dutyFeeTaxAmount>
    <dutyFeeTaxBasisAmount currencyCode="EUR">40</dutyFeeTaxBasisAmount>
    <dutyFeeTaxCategoryCode>STANDARD_RATE</dutyFeeTaxCategoryCode>

```

```

        <dutyFeeTaxPercentage>19.00</dutyFeeTaxPercentage>
        <dutyFeeTaxTypeCode>VALUE_ADDED_TAX</dutyFeeTaxTypeCode>
    </invoiceLineTaxInformation>
    <invoiceLineItemInformationAfterTaxes>
        <amountInclusiveAllowancesCharges
            currencyCode="EUR">47.6</amountInclusiveAllowancesCharges>
    </invoiceLineItemInformationAfterTaxes>
    <purchaseOrder>
        <entityIdentification>PO3352</entityIdentification>
        <creationDateTime>2011-03-11T11:00:00.000-05:00</creationDateTime>
        <lineItemNumber>2</lineItemNumber>
    </purchaseOrder>
    <euUniqueID>
        <euUniqueIDTypeCode>3</euUniqueIDTypeCode>
        <unitPacketLevelUniqueIdentifier>5vPxnb8&n2h501234567890128</unitPacketLevelUniqueIdentifier>
        <unitPacketLevelUniqueIdentifier>5vPxbrJk3th501234567890128</unitPacketLevelUniqueIdentifier>
        <aggregatedLevelUniqueIdentifier>106141412345678908</aggregatedLevelUniqueIdentifier>
    </euUniqueID>
</invoiceLineItem>
</invoice>
</invoice:invoiceMessage>

```

3.9.2 EDI - EPO – (4.2) Issuing of the order number

3.9.2.1 Description

Adds a purchase order event to a UI.

Field	Comments	Data Type	Cardinality	Priority	Values	XML
Message_Type	Identification of message type	Text	S	M	4-2	<orderTypeCode>220</orderTypeCode>
EO_ID	Economic operator identifier code of the submitting entity	EOID	S	M		<contentOwner> <gln>4098765000010</gln> <additionalPartyIdentification additionalPartyIdentificationTypeCode="EOID">5v1_4098765000010</additionalPartyIdentification> </contentOwner>
Event_Time	Time of event occurrence	Time(s)	S	M		<creationDateTime>2019-04-11T08:00:00.000-05:00</creationDateTime>
Order_Number	Number of the purchase order	Text	S	M		<entityIdentification>PO3352</entityIdentification>
Order_Date	Date of the purchase order	Date	S	M		<creationDateTime>2019-

						04-11T08:00:00.000-05:00</creationDateTime>
UI_Type	Identification of UI types covered by the purchase order (recorded at the highest level of available aggregation)	Integer	S	M	1 – only unit packet level UIs 2 – only aggregated level UIs 3 – both unit packet and aggregated level UIs	<euUniqueIDTypeCode>3</euUniqueIDTypeCode>
upUIs	List of unit packet level UIs covered by the purchase order	upUI(L)	M	M, if UI_Type = 1 or 3		<unitPacketLevelUniqueIdentifier>5vY)<&Jp3*j701234567543215</unitPacketLevelUniqueIdentifier> <unitPacketLevelUniqueIdentifier>5vPxbrJk3th501234567543215</unitPacketLevelUniqueIdentifier>
aUIs	List of aggregated level UIs covered by the purchase order	aUI	M	M, if UI_Type = 2 or 3		<aggregatedLevelUniqueIdentifier>106141412345678908</aggregatedLevelUniqueIdentifier>
Order_comment	Description of the reason for delayed recording of the purchase order	Text(5000)	S	O		<note languageCode="en">Check markings on cases, there was a problem with past orders. This is general information only, not to be processed by your system.</note>

3.9.2.2 EDI orderMessage Example

```
<?xml version="1.0" encoding="UTF-8"?>
<order:orderMessage xmlns:order="urn:gs1:ecom:order:xsd:3"
xmlns:sh="http://www.unece.org/cefact/namespaces/StandardBusinessDocumentHeader"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance" xsi:schemaLocation="urn:gs1:ecom:order:xsd:3
../Schemas/gs1/ecom/Order.xsd">
  <sh:StandardBusinessDocumentHeader>
    <sh:HeaderVersion>1.0</sh:HeaderVersion>
    <sh:Sender>
      <sh:Identifier Authority="GS1">5412345000013</sh:Identifier>
      <sh:ContactInformation>
        <sh:Contact>John Doe</sh:Contact>
        <sh:EmailAddress>John_Doe@purchasing.XYZretailer.com</sh:EmailAddress>
        <sh:FaxNumber>+1-212-555-1213</sh:FaxNumber>
        <sh:TelephoneNumber>+1-212-555-2122</sh:TelephoneNumber>
        <sh:ContactTypeIdentifier>Buyer</sh:ContactTypeIdentifier>
      </sh:ContactInformation>
    </sh:Sender>
  </sh:StandardBusinessDocumentHeader>
</order:orderMessage>
```

```

</sh:Sender>
<sh:Receiver>
  <sh:Identifier Authority="GS1">4098765000010</sh:Identifier>
  <sh:ContactInformation>
    <sh:Contact>Mary Smith</sh:Contact>
    <sh:EmailAddress>Mary_Smith@widgets.com</sh:EmailAddress>
    <sh:FaxNumber>+1-312-555-1214</sh:FaxNumber>
    <sh:TelephoneNumber>+1-312-555-2125</sh:TelephoneNumber>
    <sh:ContactTypeIdentifier>Seller</sh:ContactTypeIdentifier>
  </sh:ContactInformation>
</sh:Receiver>
<sh:DocumentIdentification>
  <sh:Standard>GS1</sh:Standard>
  <sh:TypeVersion>3.4</sh:TypeVersion>
  <sh:InstanceIdentifier>100002</sh:InstanceIdentifier>
  <sh:Type/>
  <sh:MultipleType>false</sh:MultipleType>
  <sh:CreationDateAndTime>2019-04-11T08:00:01.000-05:00</sh:CreationDateAndTime>
</sh:DocumentIdentification>
</sh:StandardBusinessDocumentHeader>
<order>
  <creationDateTime>2019-04-11T08:00:00.000-05:00</creationDateTime>
  <documentStatusCode>ORIGINAL</documentStatusCode>
  <orderIdentification>
    <entityIdentification>PO3352</entityIdentification>
    <contentOwner>
      <gln>5412345000013</gln>
    </contentOwner>
    <additionalPartyIdentification>
      <additionalPartyIdentificationTypeCode="EOID">5v1_5412345000013</additionalPartyIdentification>
    </additionalPartyIdentification>
    </contentOwner>
    </orderIdentification>
    <orderTypeCode>220</orderTypeCode>
    <isOrderFreeOfExciseTaxDuty>false</isOrderFreeOfExciseTaxDuty>
    <note languageCode="en">Check markings on cases, there was a problem with past orders. This is general
information only, not to be processed by your system.</note>
    <buyer>
      <gln>5412345000013</gln>
    </buyer>
    <seller>
      <gln>4098765000010</gln>
    </seller>
    <orderLogisticalInformation>
      <shipTo>
        <gln>5412345000037</gln>
      </shipTo>
      <orderLogisticalDateInformation>
        <requestedDeliveryDateTime><date>2011-04-11</date></requestedDeliveryDateTime>
      </orderLogisticalDateInformation>
    </orderLogisticalInformation>
    <orderLineItem>
      <lineItemNumber>1</lineItemNumber>
      <requestedQuantity>2</requestedQuantity>
      <netPrice currencyCode="EUR">10</netPrice>
      <transactionalTradeItem>
        <gtin>01234567543215</gtin>
      </transactionalTradeItem>
      <euUniqueID>

```

```

    <euUniqueIDTypeCode>3</euUniqueIDTypeCode>
<unitPacketLevelUniqueIdentifier>5vY<&Jp3*j701234567543215</unitPacketLevelUniqueIdentifier>
<unitPacketLevelUniqueIdentifier>5vPxbrJk3th501234567543215</unitPacketLevelUniqueIdentifier>
<aggregatedLevelUniqueIdentifier>106141412345678908</aggregatedLevelUniqueIdentifier>
    </euUniqueID>
    <leviedDutyFeeTax>
      <dutyFeeTaxAmount currencyCode="EUR">3.8</dutyFeeTaxAmount>
      <dutyFeeTaxBasisAmount currencyCode="EUR">20</dutyFeeTaxBasisAmount>
      <dutyFeeTaxPercentage>19.00</dutyFeeTaxPercentage>
      <dutyFeeTaxTypeCode>VAT</dutyFeeTaxTypeCode>
    </leviedDutyFeeTax>
  </orderLineItem>
<orderLineItem>
  <lineItemNumber>2</lineItemNumber>
  <requestedQuantity>2</requestedQuantity>
<netPrice currencyCode="EUR">20</netPrice>
  <transactionalTradeItem>
    <gtin>01234567890128</gtin>
  </transactionalTradeItem>
  <euUniqueID>
    <euUniqueIDTypeCode>3</euUniqueIDTypeCode>
    <euUniqueIDTypeCode>3</euUniqueIDTypeCode>
<unitPacketLevelUniqueIdentifier>5vPxnb8&n2h501234567890128</unitPacketLevelUniqueIdentifier>
<unitPacketLevelUniqueIdentifier>5vPxbrJk3th501234567890128</unitPacketLevelUniqueIdentifier>
<aggregatedLevelUniqueIdentifier>106141412345678908</aggregatedLevelUniqueIdentifier>
    </euUniqueID>
    <leviedDutyFeeTax>
      <dutyFeeTaxAmount currencyCode="EUR">7.6</dutyFeeTaxAmount>
      <dutyFeeTaxBasisAmount currencyCode="EUR">40</dutyFeeTaxBasisAmount>
      <dutyFeeTaxPercentage>19.00</dutyFeeTaxPercentage>
      <dutyFeeTaxTypeCode>VAT</dutyFeeTaxTypeCode>
    </leviedDutyFeeTax>
  </orderLineItem>
</order>
</order:orderMessage>

```

3.9.3 EDI - EPR – (4.3) Receipt of the payment

3.9.3.1 Description

Adds a payment record event to a UI.

Field	Comments	Data Type	Cardinality	Priority	Values	XML
Message_Type	Identification of message type	Text	S	M	4-3	<settlementHandlingTypeCode>REMITTANCE_ONLY</settlementHandlingTypeCode>
EO_ID	Economic operator identifier code of	EOID	S	M		<contentOwner>

	the submitting entity					<gln>4098765000010</gln> <additionalPartyIdentification additionalPartyIdentificationTypeCode="EOID">5v1_4098765000010</additionalPartyIdentification> </contentOwner>
Event_Time	Time of event occurrence	Time(s)	S	M		<creationDateTime>2019-04-11T08:15:00.000-05:00</creationDateTime>
Payment_Date	Date of the payment receipt	Date	S	M		<creationDateTime>2019-04-11T11:00:00.000-05:00</creationDateTime>
Payment_Type	Type of payment	Integer	S	M	1 – bank transfer 2 – bank card 3 – cash 4 – other	<paymentMethodCode>BANK_GIRO</paymentMethodCode>
Payment_Amount	Amount of the payment	Decimal	S	M		<totalAmountcurrencyCode="EUR">1.99</totalAmount>
Payment_Currency	Currency of the payment	Currency	S	M		<totalAmountcurrencyCode="EUR">1.99</totalAmount>
Payment_Payer 1	Identification if the payer is located in the EU	Boolean	S	M	0 – No 1 – Yes	<isPayerBasedInEu>>false</isPayerBasedInEu>
Payment_Payer 2	Identity of the payer	E OID	S	M, if Payment_Payer1 = 1		<additionalPartyIdentificationadditionalPartyIdentificationTypeCode="EOID">5v1_4098765000010</additionalPartyIdentification>
Payer_Name	Payer's registered legal name	Text(5000)	S	M, if Payment_Payer1=0		<name>GS1 AISBL</name>
Payer_Address	Payer's address – street name, house number, postal code and city	Text(5000)	S	M, if Payment_Payer1=0		<streetAddressOne>Avenue Louise 326</streetAddressOne> <streetAddressTwo>Ixelles</streetAddressTwo> <city>Bruxelles</city> <postalCode>1050</postalCode>
Payer_CountryReg	Payer's country of registration	Country	S	M, if Payment		<countryCode>BE</countryCode>

				_Payer1 = 0		
Payer_TAX_N	Payer's tax registration number	Text(5000)	S	M, if Payment_Payer1 = 0		<dutyFeeTaxRegistrationID>TAX0001</dutyFeeTaxRegistrationID>
Payment_Recipient	Identity of the recipient	EOID	S	M		payee<additionalPartyIdentificationadditionalPartyIdentificationTypeCode="EOID">5v1a_541234500013</additionalPartyIdentification>
Payment_Invoice	Indication if the payment corresponds to the existing invoice	Boolean	S	M	0 – No 1 – Yes	<isPaymentCorrespondingToExistingInvoice>true</isPaymentCorrespondingToExistingInvoice>
Invoice_Paid	Number of the invoice paid with the payment	Text(5000)	S	M, if Payment_Invoice = 1		<entityIdentification>IN11-548</entityIdentification>
UI_Type	Identification of UI types covered by the payment (recorded at the highest level of available aggregation)	Integer	S	M, if Payment_Invoice = 0	1 – only unit packet level UIs 2 – only aggregated level UIs 3 – both unit packet and aggregated level UIs	<euUniqueIDTypeCode>3</euUniqueIDTypeCode>
upUIs	List of unit packet level UIs covered by the payment	upUI(L)	M	M, if Payment_Invoice = 0 and UI_Type = 1 or 3		<unitPacketLevelUniqueIdentifier>5vY)<&Jp3*j701234567543215</unitPacketLevelUniqueIdentifier> <unitPacketLevelUniqueIdentifier>5vPxbrJk3th501234567890128</unitPacketLevelUniqueIdentifier>
aUIs	List of aggregated level UIs covered by the payment	aUI	M	M, if Payment_Invoice = 0 and UI_Type = 2 or 3		<aggregatedLevelUniqueIdentifier>106141412345678908</aggregatedLevelUniqueIdentifier>
Payment_comment	Comments by the reporting entity	Text(5000)	S	O		<note languageCode="en">A comment or note about this settlement</note>

3.9.3.2 EDI settlementMessage Example

```
<?xml version="1.0" encoding="UTF-
8"?><settlement:settlementMessagexmlns:settlement="urn:gs1:ecom:settlement:xsd:3"
xmlns:sh="http://www.unece.org/cefact/namespaces/StandardBusinessDocumentHeader"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:schemaLocation="urn:gs1:ecom:settlement:xsd:3 ../Schemas/gs1/ecom/Settlement.xsd">
<sh:StandardBusinessDocumentHeader>
<sh:HeaderVersion>1.0</sh:HeaderVersion>
<sh:Sender>
<sh:Identifier Authority="GS1">5412345000013</sh:Identifier>
<sh:ContactInformation>
<sh:Contact>John Doe</sh:Contact>
<sh:EmailAddress>John\_Doe@purchasing.XYZretailer.com</sh:EmailAddress>
<sh:FaxNumber>+1-212-555-1213</sh:FaxNumber>
<sh:TelephoneNumber>+1-212-555-2122</sh:TelephoneNumber>
<sh:ContactTypeIdentifier>Buyer</sh:ContactTypeIdentifier>
</sh:ContactInformation>
</sh:Sender>
<sh:Receiver>
<sh:Identifier Authority="GS1">4098765000010</sh:Identifier>
<sh:ContactInformation>
<sh:Contact>Mary Smith</sh:Contact>
<sh:EmailAddress>Mary\_Smith@widgets.com</sh:EmailAddress>
<sh:FaxNumber>+1-312-555-1214</sh:FaxNumber>
<sh:TelephoneNumber>+1-312-555-2125</sh:TelephoneNumber>
<sh:ContactTypeIdentifier>Seller</sh:ContactTypeIdentifier>
</sh:ContactInformation>
</sh:Receiver>
<sh:DocumentIdentification>
<sh:Standard>GS1</sh:Standard>
<sh:TypeVersion>3.4</sh:TypeVersion>
<sh:InstanceIdentifier>xyz123456</sh:InstanceIdentifier>
<sh:Type/>
<sh:MultipleType>false</sh:MultipleType>
<sh:CreationDateAndTime>2006-01-10T12:00:01.000-05:00</sh:CreationDateAndTime>
</sh:DocumentIdentification>
</sh:StandardBusinessDocumentHeader>
<settlement>
<creationDateTime>2019-04-11T11:00:00.000-05:00</creationDateTime>
<documentStatusCode>ORIGINAL</documentStatusCode>
<settlementIdentification>
<entityIdentification>SE25709</entityIdentification>
<contentOwner>
<gln>5412345000013</gln>
```



```

<additionalPartyIdentificationadditionalPartyIdentificationTypeCode="EOID">5v1_54123450
00013</additionalPartyIdentification>
</contentOwner>
</settlementIdentification>

```

```

<settlementHandlingTypeCode>REMITTANCE_ONLY</settlementHandlingTypeCode>

```

```

<isPayerBasedInEu>>false</isPayerBasedInEu>
<note languageCode="en">A comment or note about this settlement</note>
<payer>
<gln>5412345000013</gln>
<additionalPartyIdentificationadditionalPartyIdentificationTypeCode
="EOID">5v1_5412345000013</additionalPartyIdentification>
<address>
<city>Bruxelles</city>
<countryCode>BE</countryCode>
<name>GS1 AISBL</name>
<postalCode>1050</postalCode>
<streetAddressOne>Avenue Louise 326</streetAddressOne>
<streetAddressTwo>Ixelles</streetAddressTwo>
</address>
<dutyFeeTaxRegistration>
<dutyFeeTaxRegistrationID>SE556667677001</dutyFeeTaxRegistrationID>
</dutyFeeTaxRegistration>
</payer>
<payee>
<gln>4098765000010</gln>
<additionalPartyIdentificationadditionalPartyIdentificationTypeCode
="EOID">5v1a4098765000010</additionalPartyIdentification>
<financialInstitutionInformation>
<financialAccount>
<financialAccountNumber>NL62510007547061</financialAccountNumber>
<financialAccountNumberTypeCode>CHECKING_ACCOUNT</financialAccountNumberTypeCo
de>
<financialAccountName>DUTCHBANK</financialAccountName>
</financialAccount>
</financialInstitutionInformation>
</payee>
<paymentMethod>
<paymentMethodCode>BANK_GIRO</paymentMethodCode>
</paymentMethod>
<settlementLineItem>
<lineItemNumber>1</lineItemNumber>
<amountPaidcurrencyCode="EUR">71.4</amountPaid>
<isPaymentCorrespondingToExistingInvoice>true</
isPaymentCorrespondingToExistingInvoice>

```

```

<settlementParty>
<gln>5412345000013</gln>
<partyRoleCode>BUYER</partyRoleCode>
</settlementParty>
<invoice>
<entityIdentification>IN19-548</entityIdentification>
<contentOwner>
<gln>4098765000010</gln>
</contentOwner>
<invoiceTypeCode>INVOICE</invoiceTypeCode>
</invoice>
</settlementLineItem>
<settlementLineItem>
<lineItemNumber>1</lineItemNumber>
<amountPaidcurrencyCode="EUR">380</amountPaid>
<originalAmountcurrencyCode="EUR">480</originalAmount>
<settlementParty>
<gln>5412345000174</gln>
<partyRoleCode>STORE</partyRoleCode>
</settlementParty>
<invoice>
<entityIdentification>IN11-549</entityIdentification>
<contentOwner>
<gln>4098765000010</gln>
</contentOwner>
<invoiceTypeCode>INVOICE</invoiceTypeCode>
</invoice>
<euUniqueID>
<euUniqueIDTypeCode>3</euUniqueIDTypeCode>
<unitPacketLevelUniqueIdentifier>5vY)<&Jp3*j701234567543215</unitPacketLevelUniqueIdentifier>
<unitPacketLevelUniqueIdentifier>5vPxbrJk3th501234567890128</unitPacketLevelUniqueIdentifier>
<aggregatedLevelUniqueIdentifier>106141412345678908</aggregatedLevelUniqueIdentifier>
</euUniqueID>
</settlementLineItem>
</settlement>
</settlement:settlementMessage>

```

3.10 Recall

3.10.1 RCL – (5.0) Recalls of requests, operational and transactional messages

3.10.1.1 Description

Given a recall id ("Code" in the return of any message) The caller can mark that event invalid.

This is possible for message types 2-1, 2-2, 3-1 to 3-7, 4-1, 4-2 and 4-3)

3.10.1.2 Description of the fields

Recall – request					
Field	Description	Data Type	Cardinality	Priority	Values
BasicInfo_Req	Block of basic information elements	Component << Basic Information Request >>	S	M	Message_Type = RCL
EO_ID	Economic operator identifier code of the submitting entity	EOID	S	M	
Message_Time_Long	Message sending Time	Time(L)	S	M	
Recall_Reason_1	Reason for recalling the original message	Integer	S	M	See RecallReasonType
Recall_Reason_2	Description of the reason for recalling the original message	Text(5000)	S	M, if Recall_Reason_1 = 3 (other reason)	
Recall_Reason_3	Any additional explanations on the reason for recalling the original message	Text(5000)	S	O	

3.10.1.3 Response:

Recall – response					
Field	Description	Data Type	Cardinality	Priority	Values
BasicInfo_Resp	Block of basic information elements	Component << Basic Information Response >>	S	M	Message_Type = RCL

3.10.1.4 Request sample

```
{
  "EO_ID": "QCUKR+1AB020054",
  "Message_Time_Long": "2019-03-20T14:16:45Z",
  "RecallReason1": 1,
  "RecallReason2": 1,
  "RecallReason3": "Comments",
  "Message_Type": "RCL",
  "Code": "873345b2-882f-4064-91f0-90669b46c30a"
}
```

3.10.1.5 Successful response sample

HTTP Status 202

```
{
  "Code": "873345b2-882f-4064-91f0-90669b46c30a",
  "Message_Type": "RCL",
  "Error": false,
  "Errors": null,
  "Checksum": "G6HF5H"
}
```

3.10.1.6 Error response sample

HTTP status	Error Code	Error Description
<< Common response code >>		
400	RECALL_AFTER_ONE_WORKING_DAY	For requests of unit level or aggregated level UIs (ISU, IRU, ISA, IRA), recalls can be performed up to one working day after the original message.
400	RECALL_NOT_LAST_EVENT	Recall code not found: ERROR: The provided recall code does not exist. Recallcode not the last event ERROR: Please note that a recall can only be performed on valid messages that referred to UIs which were not later used in other messages.

3.11 EPCIS - Recall

3.11.1 EPCIS - RCL – (5) Recalls of requests, operational messages

3.11.1.1 Description

```
<?xml version="1.0"?>
<epcis:EPCISDocument xmlns:epcis="urn:epcglobal:epcis:xsd:1" schemaVersion="1.2"
  xmlns:fit="https://gs1.org/cbv/fit" xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xsi:schemaLocation="urn:epcglobal:epcis:xsd:1 EPCglobal-epcis-1_2.xsd"
  creationDate="2019-03-11T16:46:00.000Z">

  <EPCISBody>
    <EventList>

      <!-- ERROR DECLARATION (5 - Recalls of requests, operational and transactional
      messages) example follows -->
```

```

<ObjectEvent>
  <eventTime>2018-12-04T13:13:00.000+01:00</eventTime>
  <eventTimeZoneOffset>+01:00</eventTimeZoneOffset>
  <baseExtension>
    <!-- including UUID of original, erroneous event -->
    <eventID>urn:uuid:dc58edda-c24f-4416-9dc9-a5f41e58b76f</eventID>
    <errorDeclaration>
      <declarationTime>2018-12-07T21:21:00.000+01:00</declarationTime>
      <reason>urn:epcglobal:cbv:er:did_not_occur</reason>
    </errorDeclaration>
  </baseExtension>
  <epcList>
    <epc>urn:epc:id:sscc:1234567.0123456789</epc>
  </epcList>
  <action>OBSERVE</action>
  <bizStep>urn:epcglobal:cbv:bizstep:shipping</bizStep>
  <disposition>urn:epcglobal:cbv:disp:in_transit</disposition>
  <readPoint>
    <id>urn:epc:id:sgln:1234567.54321.0</id>
    <fit:fid>(7040)5v9_(414)1234567543215</fit:fid>
  </readPoint>
  <fit:messageType>3-3</fit:messageType>
  <fit:uiType>2</fit:uiType>
  <fit:eoid epc="urn:epc:id:pgl:1234567.89012"
gs1ElementString="(7040)5f(417)1234567890128"/>
  <fit:destinationID1>2</fit:destinationID1>
  <fit:destinationIDList>
    <fit:destinationID type="2" epc="urn:epc:id:sgln:0614141.00777.0"
gs1ElementString="(7040)5v9_(414)0614141007776"/>
    <fit:destinationID type="2" epc="urn:epc:id:sgln:0614141.00778.0"
gs1ElementString="(7040)5v9_(414)0614141007783"/>
  </fit:destinationIDList>
  <fit:destinationID5name>Ramos Tobacco</fit:destinationID5name>
  <fit:destinationID5streetAddressOne>Plaza de Espaga,
1</fit:destinationID5streetAddressOne>
  <fit:destinationID5streetAddressTwo/>
  <fit:destinationID5city>Mostoles</fit:destinationID5city>
  <fit:destinationID5postalCode>28934</fit:destinationID5postalCode>
  <fit:destinationID5countryCode>ES</fit:destinationID5countryCode>
  <fit:transportMode>3</fit:transportMode>
  <fit:transportVehicle>(E)IXX359</fit:transportVehicle>
  <fit:transportCont2>(00)012345671234567893</fit:transportCont2>
  <fit:transportS1>>false</fit:transportS1>
  <fit:transportS2>(00)012345671234567893</fit:transportS2>
  <fit:emcsARC>12ES00000000006107577</fit:emcsARC>
  <fit:saadNumber>3649/92sample</fit:saadNumber>
  <fit:expDeclarationNumber>01ES45671234567893</fit:expDeclarationNumber>
  <fit:comment>5 Recalls of requests, operational and transactional
messages</fit:comment>
</ObjectEvent>
<!-- end of ERROR DELCARATION example -->
</EventList>
</EPCISBody>
</epcis:EPCISDocument>

```

3.12 Manufacturer interface

3.12.1 LDI Lookup Dispatch Interface

3.12.1.1 Context

Provide the manufacturer the ability to check the validity of the final dispatch messages (when the subsequent arrival message is expected to be sent to the router). Ensuring the successful reception of the goods by the distributors.

3.12.1.2 Scope

This interface ONLY allows the manufacturer to validate the accuracy of the reporting for the first dispatch that will be arrived by the supply chain reporting the arrival event through the Router.

The interface will not cover and therefore will not provide a response to

- Manufacturer internal dispatch events.
- Distributors dispatch events.

3.12.1.3 Approach

The Recallcode validation.

The Manufacturer will be able to

- Retrieve the **status of the dispatch** on the secondary repository. Allowing the confirmation that the primary has processed the dispatch message and transmitted it successfully to the Secondary repository.
- Confirm the **arrival status** at the distributor side by "simulating" the arrival process and provide the router response.

3.12.1.4 Response information

The Traceability response to the manufacturer request over the dispatch

3.12.1.4.1 Dispatch status

	Description
0	The recallcode of the dispatch message (3.3) is not present in the Secondary repository. The recallcode of the dispatch message (3.3) is present but the messages have been recalled successfully.
1	The recallcode of the dispatch message (3.3) is present in the Secondary repository and has been successfully processed.

3.12.1.4.2 Arrival status

The system will execute the reception validation controls.

The result of the validation controls will be provided in the arrival status.

	Description
null	When Dispatch_status = 0
0	The execution the reception validation controls encountered failed validation. At this point, the corresponding arrival message will result in the same validation errors.
1	The recallcode of the dispatch message (3.3) is present in the Secondary repository and has been successfully processed.

3.12.1.5 Daily Limit

The limit per manufacturer is set to 30 000 calls per day.

In case the daily limit per manufacturer is exceeded, the call will return a validation error.

HTTP status		
400	FAILED_VALIDATION	In case the maximum number of requests is reached

3.12.1.6 Description of the fields

Application and aggregation envelop event					
Field	Description	Data Type	Cardinality	Priority	Values
BasicInfo_Req	Block of basic information elements	Component << Basic Information Request >>	S	M	Message_Type = LDI
Message_Time_long	Message sending Time	Time(L)	S	M	
Dispatch_Code	Dispatch RecallCode		S	M	
Dispatch_EOID	EOID		S	M	

3.12.1.7 Response:

upUI application event – response					
Field	Description	Data Type	Cardinality	Priority	Values
BasicInfo_Resp	Block of basic information elements	Component << Basic Information Response >>	S	M	Message_Type = LDI
Validation_Time	Validation Timestamp		S	M	
Dispatch_Code	Dispatch RecallCode		S	M	
Dispatch_Status			S	M	
Arrival_Status	Response of the simulated arrival related to the dispatch				

3.12.1.8 Request sample

```
{
  "Message_Type": "LDI",
  "Code": null,
  "Dispatch_Code": "873345b2-882f-4064-91f0-90669b46c30a",
  "Dispatch_EOID": "AAAAAAA",
  "Message_Time_Long": "2019-03-20T14:16:45Z"
}
```


3.12.1.9 Successful response sample

HTTP Status 200

```
{
  "Code": "873345b2-882f-4064-91f0-90669b46c30a",
  "Message_Type": "LDI",
  "Dispatch_Code": "873345b2-882f-4064-91f0-90669b46c30a",
  "Validation_Time": "2019-03-20T14:16:45Z",
  "Dispatch_Status": 1,
  "Arrival_Status": {
    "Error": false,
    "Errors": null
  },
  "Error": false,
  "Errors": null,
  "Checksum": "G6HF5H"
}
```

3.12.1.1 Arrival Not Allowed response sample

Response status: 200

```
{
  "Validation_Time": "2021-03-15T12:08:53.0013823+00:00",
  "Dispatch_Code": "870935a0-64fc-55f8-b669-2e6cc09ed68b",
  "Dispatch_EOID": "I85B2J22DN7823851457TPULHSIDZR2735861466DPINXHLMJ",
  "Dispatch_Status": 1,
  "Arrival_Status": {
    "Error": 1,
    "Errors": [{
      "Error_Code": "ARRIVAL_NOTALLOWED",
      "Error_Descr": "ERROR: VAL_UI_ORD_ARRIVAL, Arrival not allowed because one or more of the UIs are already IN_STOCK in this or another location (IN_STOCK/ERP_DELIVERED)",
      "Error_InternalID": null,
      "Error_Data": null
    }]
  },
  "Code": "e7de7c5c-ce96-5753-a2fb-ed655349ce23",
  "Message_Type": "LDI",
  "Error": 0,
  "Errors": null,
  "Checksum": "4d5ddd222480fc8e2f87b2228a3cdde7"
}
```

3.12.1.2 Error response sample

HTTP status		
<< Common response code >>		
400	FAILED_VALIDATION	In case the maximum number of requests is reached
400	FAILED_VALIDATION	The EOID is not valid.
400	FAILED_VALIDATION	The field Dispatch_Code is linked to an event that is not covered by the LDI scope

3.12.1.3 LDI Validations clarification

3.12.1.3.1 Limit Validation

In order to protect the system a limit of 30k call has been defined per primary repository

In case the daily limit is exceeded, a validation error will be returned (http status 400)

HTTP status		
400	FAILED_VALIDATION	In case the maximum number of requests is reached

3.12.1.3.2 Dispatch_EOID existence check

Validate the existence of the EOID present in the request
In case of failure the answer is a 400

HTTP status		
400	FAILED_VALIDATION	The EOID is not valid.

3.12.1.3.3 EDP RecallCode Existence Validation

The first validation is done on the existence of the EDP in the secondary repository.

Condition:

- Recall code must exist

- Recall code must exist as received on secondary side ONLY (not router)
- Recall code must be for a Dispatch event EDP (Message_Type = EDP)
- Recall code has not be part of any recall events

in case one of the previous conditions is not met the LDI will return a success response with the Dispatch_Status = 0

HTTP status		
200	SUCCESS	Dispatch_Status = 0 (no dispatch event 3.3 with that RecallCode has been reported to the secondary repository)

3.12.1.3.4 EDP RecallCode LDI Authorisation

This step consist in checking if the EDP can be disclosed.

A number of limitations are implemented to avoid the manufacturer to access the information internal events as well as events from the supply chain

Conditions:

The LDI is limited to the Dispatch events from a source FID that belongs to the manufacturer (that is consuming the LDI) and the destination FID does not belong to the Manufacturer (meaning it sends the goods to a location outside of his custody)

- EDP must be for EU and have only one destination field filled (Destination_ID2)
- EDP Source Facility ID must be owned by an EO that is linked to a manufacturer
- EDP Source Facility ID and Destination Facility ID must not be the same
- EDP Source Facility ID and Destination Facility ID must not be linked to the same target primary

HTTP status		
400	FAILED_VALIDATION	The field Dispatch_Code is linked to an event that is not covered by the LDI scope

Note: These conditions might be updated in order to accommodate specific manufacturer distribution configuration including the use of 3PLs. Any update of these conditions will be communicated through the release notes.

4 List of Error Codes

4.1 Security errors

HTTP status	Error Code	Text Description
401	INVALID_OR_EXPIRED_TOKEN Related control: VAL_SEC_TOKEN	Error Descr: The incoming token is not valid or expired Comment: The security token has expired and should be renewed.

4.2 Processing errors

HTTP status	Error Code	Text Description
400	FAILED_VALIDATION Related control: VAL_FIE_REF VAL_MSG_XML	Error Descr: The field <XXX> should contain a valid <YYY> Error Descr for Circular Reference issue: The message contains UI values that form a circular reference Eg: The value for the field Aggregation_Type (XXX) is not in the defined set of values for AggregationType (YYY) (1 2 or 3) Comments: The values must match the values included in the set defined in the Data Dictionary. Concerning circular reference error: the UI mentioned in the event message is a parent of another UI present in the same message.
400	REQUIRED_FIELD_FAILED_VALIDATION Related controls: VAL_FIE_MAN VAL_MSG_JSON	Error Descr: The field <XXX> is required. VAL_FIE_MAN: Data missing in Mandatory field. Eg: field = "" VAL_MSG_JSON: Missing mandatory field. Eg: field = null or not present in the JSON
400	INVALID_MESSAGE_TYPE Related control: VAL_MSG_TYPE	Error Descr: Message type is unknown Comment: The type of Message you are using is not present in the Data Dictionary.
400	INVALID_SIGNATURE Related control:	Error Descr: Hash information not matching the message signature

	VAL_SEC_HASH	Comment: The validation of the HASH of the body of the message doesn't match the transmitted HASH information in the header X-OriginalHash.
400	MAX_LENGTH_FAILED_VALIDATION Related control: VAL_MSG_JSON	Error Descr: The field <XXX> should be a value with maximum length of <Y> Error Data: Field value Comment: The message doesn't follow the specifications defined in the Data Dictionary. The number of characters must remain under the max length.
400	MIN_LENGTH_FAILED_VALIDATION Related control: VAL_MSG_JSON	Error Descr: The field <XXX> should be a value with minimum length of <Y> Error Data: Field value Comment: The message doesn't follow the specifications defined in the Data Dictionary. The number of characters must remain above the min length.
400	ENTRY_LENGTH_FAILED_VALIDATION Related control: VAL_MSG_JSON	Error Descr: The field <XXX> should be a 2-dimensional array where each row contains <Y> elements Comment: The message doesn't follow the specifications defined in the Data Dictionary.
400	INVALID_INPUT_FORMAT Related controls: VAL_MSG_JSON VAL_FIE_FORMAT	Error Descr: see examples below Example for 3.3 message (dispatch - EDP): n/a is a permitted value for the field 'Transport_vehicle' only if Transport_mode = 0 Example for recall messages: Please note that a recall can not be performed on <XXX> messages. Comments: The message doesn't follow the specifications defined in the Data Dictionary. The body of the message contains at least one field in wrong format or does not correspond to a valid JSON message. Recall messages in particular cannot be performed on 2.1 messages (IRU),

		2.2 messages (IRA) and 2.3 messages (IDA)
400	PAYLOAD_NOT_UNIQUE Related control: VAL_MSG_DUPLICATE	Error Descr: The message should contain a payload which was not previously used Comment: The system already processed the same payload delivered in an earlier message. You cannot resend the same payload.
400	EXCISE_NUMBER_NOT_VALID Related control: VAL_MSG_JSON	Error Descr: The field 'EO_ExciseNumber2' should contain a valid excise number Error Data: Field value Comment: The format of the field EO_ExciseNumber2 doesn't match the Data Dictionary.
400	NON_COMPATIBLE_UIS Related control: VAL_MSG_JSON	Error Descr: the field 'upUI_2' should be compatible with 'upUI_1' Error Data: List of UI Comment: Activation failed as ordered list of UIs with timestamp, did not match short UIs.
400	NOT_THE_SAME_NUMBER_OF_ITEMS Related control: VAL_MSG_JSON	Error Descr: For 3.1 message (activation - EUA): The field 'upUI_1' should contain the same number of items as 'upUIs_2' For 4.1 message (invoice - EIV): The field 'Product_Items_2' should contain the same number of items as 'ProductIdentifiers' And The field 'Product_Price' should contain the same number of items as 'ProductIdentifiers' Comments: 3.1 message (activation - EUA): Activation failed as number of UI with timestamp, did not same number as short UIs. 4.1 message (invoice - EIV): message failed as the items contained int the fields 'Product_Items_2' and/or 'Product_Price' are/is not the same as the number of items in 'ProductIdentifiers'.
400	MULTIPLE_UID Related control: VAL_UI_MULT_MSG	Error Descr: The field 'upUI'/'aUI' contains duplicate values Error Data: List of UI

		Comment: Multiple duplicate UI present in the message lists. Message must contain only one occurrence of the same UI.
500	SYSTEM_ERROR	Error descr: Null Comment: The internal error ID should be provided to Dentsu support if required.

4.3 Validation Warning

HTTP status	Error Code	Text Description
299	OPERATION_WITHIN_24_HOURS Related control: VAL_EVT_24H	Warning Descr: Reporting events should be performed within 24 hours of the occurrence of the event (except dispatch and trans-loading events) Comment: You received this warning because this message has been reported late, i.e. more than 24 hours after the event time. Please note that the reporting time frame will be reduced to 3 hours starting from May 2028.
299	SHIPMENT_WITHIN_24_HOURS Related control: VAL_EVT_TIME	Warning Descr: The date/Time provided in the field 'Event_Time' should not be more than 24 hours ahead of the actual reporting time Comment: Dispatch and transloading events have to be reported within a time frame of 24 hours prior to the occurrence of the movement. Control is based on the "actual date – Event_Time" time difference.
299	UI_SEQUENCE_WARNING Related control: VAL_UI_ORD_SEQUENCE_WARNING	Warning Descr: <action> is not expected nor allowed when state is generated/deactivated/implicitly disaggregated Error Data: list of UI Comment: This error happens when you are trying to generate upUIs which are already existing in the Secondary, or to deactivate upUIs/aUIs already deactivated, or to deactivate aUIs already implicitly disaggregated.
299	UI_NOT_EXIST Related controls: VAL_UI_EXIST_UPUI VAL_UI_EXIST_AUI	Warning Descr: The field 'upUIs/aUIs' must contain elements that are already recorded and in one of the following states: Activated, Generated

		Error Data: list of UI Comment: This error is implemented for logistic actions, excluding UI activation. The most common reasons causing this message to occur are: a) the UI in question is a pre TPD/legacy UI never reported to the Secondary, b) the UI in question is a new UI not yet reported to the Secondary, c) The UI in question has not been encoded or decoded in line with the existing formatting instructions VAL_UI_EXIST_AUI Logistic action is not expected nor allowed if a UI does not exist (has not been part of an EPA message as a parent). VAL_UI_EXIST_UPUI Logistic action is not expected nor allowed if a UI does not exist (has not been part of any IRU message).
--	--	--

4.4 Validation errors

HTTP status	Error Code	Text Description
400	CANNOT_ROUTE Related control: CANNOT_ROUTE	Error Descr: This message cannot be routed Comment: The IRU message cannot be routed to the corresponding primary repository. The ID Issuer should contact the primary provider and ensure that the EOID is correctly configured and pointing to the corresponding primary repository.
400	UI_NOT_VALID Related controls: VAL_UI_EXIST_UPUI_SEQ VAL_UI_EXIST_AUI_SEQ	Error Descr: <action> is not expected nor allowed when the pack has not been part of an application or an aggregation Error Data: list of UI Comment: Action on upUI is not expected nor allowed when the upUI has not been applied. Action on aUI is not expected nor allowed when the aUI has not been aggregated
400	UIS_APPLICATION_ERROR Related controls: VAL_UI_EXIST_APP	Error Descr for 3.1 message (activation - EUA): Unique Identifier application on unit pack is not expected nor allowed when pack

	VAL_UI_DUPLICATE_APP	does not exist or has been reported to be already applied Error descr for 2.3 message (deactivation - IDA): Deactivation of upUI/aUI is not expected nor allowed when upUI/aUI does not exist Error Data: list of UI Comment: this error is generated when trying to activate/deactivate UIs which are not recorded in the Secondary or which have already received an application event.
400	UI_DEACTIVATED Related controls: VAL_UI_ORD_REACTIVATION VAL_UI_ORD_DEACTIVATED	Error Descr for 3.1 messages (activation - EUA): Unique identifier application on unit pack is not expected nor allowed once the unique identifier has been deactivated Error Descr for other logistic actions: <Action> is not expected nor allowed once the unique identifier has been deactivated Error Data: list of UI Comment: The action you want to perform is not expected nor allowed after the UI has been deactivated with the 2.3 message.
400	MULTIPLE_AGGREGATION Related control: VAL_UI_ORD_AGG_MULT	Error Descr: Aggregation is not expected nor allowed when the pack is considered as aggregated or implicitly disaggregated Error Data: list of UI Comment: Multiple aggregation identified for an aUI (as a parent) without having an explicit disaggregation of this aUI.
400	UI_ALREADY_DISAGGREGATED Related controls: VAL_UI_ORD_DISAGG VAL_UI_ORD_IMPLDISAGG	Error Descr: <action> is not expected nor allowed once the pack has been made explicitly available for aggregation after disaggregation Error Data: list of UI Comment: an aUI that has been disaggregated (explicitly or implicitly) cannot be part of any product movement prior of being aggregated.
400	LOCATION_MISMATCH Related controls: VAL_UI_ORD_AGG_FID VAL_UI_ORD_DISPATCH	Error Descr: the FID must match with the location state of the reported unique identifiers Error Data: list of UI Comment: VAL_UI_ORD_AGG_FID

		All the goods must have been produced or reported to be in stock in the location where they are aggregated / disaggregated. VAL_UI_ORD_DISPATCH All the goods must have been produced or reported to be in stock in the location from which they are i dispatched.
400	FID_MISMATCH Related Control: VAL_UI_FID_APP	Error Descr: the FID must match the FID specified in the meta data of unique identifiers Comment: UI application in this location is not expected nor allowed as this location is not the one of the 2.1 message. Error Data: list of UI
400	ARRIVAL_NOTALLOWED Related Control: VAL_UI_ORD_ARRIVAL VAL_UI_ORD_ARRIVAL_RETURN	Error Descr: <action> not expected nor allowed when the pack is considered as in stock within EU facility following an application, arrival or return Error Data: list of UI Comment: arrival in EU facility is not expected nor allowed when the UI is considered as 'in stock' in a non-retail facility , meaning that a UI must have been part of a prior reported dispatch or transloading event before having an arrival It is not allowed to arrive multiple times the same UIs. <u>Exceptions:</u> Imported products are allowed for arrival in EU facility without having any prior dispatch or transloading
400	UI_SEQUENCE_ERROR Related control: VAL_UI_ORD_SEQUENCE	Error descr: <action> is not expected nor allowed when/once <state> Error Data: list of UI Comment: this is a generic sequence validation error caused by a message sent out of the permitted sequence. In particular, an implicit disaggregation in transit is not allowed, meaning that the reporting of an arrival must be done with reference to the same UI(s) as reported for the purpose of preceding dispatch/transloading. Example for a 3.3 message (dispatch):

		<i>Dispatch from EU for delivery to retail destination is not expected nor allowed when the pack has been reported as dispatched for delivery to retail destination</i> (DISPATCHED_EU_FIXED_QT_RETAIL/EDP_EU_FIXED_QT_RETAIL) In this case, the dispatch is failing because it is including UIs which are in state dispatched Example for a 3.7 message (report of delivery through Vending Van) <i>Report of EU delivery with a vending van to retail outlet destination is not expected nor allowed when the pack has not been previously reported as dispatched for VV delivery</i> (DISPATCHED_EU_FIXED_QT_RETAIL/EVR) In this case, the delivery through Vending Van is not allowed because the previous event is a dispatch to a facility with delivery of fixed quantity. It should have been a dispatch with delivery with Vending Van.
400	UI_EXPIRED Related control: VAL_UI_EXPIRY	Error Descr: Some or all unique identifiers listed in the message have expired Error Data: list of UI Comment: Validation if the application or the aggregation date doesn't exceed the 6 months period after the generation of unique identifiers by the ID issuers.
400	EOID_NOT_EXIST_OR_ACTIVE Related controls: VAL_ENT_EXIST_EOID VAL_ENT_ACTIVE_EOID	Error Descr: EOID mentioned in the field 'EO_ID' is not marked as active in the repository Error Data: EOID Comment: The field 'EO_ID' must contain elements that are already recorded and active.
400	FID_NOT_EXIST_OR_ACTIVE Related controls: VAL_ENT_EXIST_FID VAL_ENT_ACTIVE_FID	Error Descr: FID mentioned in the field 'F_ID' is not marked as active in the repository Error Data: FID Comment: The field 'F_ID' must contain elements that are already recorded and active.
400	MID_NOT_EXIST_OR_ACTIVE Related controls: VAL_ENT_EXIST_MID VAL_ENT_ACTIVE_MID	Error Descr: MID mentioned in the field 'M_ID' is not marked as active in the repository Error Data: MID Comment: The field 'M_ID' must contain elements that are already recorded and active.
400	FID_NOT_RELATED_TO_EOID Related control:	Error Descr: There is no existing relation recorded between FID mentioned in the field 'F_ID' and a EOID

	VAL_ENT_REL_EOID_FID	Comment: There is no existing relation recorded between FID mentioned in the field "F_ID" and an EOID.
400	MID_NOT_RELATED_TO_FID Related control: VAL_ENT_REL_FID_MID	Error Descr: There is no existing relation recorded between MID mentioned in the field 'M_ID' and a FID Comment: there is no existing relation recorded between MID mentioned in the field "M_ID" and a FID.
400	CODE_NOT_UNIQUE Related controls: VAL_MSG_CODE_DUPLICATE VAL_RECALL_EXIST	Error Descr: The field 'Recall_Code' must contain a value which was not previously used Comment: The recall code provided has been used before. For recall messages, you cannot recall twice on the same recall code if the previous recall message succeeded.
400	CODE_NOT_EXIST Related control: VAL_RECALL_EXIST	Error Descr: The field 'Recall_Code' must contain elements that are already recorded Comment: The recall code provided has not been found into the secondary.
400	RECALL_NOT_LAST_EVENT Related control: VAL_RECALL_LAST	Error Descr: Please note that a recall can only be performed on valid messages that referred to UIs which were not later used in other messages. Error Data: list of pair (UI @ Previous RecallCode) Comment: recalls can only be performed on last event.